

Diethylene glycol monobutyl ether solution 100.3 g/l technical grade denatured with MEK in ethanol s								
Revision date: 06.03.2024	Product code: 0473)	Page 1 of 13					
SECTION 1: Identification of the substance/mixture and of the company/undertaking								
1.1. Product identifier Diethylene glycol monobutyl eth	er solution 100.3 g/l technical grade de	natured with MEK in ethanol s						
UFI:	WV3E-R0R9-U008-MX1X							
1.2. Relevant identified uses of the su	bstance or mixture and uses advised	l against						
Professional uses: Public domai Uses advised against	ces as such or in preparations at indus n (administration, education, entertainr							
Do not use for private purposes								
<u>1.3. Details of the supplier of the safe</u> Company name: Street: Place:	<u>ty data sheet</u> AnalytiChem GmbH ACD Stempelstraße 6 D-47167 Duisburg							
Telephone: E-mail: Contact person: E-mail: Internet: Responsible Department:	0203/5194-0 info@analytichem.de Abteilung Produktsicherheit produktsicherheit@analytichem.de www.analytichem.de Abteilung Produktsicherheit	Telefax: 0203/5194-290 Telephone: 0203/5194-107/117						
1.4. Emergency telephone For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, number: Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted) Further Information								

Further Information

inapplicable, this product is a mixture REACH registration number see section 3

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation Flam. Liq. 2; H225

Eye Irrit. 2; H319

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP	Regulation
Signal	word:

Pictograms:

Danger





Hazard statements H225 H319

Highly flammable liquid and vapour. Causes serious eye irritation.



Revision date: 06.03.2024

according to UK REACH Regulation

Diethylene glycol monobutyl ether solution 100.3 g/l technical grade denatured with MEK in

Product code: 04739

ethanol s

Page 2 of 13

Precautionary statements

countionaly statemen	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P280	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name						
	EC No	Index No	Index No REACH No				
	Classification (GB CLP Regulation)						
64-17-5	ethanol						
	200-578-6	603-002-00-5	01-2119457610-43				
	Flam. Liq. 2, Eye Irrit. 2;	H225 H319					
112-34-5	5 2-(2-butoxyethoxy)ethanol						
	203-961-6	603-096-00-8	01-2119475104-44				
	Eye Irrit. 2; H319						

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity				
	Specific Conc. Limits, M-factors and ATE						
64-17-5	200-578-6	200-578-6 ethanol					
	inhalation: LC50 = 124,7 mg/l (vapours); oral: LD50 = 10470 mg/kg Eye Irrit. 2; H319: >= 50 - 100						
112-34-5	203-961-6	203-961-6 2-(2-butoxyethoxy)ethanol					
	dermal: LD50 = 2764 mg/kg; oral: LD50 = 2410 mg/kg						

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information No data available

After inhalation

Provide fresh air. Call a doctor if you feel unwell.



Diethylene glycol monobutyl ether solution 100.3 g/l technical grade denatured with MEK in

ethanol s

Revision date: 06.03.2024

Product code: 04739

Page 3 of 13

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Never give anything by mouth to an unconscious person or a person with cramps.

Rinse mouth immediately and drink plenty of water.

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

4.2. Most important symptoms and effects, both acute and delayed

Irritant Dizziness The product causes narcotic-like effects. Inebriation Vomiting

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray jet, Carbon dioxide (CO2), Foam, Extinguishing powder.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquid.

Vapours are heavier than air, spread along floors and form explosive mixtures with air. Hazardous combustion products In case of fire may be liberated: Carbon dioxide (CO2) Carbon monoxide Beware of reignition.

5.3. Advice for firefighters

Remove persons to safety. Do not inhale explosion and combustion gases.

Avoid contact with skin, eyes and clothes.

In case of fire: Wear self-contained breathing apparatus.

Use water spray jet to protect personnel and to cool endangered containers.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Suppress gases/vapours/mists with water spray jet. Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.



Diethylene glycol monobutyl ether solution 100.3 g/l technical grade denatured with MEK in

ethanol s

Revision date: 06.03.2024

Product code: 04739

Page 4 of 13

For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment. Avoid contact with skin, eyes and clothes. Remove persons to safety. Emergency procedures Consult an expert Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains. The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration. Danger of explosion

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation. Do not breathe dust/fume/gas/mist/vapours/spray. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care. When using do not eat, drink, smoke, sniff. Keep container tightly closed. Use personal protection equipment. Use extractor hood (laboratory). Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse. If handled uncovered, arrangements with local exhaust ventilation have to be used. Draw up and observe skin protection programme.



Diethylene glycol monobutyl ether solution 100.3 g/l technical grade denatured with MEK in

ethanol s

Revision date: 06.03.2024

Product code: 04739

Page 5 of 13

Wash hands and face before breaks and after work and take a shower if necessary.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances. national regulations

Further information on storage conditions

Vapours may form explosive mixtures with air.

7.3. Specific end use(s)

Laboratory use Laboratory chemical

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
112-34-5	2-(2-Butoxyethoxy)ethanol	10	67.5		TWA (8 h)	WEL
		15	101.2		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL

DNEL/DMEL values

CAS No	Substance						
DNEL type		Exposure route	Effect	Value			
64-17-5	ethanol						
Worker DNEL,	long-term	inhalation	systemic	950 mg/m³			
Worker DNEL,	long-term	dermal	systemic	343 mg/kg bw/day			
Consumer DN	EL, long-term	inhalation	systemic	114 mg/m³			
Consumer DN	EL, long-term	dermal	systemic	206 mg/kg bw/day			
Consumer DN	EL, long-term	oral	systemic	87 mg/kg bw/day			
112-34-5	2-(2-butoxyethoxy)ethanol						
Worker DNEL,	long-term	inhalation	systemic	67,5 mg/m³			
Worker DNEL,	long-term	inhalation	local	67,5 mg/m³			
Worker DNEL,	acute	inhalation	local	101,2 mg/m ³			
Worker DNEL,	long-term	dermal	systemic	83 mg/kg bw/day			
Consumer DN	EL, long-term	inhalation	systemic	40,5 mg/m ³			
Consumer DNEL, long-term		inhalation	local	40,5 mg/m ³			
Consumer DNEL, acute		inhalation	local	60,7 mg/m³			
Consumer DNEL, long-term		dermal	systemic	50 mg/kg bw/day			
Consumer DN	Consumer DNEL, long-term		systemic	5 mg/kg bw/day			



Diethylene glycol monobutyl ether solution 100.3 g/l technical grade denatured with MEK in

Revision date: 06.03.2024

ethanol s Product code: 04739

Page 6 of 13

PNEC values

CAS No	Substance	
Environment	tal compartment	Value
64-17-5	ethanol	
Freshwater		0,96 mg/l
Freshwater ((intermittent releases)	2,75 mg/l
Marine wate	r	0,79 mg/l
Freshwater s	sediment	3,6 mg/kg
Marine sedir	nent	2,9 mg/kg
Secondary p	oisoning	380 mg/kg
Micro-organi	isms in sewage treatment plants (STP)	580 mg/l
Soil		0,63 mg/kg
112-34-5	2-(2-butoxyethoxy)ethanol	
Freshwater		1,1 mg/l
Freshwater ((intermittent releases)	11 mg/l
Marine wate	r	0,11 mg/l
Freshwater s	sediment	4,4 mg/kg
Marine sedir	nent	0,44 mg/kg
Secondary p	poisoning	56 mg/kg
Micro-organi	isms in sewage treatment plants (STP)	200 mg/l
Soil		0,32 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: goggles.

Hand protection

Suitable examples are gloves of KCL GmbH, D-36124 Eichenzell, e-mail: vertrieb@kcl.de with the following specification (test according to EN 374):

By long-term hand contact Trade name/designation KCL 897 Butoject® Suitable material: Butyl caoutchouc (butyl rubber) 0,3 mm Wearing time with permanent contact: >480min

By short-term hand contact Trade name/designation KCL 730 Camatril® Velours Suitable material: NBR (Nitrile rubber) 0,4mm Wearing time with occasional contact (splashes): >120min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet supplied by us and for the designated use. When dissolving in or mixing with other substances and



Diethylene glycol monobutyl ether solution 100.3 g/l technical grade denatured with MEK in

Revision date: 06.03.2024

ethanol s Product code: 04739

Page 7 of 13

under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Environmental exposure controls

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration. Danger of explosion

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

	i. Information on basic physical and cher	nical properties	
	Physical state:	Liquid	
	Colour:	colourless	
	Odour:	like: Alcohol	
	Odour threshold:	No data available	
	Melting point/freezing point:		No data available
	Boiling point or initial boiling point and		No data available
	boiling range:		
	Flammability:		not applicable
	Lower explosion limits:		No data available
	Upper explosion limits:		No data available
	Flash point:		~21 °C
	Auto-ignition temperature:		No data available
	Decomposition temperature:		not determined
	pH-Value:		No data available
	Viscosity / kinematic:		No data available
	Solubility in other solvents		
	not determined		
	Dissolution rate:		No data available
	Partition coefficient n-octanol/water:		No data available
	Dispersion stability:		No data available
	Vapour pressure:		No data available
	Vapour pressure:		No data available
	Density:		0,8505 g/cm³
	Relative density:		No data available
	Bulk density:		No data available
	Relative vapour density:		not determined
	Particle characteristics:		No data available
).2	2. Other information		
	Information with regard to physical haza	ard classes	
	Explosive properties		
	Vapours can form explosive mixtures v	with air.	
	Sustaining combustion:		No data available
	Self-ignition temperature		
	Solid:		not applicable
	Gas:		not applicable

9.



according to UK REACH Regulation

olution 100.2 all toobai

Diethylene glycol monobulyl ether solution 100.3 g/l technical grade denatured with MEK in						
	ethanol s					
Revision date: 06.03.2024	Product code: 04739	Page 8 of 13				
Oxidizing properties						
Not oxidising.						
Other safety characteristics						
Evaporation rate:	No data available					
Solvent separation test:	No data available					
Solvent content:	No data available					
Solid content:	No data available					
Sublimation point:	No data available					
Softening point:	No data available					
Pour point:	No data available					
No data available:						
Viscosity / dynamic:	No data available					
Flow time:	No data available					
Further Information						
No data available						

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable.

Vapours can form explosive mixtures with air.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon dioxide (CO2) Carbon monoxide

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Toxicocinetics, metabolism and distribution

There are no data available on the preparation/mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l



Diethylene glycol monobutyl ether solution 100.3 g/l technical grade denatured with MEK in ethanol s

Revision date: 06.03.2024

Product code: 04739

Page 9 of 13

CAS No	Chemical name	Chemical name								
	Exposure route	Dose		Species	Source	Method				
64-17-5	ethanol	ethanol								
	oral	LD50 mg/kg	10470	Rat	Study report (1976)	OECD Guideline 401				
	inhalation (4 h) vapour	r LC50 124,7 mg/l		Rat	Study report (1980)	OECD Guideline 403				
112-34-5	2-(2-butoxyethoxy)ethan	ol								
	mg/kg			Mouse	Study report (1981)	OECD Guideline 401				
				Rabbit	Study report (1981)	OECD Guideline 402				

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

There are no data available on the preparation/mixture itself.

Specific effects in experiment on an animal

There are no data available on the preparation/mixture itself.

Additional information on tests

There are no data available on the preparation/mixture itself.

Practical experience

There are no data available on the preparation/mixture itself.

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Other information

Irritant Dizziness The product causes narcotic-like effects. Inebriation Vomiting

Further information

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).



Diethylene glycol monobutyl ether solution 100.3 g/l technical grade denatured with MEK in

Revision date: 06.03.2024

ethanol s Product code: 04739

Page 10 of 13

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
64-17-5	ethanol						
	Acute fish toxicity	LC50 mg/l	15400	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-00 9, 1975
	Acute algae toxicity	ErC50 22000 mg/l	ca.	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	> 10000	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11
	Algae toxicity	NOEC mg/l	5400	5 d	Skeletonema costatum	Environ Toxicol Chem 8(5):451-455. (1989	Study to determine the sensitivity of a
	Crustacea toxicity	NOEC	2 mg/l	10 d	Ceriodaphnia dubia	Arch Environ Contam Toxicol 20(2):211-21	Follows the basic methodology for the th
112-34-5	2-(2-butoxyethoxy)ethance)					
	Acute fish toxicity	LC50 mg/l	1300	96 h	Lepomis macrochirus	J Haz Mat, 1, p303-18 (1977)	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	> 100	96 h	Desmodesmus subspicatus	Study report (1992)	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	> 100	48 h	Daphnia magna	Study report (1992)	EU Method C.2

12.2. Persistence and degradability

There are no data available on the preparation/mixture itself.

12.3. Bioaccumulative potential

There are no data available on the preparation/mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-17-5	ethanol	-0,77
112-34-5	2-(2-butoxyethoxy)ethanol	1

BCF

CAS No	Chemical name	BCF	Species	Source
64-17-5	ethanol	1	Cyprinus carpio	Comparative Biochemi

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.



Diethylene glycol monobutyl ether solution 100.3 g/l technical grade denatured with MEK in

ethanol s

Revision date: 06.03.2024

Product code: 04739

Page 11 of 13

12.7. Other adverse effects

There are no data available on the preparation/mixture itself.

Further information

Avoid release to the environment. Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Send to a physico-chemical treatment facility under observation of official regulations. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Contaminated packaging

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	
14.2. UN proper shipping name:	ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3
Classification code:	F1
Special Provisions:	144 601
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	30
Tunnel restriction code:	D/E
Inland waterways transport (ADN)	
14.1. UN number or ID number:	UN 1170
14.2. UN proper shipping name:	ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3
Classification code:	F1
Special Provisions:	144 601
Limited quantity:	5 L
Excepted quantity:	E1
Marine transport (IMDG)	
<u>14.1. UN number or ID number:</u>	UN 1170
14.2. UN proper shipping name:	ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3
Special Provisions:	144, 223
Limited quantity:	5 L
Excepted quantity:	E1
· · ·	



Diethylene glycol monobutyl ether solution 100.3 g/l technical grade denatured with MEK in ethanol s				
Revision date: 06.03.2024	Product code: 04739	Page 12 of 13		
EmS:	F-E, S-D			
Air transport (ICAO-TI/IATA-DGR)				
14.1. UN number or ID number:	UN 1170			
14.2. UN proper shipping name:	ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)			
14.3. Transport hazard class(es):	3			
14.4. Packing group:	III			
Hazard label:	3			
Special Provisions:	A3 A58 A180			
Limited quantity Passenger:	10 L			
Passenger LQ:	Y344			
Excepted quantity: IATA-packing instructions - Passenger:	E1 355			
IATA-max. quantity - Passenger:	60 L			
IATA-packing instructions - Cargo:	366			
IATA-max. quantity - Cargo:	220 L			
14.5. Environmental hazards				
ENVIRONMENTALLY HAZARDOUS:	No			
14.6. Special precautions for user				
Warning: Combustible liquid.				
14.7. Maritime transport in bulk according to	IMO instruments			
not applicable				
SECTION 15: Regulatory information				
15.1. Safety, health and environmental regul	ations/legislation specific for the substance or mixture			
EU regulatory information				
Restrictions on use (REACH, annex XVII):				
Entry 3, Entry 40, Entry 55, Entry 75				
Information according to Directive	P5c FLAMMABLE LIQUIDS			
2012/18/EU (SEVESO III):				
National regulatory information				
Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juve work protection guideline' (94/33/EC).	nile		
Water hazard class (D):	1 - slightly hazardous to water			
15.2. Chemical safety assessment				
For this substance a chemical safety as	ssessment has not been carried out.			

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,9.



Diethylene glycol monobutyl ether solution 100.3 g/l technical grade denatured with MEK in

ethanol s

Revision date: 06.03.2024

Product code: 04739

Page 13 of 13

Abbreviations and acronyms

Flam. Lig: Flammable liquids Eye Irrit: Eye irritation

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method

Relevant H and EUH statements (number and full text)

Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

Further Information

H225

Provide appropriate information, instructions and training to users

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)