

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Alkali blue indicator solution 0.4 g/l in ethanol-toluene mixture

Revision date: 09.02.2024

Product code: 22777

Page 1 of 13

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Alkali blue indicator solution 0.4 g/l in ethanol-toluene mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

#### Uses advised against

Do not use for private purposes (household).

### 1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH	
	ACD	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
E-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
E-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	

### 1.4. Emergency telephone

#### number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

### Further Information

This product is a mixture. REACH Registration Number see section 3.

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Regulation (EC) No 1272/2008

Flam. Liq. 2; H225

Asp. Tox. 1; H304

Skin Irrit. 2; H315

Repr. 2; H361d

STOT SE 3; H336

STOT RE 2; H373

Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

#### Regulation (EC) No 1272/2008

#### Hazard components for labelling

toluene

Signal word: Danger

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Alkali blue indicator solution 0.4 g/l in ethanol-toluene mixture**

Revision date: 09.02.2024

Product code: 22777

Page 2 of 13

**Pictograms:**



**Hazard statements**

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P403+P235	Store in a well-ventilated place. Keep cool.

**2.3. Other hazards**

No information available.

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**

**Relevant ingredients**

CAS No	Chemical name	Quantity
	EC No	Index No
	REACH No	
	Classification (Regulation (EC) No 1272/2008)	
108-88-3	toluene	55 - < 60 %
	203-625-9	601-021-00-3
		01-2119471310-51
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H225 H361d H315 H336 H373 H304 H412	
64-17-5	ethanol	40 - < 45 %
	200-578-6	603-002-00-5
		01-2119457610-43
	Flam. Liq. 2, Eye Irrit. 2; H225 H319	

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
108-88-3	203-625-9	toluene	55 - < 60 %
	inhalation: LC50 = 28,1 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = 5580 mg/kg		
64-17-5	200-578-6	ethanol	40 - < 45 %
	inhalation: LC50 = 124,7 mg/l (vapours); oral: LD50 = 10470 mg/kg Eye Irrit. 2; H319: >= 50 - 100		

**Further Information**

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Alkali blue indicator solution 0.4 g/l in ethanol-toluene mixture

Revision date: 09.02.2024

Product code: 22777

Page 3 of 13

#### SECTION 4: First aid measures

##### 4.1. Description of first aid measures

###### General information

No data available

###### After inhalation

Provide fresh air. Medical treatment necessary.

###### After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

###### After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

###### After ingestion

Rinse mouth immediately and drink plenty of water.

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

##### 4.2. Most important symptoms and effects, both acute and delayed

Vapours may cause drowsiness and dizziness.

Irritant

##### 4.3. Indication of any immediate medical attention and special treatment needed

No data available

#### SECTION 5: Firefighting measures

##### 5.1. Extinguishing media

###### Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

###### Unsuitable extinguishing media

no restriction

##### 5.2. Special hazards arising from the substance or mixture

Combustible liquids

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO<sub>2</sub>), Carbon monoxide

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Heating causes rise in pressure with risk of bursting.

##### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

###### Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

#### SECTION 6: Accidental release measures

##### 6.1. Personal precautions, protective equipment and emergency procedures

###### General advice

Keep away from sources of ignition - No smoking.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Alkali blue indicator solution 0.4 g/l in ethanol-toluene mixture

Revision date: 09.02.2024

Product code: 22777

Page 4 of 13

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

#### For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Do not breathe dust/fume/gas/mist/vapours/spray.

#### For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

#### 6.3. Methods and material for containment and cleaning up

##### For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

##### For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

##### Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

#### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

Vapours can form explosive mixtures with air.

#### Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

#### Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Alkali blue indicator solution 0.4 g/l in ethanol-toluene mixture**

Revision date: 09.02.2024

Product code: 22777

Page 5 of 13

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Further information on storage conditions**

Keep cool. Protect from sunlight.

**7.3. Specific end use(s)**

Laboratory chemicals

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limits**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
64-17-5	Ethyl alcohol	1000	-		STEL (15 min)	
108-88-3	Toluene	50	192		TWA (8 h)	
		100	384		STEL (15 min)	

**Biological limit values**

CAS No	Substance	Parameter	Value	Test material	Sampling time
108-88-3	Toluene	Toluene	0.02 mg/L	Blood	Prior to last shift of workweek

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Alkali blue indicator solution 0.4 g/l in ethanol-toluene mixture**

Revision date: 09.02.2024

Product code: 22777

Page 6 of 13

**DNEL/DMEL values**

CAS No	Substance		
DNEL type	Exposure route	Effect	Value
108-88-3	toluene		
Worker DNEL, long-term	inhalation	systemic	192 mg/m <sup>3</sup>
Worker DNEL, acute	inhalation	systemic	384 mg/m <sup>3</sup>
Worker DNEL, long-term	inhalation	local	192 mg/m <sup>3</sup>
Worker DNEL, acute	inhalation	local	384 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic	384 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	56,5 mg/m <sup>3</sup>
Consumer DNEL, acute	inhalation	systemic	226 mg/m <sup>3</sup>
Consumer DNEL, long-term	inhalation	local	56,5 mg/m <sup>3</sup>
Consumer DNEL, acute	inhalation	local	226 mg/m <sup>3</sup>
Consumer DNEL, long-term	dermal	systemic	226 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	8,13 mg/kg bw/day
64-17-5	ethanol		
Worker DNEL, long-term	inhalation	systemic	950 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic	343 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	114 mg/m <sup>3</sup>
Consumer DNEL, long-term	dermal	systemic	206 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	87 mg/kg bw/day

**PNEC values**

CAS No	Substance	
Environmental compartment	Value	
108-88-3	toluene	
Freshwater	0,68 mg/l	
Freshwater (intermittent releases)	0,68 mg/l	
Marine water	0,68 mg/l	
Freshwater sediment	16,39 mg/kg	
Marine sediment	16,39 mg/kg	
Micro-organisms in sewage treatment plants (STP)	13,61 mg/l	
Soil	2,89 mg/kg	
64-17-5	ethanol	
Freshwater	0,96 mg/l	
Freshwater (intermittent releases)	2,75 mg/l	
Marine water	0,79 mg/l	
Freshwater sediment	3,6 mg/kg	
Marine sediment	2,9 mg/kg	
Secondary poisoning	380 mg/kg	
Micro-organisms in sewage treatment plants (STP)	580 mg/l	
Soil	0,63 mg/kg	

**8.2. Exposure controls**

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Alkali blue indicator solution 0.4 g/l in ethanol-toluene mixture

Revision date: 09.02.2024

Product code: 22777

Page 7 of 13

#### Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

#### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Wear eye/face protection.

##### Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: [vertrieb@kcl.de](mailto:vertrieb@kcl.de) With specification (test according to EN374):

By long-term hand contact

Recommended glove articles: KCL 890 Vitoject®

Recommended material: FKM (fluoro rubber) 0,7 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Recommended glove articles: KCL 890 Vitoject®

Recommended material: FKM (fluoro rubber) 0,7 mm

Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet (>, <) supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

##### Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

##### Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

##### Environmental exposure controls

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Danger of explosion

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	blue	
Odour:	Toluene	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		78 °C
Flammability:		not applicable
Lower explosion limits:		No data available
Upper explosion limits:		No data available
Flash point:		<21 °C
Auto-ignition temperature:		No data available
Decomposition temperature:		No data available
pH-Value:		No data available

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Alkali blue indicator solution 0.4 g/l in ethanol-toluene mixture

Revision date: 09.02.2024

Product code: 22777

Page 8 of 13

Viscosity / kinematic:	No data available
Water solubility:	No data available
Solubility in other solvents not determined	
Dissolution rate:	No data available
Partition coefficient n-octanol/water:	No data available
Dispersion stability:	No data available
Vapour pressure:	No data available
Vapour pressure:	No data available
Density:	0,83830 g/cm <sup>3</sup>
Bulk density:	No data available
Relative vapour density:	No data available

#### 9.2. Other information

##### Information with regard to physical hazard classes

Sustaining combustion:	No data available
Self-ignition temperature	
Solid:	not applicable
Gas:	not applicable
Oxidizing properties	
Not oxidising.	

##### Other safety characteristics

Evaporation rate:	not determined
Solvent separation test:	No data available
Solvent content:	No data available
Solid content:	0
Sublimation point:	No data available
Softening point:	No data available
Pour point:	No data available
No data available:	
Viscosity / dynamic:	No data available
Flow time:	No data available

##### Further Information

No data available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Vapours may form explosive mixtures with air.  
Highly flammable.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

Oxidising agent  
@000000001174

### 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

### 10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

#### Further information

No data available



**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Alkali blue indicator solution 0.4 g/l in ethanol-toluene mixture**

Revision date: 09.02.2024

Product code: 22777

Page 9 of 13

**SECTION 11: Toxicological information**

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Toxicokinetics, metabolism and distribution**

There are no data available on the mixture itself.

**Acute toxicity**

Based on available data, the classification criteria are not met.

**ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
108-88-3	toluene				
	oral	LD50 5580 mg/kg	Rat	Toxicology 4, 5-15 (1975)	EU Method B.1
	dermal	LD50 > 5000 mg/kg	Rabbit	American Industrial Hygiene Association	Study investigated mortality in groups o
	inhalation (4 h) vapour	LC50 28,1 mg/l	Rat	Study report (1980)	OECD Guideline 403
64-17-5	ethanol				
	oral	LD50 10470 mg/kg	Rat	Study report (1976)	OECD Guideline 401
	inhalation (4 h) vapour	LC50 124,7 mg/l	Rat	Study report (1980)	OECD Guideline 403

**Irritation and corrosivity**

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Suspected of damaging the unborn child. (toluene)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause drowsiness or dizziness. (toluene)

**STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure. (toluene)

**Aspiration hazard**

May be fatal if swallowed and enters airways.

**Information on likely routes of exposure**

There are no data available on the mixture itself.

**Specific effects in experiment on an animal**

There are no data available on the mixture itself.

**Additional information on tests**

There are no data available on the mixture itself.

**Practical experience**

There are no data available on the mixture itself.

**11.2. Information on other hazards**

**Alkali blue indicator solution 0.4 g/l in ethanol-toluene mixture**

Revision date: 09.02.2024

Product code: 22777

Page 10 of 13

**Other information**

There are no data available on the mixture itself.

**Further information**

There are no data available on the mixture itself.

**SECTION 12: Ecological information**

**12.1. Toxicity**

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
108-88-3	toluene					
	Acute fish toxicity	LC50 5,5 mg/l	96 h	Oncorhynchus kisutch	Transactions A. Fish. Soc. 110, 430-436.	Fry were exposed to toluene in a flow th
	Acute algae toxicity	ErC50 > 433 mg/l	96 h	Pseudokirchneriella subcapitata	REACH Registration Dossier	Method: other
	Acute crustacea toxicity	EC50 11,5 mg/l	48 h	Daphnia magna	REACH Registration Dossier	Method: other
	Fish toxicity	NOEC 1,39 mg/l	40 d	Oncorhynchus kisutch	Transactions A. Fish. Soc. 110, 430-436.	Fry were exposed to toluene in a flow th
	Algae toxicity	NOEC > 400 mg/l	7 d	Scenedesmus quadricauda	REACH Registration Dossier	Method: other
	Crustacea toxicity	NOEC 0,74 mg/l	7 d	Ceriodaphnia dubia	Ecotoxicol. Environ. Saf. 39, 136-146. (	other: US EPA 600/4-91-003
64-17-5	ethanol					
	Acute fish toxicity	LC50 15400 mg/l	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-009, 1975
	Acute algae toxicity	ErC50 ca. 22000 mg/l	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 10000 mg/l	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11
	Algae toxicity	NOEC 5400 mg/l	5 d	Skeletonema costatum	Environ Toxicol Chem 8(5):451-455. (1989)	Study to determine the sensitivity of a
	Crustacea toxicity	NOEC 2 mg/l	10 d	Ceriodaphnia dubia	Arch Environ Contam Toxicol 20(2):211-21	Follows the basic methodology for the th

**12.2. Persistence and degradability**

The product has not been tested.

**12.3. Bioaccumulative potential**

The product has not been tested.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Alkali blue indicator solution 0.4 g/l in ethanol-toluene mixture

Revision date: 09.02.2024

Product code: 22777

Page 11 of 13

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
108-88-3	toluene	2,73
64-17-5	ethanol	-0,77

**BCF**

CAS No	Chemical name	BCF	Species	Source
108-88-3	toluene	90	Leuciscus idus melanotus	Chemosphere 14 (10).
64-17-5	ethanol	1	Cyprinus carpio	Comparative Biochemi

**12.4. Mobility in soil**

The product has not been tested.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

Do not allow to enter into surface water or drains.

**Further information**

Avoid release to the environment.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Send to a physico-chemical treatment facility under observation of official regulations. Do not empty into drains.

**Contaminated packaging**

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

**SECTION 14: Transport information****Land transport (ADR/RID)**

<b>14.1. UN number or ID number:</b>	UN 1993
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, N.O.S. (toluene, ethanol)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3
Classification code:	F1
Special Provisions:	274 601 640D
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

**Inland waterways transport (ADN)**

<b>14.1. UN number or ID number:</b>	UN 1993
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, N.O.S. (toluene, ethanol)
<b>14.3. Transport hazard class(es):</b>	3

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Alkali blue indicator solution 0.4 g/l in ethanol-toluene mixture**

Revision date: 09.02.2024

Product code: 22777

Page 12 of 13

**14.4. Packing group:** II  
**Hazard label:** 3  
**Classification code:** F1  
**Special Provisions:** 274 601 640D  
**Limited quantity:** 1 L  
**Excepted quantity:** E2

**Marine transport (IMDG)**

**14.1. UN number or ID number:** UN 1993  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, N.O.S. (toluene, ethanol)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
**Hazard label:** 3  
**Special Provisions:** 274  
**Limited quantity:** 1 L  
**Excepted quantity:** E2  
**EmS:** F-E, S-E

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number or ID number:** UN 1993  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, N.O.S. (toluene, ethanol)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
**Hazard label:** 3  
**Special Provisions:** A3  
**Limited quantity Passenger:** 1 L  
**Passenger LQ:** Y341  
**Excepted quantity:** E2  
**IATA-packing instructions - Passenger:** 353  
**IATA-max. quantity - Passenger:** 5 L  
**IATA-packing instructions - Cargo:** 364  
**IATA-max. quantity - Cargo:** 60 L

**14.5. Environmental hazards**

**ENVIRONMENTALLY HAZARDOUS:** No

**14.6. Special precautions for user**

Warning: Combustible liquid.

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU regulatory information**

**Restrictions on use (REACH, annex XVII):**  
 Entry 3, Entry 40, Entry 48

**National regulatory information**

**Employment restrictions:** Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).  
**Water hazard class (D):** 3 - highly hazardous to water

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Alkali blue indicator solution 0.4 g/l in ethanol-toluene mixture**

Revision date: 09.02.2024

Product code: 22777

Page 13 of 13

**Changes**

This data sheet contains changes from the previous version in section(s): 2,9,12.

**Abbreviations and acronyms**

Flam. Liq: Flammable liquid

Asp. Tox: Aspiration hazard

Skin Irrit: Skin irritation

Eye Irrit: Eye irritation

Repr: Reproductive toxicity

STOT SE: Specific target organ toxicity - single exposure

STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Chronic: Chronic aquatic hazard

ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

**Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]**

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Calculation method
Repr. 2; H361d	Calculation method
STOT SE 3; H336	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 3; H412	Calculation method

**Relevant H and EUH statements (number and full text)**

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*