

Multielement-Standardlösung 20 Elemente je 100 mg/l in Salpetersäure 5 %

Revision date: 24.06.2024

Product code: 32970

Page 1 of 16

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Multielement-Standardlösung 20 Elemente je 100 mg/l in Salpetersäure 5 %

UFI:

CN9X-G2GC-M00A-3D09

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH	
	ACD	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
E-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
E-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	
1.4. Emergency telephone	For Hazardous Materials [or Dangero	us Goods] Incidents Spill, Leak, Fire,
number:	Exposure, or Accident Call CHEMTRE 1-800-424-9300 Outside USA and Ca accepted)	EC Day or Night Within USA and Canada: nada: +1 703-741-5970 (collect calls

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Met. Corr. 1; H290 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Carc. 1B; H350i Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling nitric acid

beryllium nitrate nickel dinitrate

Signal word: Danger

Revision No: 1,03 - Replaces version: 1,02



Multielement-Standardlösung 20 Elemente je 100 mg/l in Salpetersäure 5 %

Revision date: 24.06.2024

Pictograms:

Product code: 32970

Page 2 of 16



Hazard statements

H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H350i	May cause cancer by inhalation.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

recautionary statement	
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
pecial labelling of certa	ain mixtures

EUH071

Sp

Corrosive to the respiratory tract. Restricted to professional users.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixtures in aqueous solution



Multielement-Standardlösung 20 Elemente je 100 mg/l in Salpetersäure 5 %

Revision date: 24.06.2024

Product code: 32970

Page 3 of 16

Relevant ingredients

CAS No	Chemical name						
	EC No	Index No	REACH No				
	Classification (Regulation (EC) No 1272/2008)						
7697-37-2	nitric acid			5 - < 10 %			
	231-714-2	007-030-00-3	01-2119487297-23				
	Ox. Liq. 3, Met. Corr. 1,	Acute Tox. 3, Skin Corr. 1A; H272 H	290 H331 H314 EUH071				
13597-99-4	beryllium nitrate						
	237-062-5	004-002-00-2					
	Carc. 1B, Acute Tox. 2, RE 1, Aquatic Chronic 2						
13138-45-9	nickel dinitrate	< 0.1 %					
	236-068-5	028-012-00-1	01-2119492333-38				
	Ox. Sol. 2, Carc. 1A, Mu Resp. Sens. 1, Skin Ser H360D H332 H302 H31						
7761-88-8	silver nitrate			< 0.1 %			
	231-853-9	047-001-00-2	01-2119513705-43				
	Ox. Sol. 2, Met. Corr. 1, H290 H314 H318 H400						

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity	
	Specific Conc.	Limits, M-factors and ATE		
7697-37-2	231-714-2	nitric acid	5 - < 10 %	
		E 2,65 mg/l (vapours) Ox. Liq. 3; H272: >= 65 - 100 Skin Corr. 1A; H314: >= 20 rr. 1B; H314: >= 5 - < 20		
13597-99-4	237-062-5	beryllium nitrate	< 1 %	
	inhalation: ATE = 0,5 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); oral: ATE = 100 mg/kg			
13138-45-9	236-068-5	nickel dinitrate	< 0.1 %	
	361,9 mg/kg S			
7761-88-8	231-853-9	silver nitrate	< 0.1 %	
		= > 348 mg/kg; oral: LD50 = > 2000 mg/kg		

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection!

After inhalation

Provide fresh air. Call a physician immediately.



according to Regulation (EC) No 1907/2006 Multielement-Standardlösung 20 Elemente je 100 mg/l in Salpetersäure 5 %

Revision date: 24.06.2024

Product code: 32970

Page 4 of 16

After contact with skin

Wash immediately with: Water Take off immediately all contaminated clothing and wash it before reuse. Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing. Protect uninjured eye.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Do not allow a neutralisation agent to be drunk. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns. Irritant Cough Dyspnoea Vomiting Methaemoglobinaemia Risk of serious damage to eyes. Allergic reactions

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Non-combustible liquids Hazardous combustion products In case of fire may be liberated: Nitrogen oxides (NOx)

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. In case of fire and/or explosion do not breathe fumes. Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Move undamaged containers from immediate hazard area if it can be done safely. Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Corrosive to metals.



Multielement-Standardlösung 20 Elemente je 100 mg/l in Salpetersäure 5 %

Revision date: 24.06.2024

Product code: 32970

Page 5 of 16

For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment. Avoid contact with skin, eyes and clothes. Remove persons to safety. Emergency procedures Consult an expert Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation. Do not breathe dust/fume/gas/mist/vapours/spray. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care. When using do not eat, drink, smoke, sniff. Use personal protection equipment. Provide adequate ventilation. Avoid contact with skin, eyes and clothes. Do not breathe vapour/aerosol. Use extractor hood (laboratory).

Advice on protection against fire and explosion

Usual measures for fire prevention.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

Further information on handling

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. Take off immediately all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Corrosive to metals.

Unsuitable container/equipment material: Metal



Multielement-Standardlösung 20 Elemente je 100 mg/l in Salpetersäure 5 %

Revision date: 24.06.2024

Product code: 32970

Page 6 of 16

The product develops hydrogen in an aqueous solution in contact with metals.

Further information on storage conditions

Keep container tightly closed.

Store in a place accessible by authorized persons only.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
7697-37-2	Nitric acid	1	2.6		STEL (15 min)	

DNEL/DMEL values

CAS No	Substance						
DNEL type		Exposure route	Effect	Value			
13138-45-9	nickel dinitrate						
Consumer DN	EL, acute	oral	systemic	0,012 mg/kg bw/day			
Consumer DNEL, long-term		oral	systemic	0,02 mg/kg bw/day			
Worker DNEL	, acute	inhalation	systemic	104 mg/m³			
Worker DNEL	, acute	inhalation	local	1,6 mg/m³			
Consumer DN	EL, acute	inhalation	systemic	8,8 mg/m ³			
Consumer DN	EL, acute	inhalation	local	0,1 mg/m ³			
7761-88-8	silver nitrate						
Consumer DN	EL, long-term	oral	systemic	0,02 mg/kg bw/day			
Worker DNEL	, long-term	inhalation	systemic	0,016 mg/m³			
Consumer DN	EL, long-term	inhalation	systemic	0,006 mg/m ³			



Multielement-Standardlösung 20 Elemente je 100 mg/l in Salpetersäure 5 %

Revision date: 24.06.2024

Product code: 32970

Page 7 of 16

PNEC values

CAS No	Substance						
Environment	tal compartment	Value					
13138-45-9	nickel dinitrate						
Freshwater		0,0071 mg/l					
Freshwater ((intermittent releases)	0 mg/l					
Marine wate	r	0,0086 mg/l					
Freshwater s	sediment	109 mg/kg					
Marine sedir	nent	109 mg/kg					
Secondary p	oisoning	0,12 mg/kg					
Micro-organi	isms in sewage treatment plants (STP)	0,33 mg/l					
Soil		29,9 mg/kg					
7761-88-8	silver nitrate						
Freshwater		0,00004 mg/l					
Marine wate	r	0,00086 mg/l					
Freshwater s	sediment	438,13 mg/kg					
Marine sedir	438,13 mg/kg						
Micro-organisms in sewage treatment plants (STP) 0,025 mg/l							
Soil		1,41 mg/kg					

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles Wear eye/face protection.

Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Recommended glove articles: KCL 741 Dermatril® L Recommended material: NBR (Nitrile rubber) 0,11 mm Wearing time with permanent contact: > 480 min

By short-term hand contact Recommended glove articles: KCL 741 Dermatril® L Recommended material: NBR (Nitrile rubber) 0,11mm Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).



Multielement-Standardlösung 20 Elemente je 100 mg/l in Salpetersäure 5 %

Revision date: 24.06.2024

Product code: 32970

Page 8 of 16

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing.

Wash hands before breaks and after work.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

	. Information on pasic physical and chem	incal properties	
	Physical state:	Liquid	
	Colour:	yellow	
	Odour:	like: Nitric acid	
	Odour threshold:	No data available	
	Melting point/freezing point:		No data available
	Boiling point or initial boiling point and		No data available
	boiling range:		
	Flammability:		No data available
	Lower explosion limits:		No data available
	Upper explosion limits:		No data available
	Flash point:		No data available
	Auto-ignition temperature:		No data available
	Decomposition temperature:		No data available
	pH-Value:		0
	Viscosity / kinematic:		No data available
	Water solubility:		No data available
	Solubility in other solvents		
	No data available		
	Dissolution rate:		No data available
	Partition coefficient n-octanol/water:		No data available
	Dispersion stability:		No data available
	Vapour pressure:		No data available
	Vapour pressure:		No data available
	Density:		1,0290 g/cm ³
	Bulk density:		No data available
	Relative vapour density:		No data available
	Particle characteristics:		No data available
).2	. Other information		
	Information with regard to physical haza	rd classes	
	Explosive properties		
	No data available		
	Sustaining combustion:		No data available
	Self-ignition temperature		
	Solid:		No data available
	Gas:		No data available
	Oxidizing properties		
	Oxidizing		

<u>9</u>.



Multielement-Standardlösung 20 Elemente je 100 mg/l in Salpetersäure 5 %

Revision date: 24.06.2024

Product code: 32970

Page 9 of 16

Other safety characteristics	
Evaporation rate:	No data available
Solvent separation test:	No data available
Solvent content:	0
Solid content:	0
Sublimation point:	No data available
Softening point:	No data available
Pour point:	No data available
No data available:	
Viscosity / dynamic:	No data available
Flow time:	No data available
Further Information	

Corrosive to metals.

SECTION 10: Stability and reactivity

10.1. Reactivity

Corrosive to metals. Oxidising agent

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Alkali (lye)

The product develops hydrogen in an aqueous solution in contact with metals. Amines, Ammonia, Alcohols, Alkali metals, Hydrogen peroxide Copper, Combustible solids, Solvent, Alkaline earth metal, mercury (Hg).

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Cellulose Metal

The product develops hydrogen in an aqueous solution in contact with metals.

10.6. Hazardous decomposition products

In case of fire may be liberated:

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

There are no data available on the preparation/mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l



Multielement-Standardlösung 20 Elemente je 100 mg/l in Salpetersäure 5 %

Revision date: 24.06.2024

Product code: 32970

Page 10 of 16

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
7697-37-2	nitric acid							
	inhalation vapour	ATE 2,65	i mg/l					
13597-99-4	beryllium nitrate							
	oral	ATE mg/kg	100					
	inhalation vapour	ATE	0,5 mg/l					
	inhalation dust/mist	ATE	0,05 mg/l					
13138-45-9	nickel dinitrate							
	oral	LD50 mg/kg	361,9	Rat	Regul Toxicol and Pharmacol (doi.org/10.	OECD Guideline 425		
	inhalation vapour	ATE	11 mg/l					
	inhalation dust/mist	ATE	1,5 mg/l					
7761-88-8	silver nitrate							
	oral	LD50 mg/kg	> 2000	Rat	Study report (1993)	OECD Guideline 401		
	dermal	LD50 mg/kg	> 348	Guinea pig	J. Vet. Med. Sci.73: 1417 - 1423. (2011)	OECD Guideline 434		

Irritation and corrosivity

Skin corrosion/irritation: Causes severe skin burns and eye damage.

Serious eye damage/eye irritation: Causes serious eye damage.

Corrosive to the respiratory tract.

Following ingestion Gastric perforation

Irritating to respiratory system.

Pulmonary oedema

see also Section 4

Sensitising effects

May cause an allergic skin reaction. (beryllium nitrate; nickel dinitrate)

Carcinogenic/mutagenic/toxic effects for reproduction

May cause cancer by inhalation. (beryllium nitrate; nickel dinitrate) Germ cell mutagenicity: Based on available data, the classification criteria are not met. Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

There are no data available on the preparation/mixture itself.

Specific effects in experiment on an animal

There are no data available on the preparation/mixture itself.

Additional information on tests

There are no data available on the preparation/mixture itself.

Practical experience

There are no data available on the preparation/mixture itself.

11.2. Information on other hazards



according to Regulation (EC) No 1907/2006 Multielement-Standardlösung 20 Elemente je 100 mg/l in Salpetersäure 5 %

Revision date: 24.06.2024

Product code: 32970

Page 11 of 16

Endocrine disrupting properties

There are no data available on the preparation/mixture itself.

Other information

There are no data available on the preparation/mixture itself.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.



Multielement-Standardlösung 20 Elemente je 100 mg/l in Salpetersäure 5 %

Revision date: 24.06.2024

Product code: 32970

Page 12 of 16

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
7697-37-2	nitric acid						
	Acute fish toxicity	LC50 mg/l	1559	96 h	Topeka shiner	Environmental Toxicology and Chemistry,	other: ASTM E729-26
	Fish toxicity	NOEC	268 mg/l	30 d	juvenile Topeka shiner and with juvenile Fathead m	Study report (2009)	Growth tests estimated the test chemical
	Algae toxicity	NOEC mg/l	> 419	10 d	several benthic diatoms; see results	Marine Biology 43:307-315 (1977)	Ten cultures of benthic diatoms were iso
	Acute bacteria toxicity	EC50 mg/l()	> 1000	3 h	Activated sludge	Study report (2008)	OECD Guideline 209
13138-45-9	nickel dinitrate						
	Acute fish toxicity	LC50 mg/l	15,3	96 h	Oncorhynchus mykiss	Aquatic Toxicology 63 (2003) 65-82 (2003	other: not reported
	Acute algae toxicity	ErC50 mg/l	0,237	72 h	Ankistrodesmus falcatus	Publication (2009)	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	0,2663	48 h	Ceriodaphnia dubia	Study report (2004)	other: American society of testing and m
	Fish toxicity	NOEC mg/l	0,057	32 d	Pimephales promelas	Water Resources Research Institute. Kent	other: ASTM 1980, E-729
	Algae toxicity	NOEC	0,6 mg/l	14 d	Anabaena cylindrica	Environ. Pollut. (Series A). 25(4):241-2	other: not reported
	Crustacea toxicity	NOEC mg/l	0,04	42 d	Daphnia magna	Wat. Res. 24(7):845-852 (1990)	Chronic exposure to sublethal concentrat
	Acute bacteria toxicity	EC50)	33 mg/l (0,5 h	Activated sludge	Journal of Hazardous Materials. B139:332	ISO 8192
7761-88-8	silver nitrate						
	Acute fish toxicity	LC50 mg/l	0,0012	96 h	Pimephales promelas	Environmental Toxicology and Chemistry.	A guideline was not specified. The test
	Acute algae toxicity	ErC50 mg/l	0,0099	96 h	Pseudokirchneriella subcapitata	Environmental Science and Technology. 44	eline: U.S. Environmental Protection Age
	Acute crustacea toxicity	EC50 mg/l	0,00022	48 h	Daphnia magna	Environmental Toxicology and Chemistry.	The protective effect of reactive sulphi
	Fish toxicity	NOEC 0,00125 m	> ng/l	73 d	Oncorhynchus mykiss	Environmental Toxicology and Chemistry 2	other: ASTM 1241-98
	Algae toxicity	NOEC mg/l	0,0012	14 d	Champia parvula	in Bishop WE, Cardwell RD Heidolph BB (E	The toxicity tests lasted 11 days for th



Multielement-Standardlösung 20 Elemente je 100 mg/l in Salpetersäure 5 %

Revision date: 24.06.2024	Product code: 32970			Page 13 of 16
Crustacea toxicity	NOEC 0,00031 mg/l	20 d Isonychia bicolour	Environmental Toxicology and Chemistry.	20 day sublethal effects on representati

12.2. Persistence and degradability

The methods for determining the biological degradability are not applicable to inorganic substances.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

CAS No	Chemical name	BCF	Species	Source
13138-45-9	nickel dinitrate	23	Spirodela polyrhiza	Ecotoxicology and en
7761-88-8	silver nitrate	70	Cyprinus carpio	Water, Air and Soil

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Discharge into the environment must be avoided.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Send to a physico-chemical treatment facility under observation of official regulations. Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 2031	
14.2. UN proper shipping name:	NITRIC ACID	
14.3. Transport hazard class(es):	8	
14.4. Packing group:	II	
Hazard label:	8	
Classification code:	C1	
Limited quantity:	1 L	
Excepted quantity:	E2	
Transport category:	2	
Hazard No:	80	
Tunnel restriction code:	E	
Inland waterways transport (ADN)		
14.1. UN number or ID number:	UN 2031	
14.2. UN proper shipping name:	NITRIC ACID	



Multielement-Standardlösung 20 Elemente je 100 mg/l in Salpetersäure 5 %		
Revision date: 24.06.2024	Product code: 32970	Page 14 of 16
14.3. Transport hazard class(es): 14.4. Packing group: Hazard label: Classification code: Limited quantity: Excepted quantity: Marine transport (IMDG) 14.1. UN number or ID number: 14.2. UN proper shipping name: 14.3. Transport hazard class(es): 14.4. Packing group: Hazard label: Special Provisions: Limited quantity: Excepted quantity:	8 II 8 C1 1 L E2 UN 2031 NITRIC ACID 8 II 8 - 1 L E2	
EmS: Air transport (ICAO-TI/IATA-DGR) <u>14.1. UN number or ID number:</u> <u>14.2. UN proper shipping name:</u> <u>14.3. Transport hazard class(es):</u> <u>14.4. Packing group:</u> Hazard label: Special Provisions: Limited quantity Passenger: Passenger LQ: Excepted quantity: IATA-packing instructions - Passenger: IATA-max. quantity - Passenger: IATA-max. quantity - Cargo:	F-A, S-B UN 2031 NITRIC ACID 8 II 8 A212 Forbidden Forbidden E0 Forbidden Forbidden 855 30 L	

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 27, Entry 75

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

Acquisition, introduction, possession or use of this product by the general public is restricted by Regulation (EU) 2019/1148. All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

National regulatory information

U	
Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile
	work protection guideline' (94/33/EC).
Water hazard class (D):	3 - highly hazardous to water

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,9,12.



Multielement-Standardlösung 20 Elemente je 100 mg/l in Salpetersäure 5 %

Revision date: 24.06.2024

Product code: 32970

Page 15 of 16

Abbreviations and acronyms

Ox. Liq: Oxidising liquid Ox. Sol: Oxidising solid Met. Corr: Substance or mixture corrosive to metals Acute Tox: Acute toxicity Skin Corr: Skin corrosion Skin Irrit: Skin irritation Eye Dam: Eye damage Eye Irrit: Eye irritation Resp. Sens: Respiratory sensitisation Skin Sens: Skin sensitisation Muta: Germ cell mutagenicity Carc: Carcinogenicity Repr: Reproductive toxicity STOT SE: Specific target organ toxicity - single exposure STOT RE: Specific target organ toxicity - repeated exposure Aquatic Acute: Acute aquatic hazard Aquatic Chronic: Chronic aquatic hazard

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method
Carc. 1B; H350i	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

e	ievalit n allu EON Stat	ements (number and run text)
	H272	May intensify fire; oxidiser.
	H290	May be corrosive to metals.
	H301	Toxic if swallowed.
	H302	Harmful if swallowed.
	H314	Causes severe skin burns and eye damage.
	H315	Causes skin irritation.
	H317	May cause an allergic skin reaction.
	H318	Causes serious eye damage.
	H319	Causes serious eye irritation.
	H330	Fatal if inhaled.
	H331	Toxic if inhaled.
	H332	Harmful if inhaled.
	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
	H335	May cause respiratory irritation.
	H341	Suspected of causing genetic defects.
	H350i	May cause cancer by inhalation.
	H360D	May damage the unborn child.
	H372	Causes damage to organs through prolonged or repeated exposure.
	H400	Very toxic to aquatic life.
	H410	Very toxic to aquatic life with long lasting effects.
	H411	Toxic to aquatic life with long lasting effects.
	H412	Harmful to aquatic life with long lasting effects.
	EUH071	Corrosive to the respiratory tract.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung 20 Elemente je 100 mg/l in Salpetersäure 5 %

Revision date: 24.06.2024

Product code: 32970

Page 16 of 16

named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. Provide appropriate information, instructions and training to users

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)