

according to Regulation (EC) No 1907/2006

# Potassium hydroxide 0.1 mol/l in 2-propanol

Revision: 11.03.2025 Product code: AC15.00224 Page 1 of 13

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Potassium hydroxide 0.1 mol/l in 2-propanol

UFI: 5STF-H0WU-H004-370P

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Reagents and laboratory chemicals

Only for laboratory and analysis purposes.

#### Uses advised against

Do not use for private purposes (household).

## 1.3. Details of the supplier of the safety data sheet

### Details of the supplier of the safety data sheet

Company name: AnalytiChem Services, Unipessoal, Lda

Street: Rua de Júlio Dinis 676 7º Place: P-4050-320 Porto +351 226002917 Telephone: info@analvtichem.com F-mail: SDS service department Contact person: E-mail: SDS@analytichem.com Internet: www.analytichem.com SDS service department Responsible Department:

Supplier or manufacturer details

Company name: AnalytiChem GmbH Street: Stempelstraße 6 Place: D-47167 Duisburg Telephone: 0203/5194-0

E-mail: info@analytichem.de
Contact person: SDS service department
E-mail: SDS@analytichem.com
Internet: www.analytichem.de
Responsible Department: AnalytiChem:

EU-Belgium: AnalytiChem Belgium, Industriezone "De Arend" 2, 8210 Zedelgem,

Belgium, +32 50 28 83 20

EU-Germany: AnalytiChem Germany, Stempelstrasse 6, 47167 Duisburg,

Germany, +49 203 51 94 - 200

EU-Netherlands: AnalytiChem Netherlands, Communicatieweg 7, 3641 SG

Mijdrecht, The Netherlands, +31 297 286848

UK: AnalytiChem UK, Unit 7 Launton Business Center, Murdock Road, Bicester,

Telefax: 0203/5194-290

OX26 4XB, England, +44 1869 355 500

USA: AnalytiChem USA, 227 China Road, Winslow, Maine, 04901, United States,

+1 800-244-8378

Canada: AnalytiChem Canada, 21800 Clark Graham Avenue, Baie d'Urfe, H9X

4B6, Canada, +1 514-457-0701

Australia: ORE Research & Exploration Pty Ltd, 37A Hosie Street, Bayswater

North, 3153, Australia, +61 3 9729 0333

1.4. Emergency telephone

number:

+353 1 901 4670 (CHEMTREC)



according to Regulation (EC) No 1907/2006

# Potassium hydroxide 0.1 mol/l in 2-propanol

Revision: 11.03.2025 Product code: AC15.00224 Page 2 of 13

### **Further Information**

This product is a mixture. REACH Registration Number see section 3.

## **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

## Regulation (EC) No 1272/2008

Flam. Liq. 2; H225 Met. Corr. 1; H290 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

#### 2.2. Label elements

## Regulation (EC) No 1272/2008

### Hazard components for labelling

"propan-2-ol; isopropyl alcohol; isopropanol" potassium hydroxide

Signal word: Danger

Pictograms:







# **Hazard statements**

H225 Highly flammable liquid and vapour.

H290 May be corrosive to metals.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

## **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P240 Ground and bond container and receiving equipment. P302+P352 IF ON SKIN: Wash with plenty of water and soap.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

### 2.3. Other hazards

No data available

# **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Potassium hydroxide 0.1 mol/l in 2-propanol

Revision: 11.03.2025 Product code: AC15.00224 Page 3 of 13

### Relevant ingredients

CAS No	Chemical name	Chemical name			
	EC No	Index No	REACH No		
	Classification (Regulatio	n (EC) No 1272/2008)	·		
67-63-0	"propan-2-ol; isopropyl alcohol; isopropanol"			90 - < 95 %	
	200-661-7	603-117-00-0	01-2119457558-25		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336				
1310-58-3	potassium hydroxide			< 1 %	
	215-181-3	019-002-00-8	01-2119487136-33		
	Met. Corr. 1, Acute Tox. 4, Skin Corr. 1A, Eye Dam. 1; H290 H302 H314 H318				

Full text of H and EUH statements: see section 16.

### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. L	imits, M-factors and ATE	
1310-58-3	215-181-3	potassium hydroxide	< 1 %
		33 mg/kg Skin Corr. 1A; H314: >= 5 - 100 Skin Corr. 1B; H314: >= 2 - < 5 Skin = 0,5 - < 2 Eye Irrit. 2; H319: >= 0,5 - < 2	

#### **Further Information**

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

# **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### **General information**

No data available

#### After inhalation

Provide fresh air.

Call a physician immediately.

## After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

### After ingestion

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

# 4.2. Most important symptoms and effects, both acute and delayed

Irritant

Respiratory complaints

Headache

Gastrointestinal complaints

Dizziness

Dizziness

Inebriation

Anaesthetic state



according to Regulation (EC) No 1907/2006

# Potassium hydroxide 0.1 mol/l in 2-propanol

Revision: 11.03.2025 Product code: AC15.00224 Page 4 of 13

Unconsciousness

Repeated exposure may cause skin dryness or cracking.

### 4.3. Indication of any immediate medical attention and special treatment needed

No data available

# **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

### Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

#### Unsuitable extinguishing media

no restriction

### 5.2. Special hazards arising from the substance or mixture

Combustible liquids

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO2) Carbon monoxide

Heating causes rise in pressure with risk of bursting.

Beware of reignition.

#### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

#### Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

### General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

Corrosive to metals.

# For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

## For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and



according to Regulation (EC) No 1907/2006

# Potassium hydroxide 0.1 mol/l in 2-propanol

Revision: 11.03.2025 Product code: AC15.00224 Page 5 of 13

basements in higher concentration.

Danger of explosion

### 6.3. Methods and material for containment and cleaning up

#### For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

#### For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

#### Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

#### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

# **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

#### Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe vapour/aerosol. Provide adequate ventilation.

Avoid: aerosol or mist formation

### Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

## Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

Wash hands and face before breaks and after work and take a shower if necessary.

When using do not eat or drink.

Avoid: aerosol or mist formation

Do not breathe vapour/aerosol.

#### Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

### 7.2. Conditions for safe storage, including any incompatibilities

## Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Store in a cool dry place.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

# Hints on joint storage

national regulations

### Further information on storage conditions

Protect from sunlight.



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Potassium hydroxide 0.1 mol/l in 2-propanol

Revision: 11.03.2025 Product code: AC15.00224 Page 6 of 13

storage temperature: +15°C - +25°C

# 7.3. Specific end use(s)

Laboratory chemicals

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

## Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
1310-58-3	Potassium hydroxide	-	2		STEL (15 min)	
67-63-0	Propan-2-ol	200	-		TWA (8 h)	
		400	-		STEL (15 min)	

# **Biological limit values**

CAS No	Substance	Parameter	Value	Test material	Sampling time
67-63-0	2-Propanol	Acetone	40 mg/L		End of shift at end of workweek

## **DNEL/DMEL values**

CAS No	Substance				
DNEL type		Exposure route	Effect	Value	
67-63-0	"propan-2-ol; isopropyl alcohol; isopropanol"				
Worker DNEL,	long-term	inhalation	systemic	500 mg/m³	
Worker DNEL, long-term		dermal	systemic	888 mg/kg bw/day	
Consumer DNEL, long-term		inhalation	systemic	89 mg/m³	
Consumer DNEL, long-term		dermal	systemic	319 mg/kg bw/day	
Consumer DNEL, long-term		oral	systemic	26 mg/kg bw/day	
1310-58-3	0-58-3 potassium hydroxide				
Worker DNEL, long-term		inhalation	local	1 mg/m³	
Consumer DNEL, long-term		inhalation	local	1 mg/m³	

# PNEC values

CAS No	Substance			
Environmenta	l compartment	Value		
67-63-0	"propan-2-ol; isopropyl alcohol; isopropanol"			
Freshwater		140,9 mg/l		
Freshwater (intermittent releases) 14		140,9 mg/l		
Marine water		140,9 mg/l		
Freshwater sediment		552 mg/kg		
Marine sediment 552 n		552 mg/kg		
Secondary poisoning 160 r		160 mg/kg		
Micro-organisms in sewage treatment plants (STP)		2251 mg/l		
Soil 28 mg/kg		28 mg/kg		

## 8.2. Exposure controls



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Potassium hydroxide 0.1 mol/l in 2-propanol

Revision: 11.03.2025 Product code: AC15.00224 Page 7 of 13

### Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

### Individual protection measures, such as personal protective equipment

#### Eye/face protection

goggles

Face protection umbrella

### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Recommended glove articles KCL 730 Camatril® Velours

Thickness of the glove material NBR (Nitrile rubber) 0,4 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Recommended glove articles KCL 720 Camapren®

Thickness of the glove material CR (polychloroprene, chloroprene rubber) 0,65 mm

Wearing time with occasional contact (splashes): > 120 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

### Skin protection

Wear fire resistant or flame retardant clothing.

Take off immediately all contaminated clothing and wash it before reuse.

Wear suitable protective clothing. Take off immediately all contaminated clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

# Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

### **Environmental exposure controls**

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Danger of explosion



according to Regulation (EC) No 1907/2006

# Potassium hydroxide 0.1 mol/l in 2-propanol

Revision: 11.03.2025 Product code: AC15.00224 Page 8 of 13

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state:

Colour:

Odour:

Odour threshold:

Liquid

colourless

like: Alcohol

No data available

Melting point/freezing point:

Boiling point or initial boiling point and

No data available

~82 °C

boiling range:

Flammability: No data available Lower explosion limits: 2 vol. % Upper explosion limits: 13 vol. % ~13 °C Flash point: Auto-ignition temperature: ~425 °C Decomposition temperature: No data available pH-Value: No data available Viscosity / kinematic: Water solubility: Soluble in: Water

Solubility in other solvents
No data available

No data available Dissolution rate: No data available Partition coefficient n-octanol/water: No data available Dispersion stability: No data available Vapour pressure: Vapour pressure: No data available ~0,812 g/cm3 Density: No data available Relative density: No data available Bulk density: No data available Relative vapour density: Particle characteristics: No data available

### 9.2. Other information

## Information with regard to physical hazard classes

Explosive properties

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustained combustibility:

Sustained combustibility

Self-ignition temperature

Solid: No data available
Gas: No data available

Oxidizing properties

No data available

### Other safety characteristics

Evaporation rate:

Solvent separation test:

No data available
Solvent content:

No data available
Solid content:

No data available
Sublimation point:

No data available
Softening point:

No data available
Pour point:

No data available
No data available
No data available

Print date: 08.10.2025



according to Regulation (EC) No 1907/2006

# Potassium hydroxide 0.1 mol/l in 2-propanol

Revision: 11.03.2025 Product code: AC15.00224 Page 9 of 13

Viscosity / dynamic: No data available Flow time: No data available

Further Information
No data available

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Vapours may form explosive mixtures with air.

## 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

Oxidising agent, Alkali metals, Alkaline earth metal

chromium trioxide, Nitric acid, aldehydes

Amines, Aluminium, Chlorine (Cl2)

Phosphorus trichloride, Strong acid, Phosgene

Hydrogen peroxide, Nitrogen oxides (NOx), Iron.

### 10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### 10.5. Incompatible materials

Glass

Metal

Plastic articles

## 10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

# **Further information**

No data available

# **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

## Toxicocinetics, metabolism and distribution

No data available

#### Acute toxicity

Based on available data, the classification criteria are not met.

Mucous membrane irritation in the mouth, throat, esophagus and gastrointestinal tract.

#### **ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name						
	Exposure route	Dose		Species	Source	Method	
1310-58-3	potassium hydroxide						
	oral	LD50 mg/kg	333		Fund. Appl. Toxicol., 8, 97-100 (1987)	OECD Guideline 425	

## Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye irritation.

Repeated exposure may cause skin dryness or cracking.



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Potassium hydroxide 0.1 mol/l in 2-propanol

Revision: 11.03.2025 Product code: AC15.00224 Page 10 of 13

## Sensitising effects

Based on available data, the classification criteria are not met.

### Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

### STOT-single exposure

May cause drowsiness or dizziness. ("propan-2-ol; isopropyl alcohol; isopropanol")

Organs affected: central nervous system

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

Observe risk of aspiration if vomiting occurs.

#### Information on likely routes of exposure

No data available

### Specific effects in experiment on an animal

No data available

#### Additional information on tests

No data available

### **Practical experience**

No data available

### 11.2. Information on other hazards

## **Endocrine disrupting properties**

No data available

#### Other information

Pulmonary oedema Pneumonia

## **Further information**

Irritant

Respiratory complaints

Headache

Gastrointestinal complaints

Dizziness

Dizziness

Inebriation

Anaesthetic state

Unconsciousness

Repeated exposure may cause skin dryness or cracking.

# **SECTION 12: Ecological information**

### 12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name						
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method	
67-63-0	"propan-2-ol; isopropyl alcohol; isopropanol"						
	Acute fish toxicity	LC50 10000 mg/l		Pimephales promelas	, ,	OECD Guideline 203	

### 12.2. Persistence and degradability



according to Regulation (EC) No 1907/2006

# Potassium hydroxide 0.1 mol/l in 2-propanol

Revision: 11.03.2025 Product code: AC15.00224 Page 11 of 13

There are no data available on the mixture itself.

### 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-63-0	"propan-2-ol; isopropyl alcohol; isopropanol"	0,05

### 12.4. Mobility in soil

There are no data available on the mixture itself.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

Avoid release to the environment.

#### **Further information**

Do not allow to enter into surface water or drains.

## **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

# **Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

3

Do not mix with other wastes.

#### Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

# **SECTION 14: Transport information**

## Land transport (ADR/RID)

14.1. UN number or ID number: UN 2924

14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. ("propan-2-ol; isopropyl

alcohol; isopropanol", potassium hydroxide)

14.3. Transport hazard class(es): Ш 14.4. Packing group: Hazard label: 3+8 Classification code: FC **Special Provisions:** 274 Limited quantity: 1 L E2 Excepted quantity:

2 Transport category: 338 Hazard No: D/E Tunnel restriction code:

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 2924

14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. ("propan-2-ol; isopropyl

alcohol; isopropanol", potassium hydroxide)



according to Regulation (EC) No 1907/2006

## Potassium hydroxide 0.1 mol/l in 2-propanol

Revision: 11.03.2025 Product code: AC15.00224 Page 12 of 13

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3+8Classification code:FCSpecial Provisions:274Limited quantity:1 LExcepted quantity:E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 2924

**14.2. UN proper shipping name:** FLAMMABLE LIQUID, CORROSIVE, N.O.S. (propan-2-ol, potassium

hydroxide)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3+8Special Provisions:274Limited quantity:1 LExcepted quantity:E2EmS:F-E, S-C

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 2924

**14.2. UN proper shipping name:** FLAMMABLE LIQUID, CORROSIVE, N.O.S. (propan-2-ol, potassium

hydroxide)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3+8Special Provisions:A3Limited quantity Passenger:0.5 LPassenger LQ:Y340Excepted quantity:E2

IATA-packing instructions - Passenger:352IATA-max. quantity - Passenger:1 LIATA-packing instructions - Cargo:363IATA-max. quantity - Cargo:5 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

## **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Information according to Directive

P5c FLAMMABLE LIQUIDS

2012/18/EU (SEVESO III):

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

### **SECTION 16: Other information**



according to Regulation (EC) No 1907/2006

# Potassium hydroxide 0.1 mol/l in 2-propanol

Revision: 11.03.2025 Product code: AC15.00224 Page 13 of 13

### Changes

This data sheet contains changes from the previous version in section(s): 1,3,9.

### Abbreviations and acronyms

Met. Corr. 1: Corrosive to metals, hazard category 1 Flam. Liq. 2: Flammable liquids, hazard category 2 Acute Tox. 4: Acute toxicity, hazard category 4 Skin Corr. 1A: Skin corrosion, sub-category 1A Skin Irrit. 2: Skin irritation, hazard category 2

Eye Dam. 1: Serious eye damage, hazard category 1

Eye Irrit. 2: Eye irritation, hazard category 2

STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3

# Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Met. Corr. 1; H290	On basis of test data
Skin Irrit. 2; H315	
Eye Irrit. 2; H319	
STOT SE 3; H336	Calculation method

## Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

#### **Further Information**

Provide appropriate information, instructions and training to users

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)