

**Potassium hydroxide 0.01 mol/l in Propan**

Revision: 27.05.2025

Product code: AC15.00477

Page 1 of 12

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

Potassium hydroxide 0.01 mol/l in Propan

UFI: RJJJ-S2RK-5WCU-1JYA

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Use of the substance/mixture**

Reagents and laboratory chemicals

Only for laboratory and analysis purposes.

**Uses advised against**

Do not use for private purposes (household).

**1.3. Details of the supplier of the safety data sheet**

**Details of the supplier of the safety data sheet**

Company name: AnalytiChem Services, Unipessoal, Lda  
 Street: Rua de Júlio Dinis 676 7º  
 Place: N-4050-320 Porto  
 Telephone: +351 226002917  
 E-mail: info@analytichem.com  
 Contact person: SDS service department  
 E-mail: SDS@analytichem.com  
 Internet: www.analytichem.com  
 Responsible Department: SDS service department

**Supplier or manufacturer details**

Company name: AnalytiChem Belgium NV  
 Street: Industriezone "De Arend" 2  
 Place: B-8210 Zedelgem  
 Telephone: +32 50 28 83 20  
 E-mail: info.be@analytichem.com  
 Contact person: SDS service department  
 E-mail: SDS@analytichem.com  
 Responsible Department: AnalytiChem:  
 EU-Belgium: AnalytiChem Belgium, Industriezone "De Arend" 2, 8210 Zedelgem, Belgium, +32 50 28 83 20  
 EU-Germany: AnalytiChem Germany, Stempelstrasse 6, 47167 Duisburg, Germany, +49 203 51 94 – 200  
 EU-Netherlands: AnalytiChem Netherlands, Communicatieweg 7, 3641 SG Mijdrecht, The Netherlands, +31 297 286848  
 UK: AnalytiChem UK, Unit 7 Launton Business Center, Murdock Road, Bicester, OX26 4XB, England, +44 1869 355 500  
 USA: AnalytiChem USA, 227 China Road, Winslow, Maine, 04901, United States, +1 800-244-8378  
 Canada: AnalytiChem Canada, 21800 Clark Graham Avenue, Baie d'Urfe, H9X 4B6, Canada, +1 514-457-0701  
 Australia: ORE Research & Exploration Pty Ltd, 37A Hosie Street, Bayswater North, 3153, Australia, +61 3 9729 0333  
 +44 20 3807 3798 (CHEMTREC)

**1.4. Emergency telephone number:**

**Further Information**

inapplicable, this product is a mixture REACH registration number see section 3

**Potassium hydroxide 0.01 mol/l in Propan**

Revision: 27.05.2025

Product code: AC15.00477

Page 2 of 12

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Flam. Liq. 2; H225  
Met. Corr. 1; H290  
Eye Irrit. 2; H319  
STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

**2.2. Label elements****Regulation (EC) No 1272/2008****Hazard components for labelling**

"propan-2-ol; isopropyl alcohol; isopropanol"

**Signal word:** Danger**Pictograms:****Hazard statements**

H225 Highly flammable liquid and vapour.  
H290 May be corrosive to metals.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P390 Absorb spillage to prevent material damage.  
P403+P235 Store in a well-ventilated place. Keep cool.  
P501 Dispose of contents/container to an appropriate recycling or disposal facility.

**2.3. Other hazards**

No data available

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Relevant ingredients**

| CAS No  | Chemical name   |              |                  | Quantity     |
|---------|---|--------------|------------------|--------------|
|         | EC No   | Index No     | REACH No         |              |
|         | Classification (Regulation (EC) No 1272/2008)         |              |                  |              |
| 67-63-0 | "propan-2-ol; isopropyl alcohol; isopropanol"         |              |                  | 95 - < 100 % |
|         | 200-661-7   | 603-117-00-0 | 01-2119457558-25 |              |
|         | Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 |              |                  |              |

Full text of H and EUH statements: see section 16.

**Potassium hydroxide 0.01 mol/l in Propan**

Revision: 27.05.2025

Product code: AC15.00477

Page 3 of 12

**Further Information**

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

No data available

**After inhalation**

Provide fresh air.

Call a physician immediately.

**After contact with skin**

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

**After contact with eyes**

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

**After ingestion**

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

**4.2. Most important symptoms and effects, both acute and delayed**

Irritant

Respiratory complaints

Headache

Gastrointestinal complaints

Dizziness

Dizziness

Inebriation

Anaesthetic state

Unconsciousness

Repeated exposure may cause skin dryness or cracking.

**4.3. Indication of any immediate medical attention and special treatment needed**

No data available

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Co-ordinate fire-fighting measures to the fire surroundings.

**Unsuitable extinguishing media**

no restriction

**5.2. Special hazards arising from the substance or mixture**

Combustible liquids

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO<sub>2</sub>), Carbon monoxide

Heating causes rise in pressure with risk of bursting.

Beware of reignition.

**Potassium hydroxide 0.01 mol/l in Propan**

Revision: 27.05.2025

Product code: AC15.00477

Page 4 of 12

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.  
In case of fire and/or explosion do not breathe fumes.  
Avoid contact with skin, eyes and clothes.

**Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.  
Move undamaged containers from immediate hazard area if it can be done safely.  
Use water spray jet to protect personnel and to cool endangered containers.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Keep away from sources of ignition - No smoking.  
This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).  
Take action to prevent static discharges.  
Corrosive to metals.

**For non-emergency personnel**

Provide adequate ventilation.  
Use personal protection equipment.  
Avoid contact with skin, eyes and clothes.  
Remove persons to safety.  
Emergency procedures  
Consult an expert  
Do not breathe dust/fume/gas/mist/vapours/spray.

**For emergency responders**

Precautionary statements For emergency responders : Personal protection equipment: see section 8

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains.  
The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.  
Danger of explosion

**6.3. Methods and material for containment and cleaning up****For containment**

Cover drains.  
Prevent spread over a wide area (e.g. by containment or oil barriers).  
Collect in closed and suitable containers for disposal.  
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

**For cleaning up**

Clean contaminated articles and floor according to the environmental legislation.

**Other information**

Provide adequate ventilation.  
Do not breathe dust/fume/gas/mist/vapours/spray.  
Wear breathing apparatus if exposed to vapours/dusts/aerosols.

**6.4. Reference to other sections**

Safe handling: see section 7  
Personal protection equipment: see section 8  
Disposal: see section 13

**Potassium hydroxide 0.01 mol/l in Propan**

Revision: 27.05.2025

Product code: AC15.00477

Page 5 of 12

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Read label before use. Handle and open container with care.  
When using do not eat, drink, smoke, sniff. Keep container tightly closed.  
Use personal protection equipment. Use extractor hood (laboratory).  
Do not breathe vapour/aerosol. Provide adequate ventilation.  
Avoid: aerosol or mist formation

**Advice on protection against fire and explosion**

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Advice on general occupational hygiene**

Keep away from food, drink and animal feedingstuffs.  
Wash hands and face before breaks and after work and take a shower if necessary.  
When using do not eat or drink.  
Avoid: aerosol or mist formation  
Do not breathe vapour/aerosol.

**Further information on handling**

Take off immediately all contaminated clothing and wash it before reuse.  
Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place.  
Store in a cool dry place.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Hints on joint storage**

National regulatory information

**Further information on storage conditions**

Protect from sunlight.

**7.3. Specific end use(s)**

Laboratory chemicals

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Exposure limits (EH40)**

| CAS No  | Substance   | ppm | mg/m <sup>3</sup> | fibres/ml | Category      | Origin |
|---------|-------------|-----|-------------------|-----------|---------------|--------|
| 67-63-0 | Propan-2-ol | 400 | 999               |           | TWA (8 h)     | WEL    |
|         |             | 500 | 1250              |           | STEL (15 min) | WEL    |

## Potassium hydroxide 0.01 mol/l in Propan

Revision: 27.05.2025

Product code: AC15.00477

Page 6 of 12

## DNEL/DMEL values

| CAS No                   | Substance                                     |                |          |                  |
|--------------------------|---|----------------|----------|------------------|
| DNEL type                |   | Exposure route | Effect   | Value            |
| 67-63-0                  | "propan-2-ol; isopropyl alcohol; isopropanol" |                |          |                  |
| Worker DNEL, long-term   |   | inhalation     | systemic | 500 mg/m³        |
| Worker DNEL, long-term   |   | dermal         | systemic | 888 mg/kg bw/day |
| Consumer DNEL, long-term |   | inhalation     | systemic | 89 mg/m³         |
| Consumer DNEL, long-term |   | dermal         | systemic | 319 mg/kg bw/day |
| Consumer DNEL, long-term |   | oral           | systemic | 26 mg/kg bw/day  |

## PNEC values

| CAS No   | Substance                                     |  |
|--|---|--|
| Environmental compartment                        | Value   |  |
| 67-63-0  | "propan-2-ol; isopropyl alcohol; isopropanol" |  |
| Freshwater                                       | 140,9 mg/l                                    |  |
| Freshwater (intermittent releases)               | 140,9 mg/l                                    |  |
| Marine water                                     | 140,9 mg/l                                    |  |
| Freshwater sediment                              | 552 mg/kg                                     |  |
| Marine sediment                                  | 552 mg/kg                                     |  |
| Secondary poisoning                              | 160 mg/kg                                     |  |
| Micro-organisms in sewage treatment plants (STP) | 2251 mg/l                                     |  |
| Soil   | 28 mg/kg                                      |  |

## 8.2. Exposure controls

## Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

## Individual protection measures, such as personal protective equipment

## Eye/face protection

goggles

Face protection umbrella

## Hand protection

Wear suitable gloves. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

## Skin protection

Wear fire resistant or flame retardant clothing.

Take off immediately all contaminated clothing and wash it before reuse.

Wear suitable protective clothing. Take off immediately all contaminated clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

## Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

**Potassium hydroxide 0.01 mol/l in Propan**

Revision: 27.05.2025

Product code: AC15.00477

Page 7 of 12

**Thermal hazards**

No data available

**Environmental exposure controls**

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Danger of explosion

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

|   |                        |
|---|------------------------|
| Physical state:   | Liquid                 |
| Colour:   | colourless             |
| Odour:  | like: Alcohol          |
| Odour threshold:  | No data available      |
| Melting point/freezing point:                             | No data available      |
| Boiling point or initial boiling point and boiling range: | ~82 °C                 |
| Flammability:   | No data available      |
| Lower explosion limits:                                   | 2 vol. %               |
| Upper explosion limits:                                   | 13 vol. %              |
| Flash point:  | ~13 °C                 |
| Auto-ignition temperature:                                | ~425 °C                |
| Decomposition temperature:                                | No data available      |
| pH-Value:   | 12                     |
| Viscosity / kinematic:                                    | No data available      |
| Water solubility:   | Soluble in: Water      |
| Solubility in other solvents                              | No data available      |
| Dissolution rate:   | No data available      |
| Partition coefficient n-octanol/water:                    | No data available      |
| Dispersion stability:                                     | No data available      |
| Vapour pressure:  | No data available      |
| Density:  | 0,78 g/cm <sup>3</sup> |
| Relative density:   | No data available      |
| Bulk density:   | No data available      |
| Relative vapour density:                                  | No data available      |
| Particle characteristics:                                 | No data available      |

**9.2. Other information****Information with regard to physical hazard classes****Explosive properties**

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

**Sustained combustibility:**

Sustained combustibility

**Self-ignition temperature**

Solid:

No data available

Gas:

No data available

**Oxidizing properties**

No data available

**Other safety characteristics****Evaporation rate:**

No data available

**Solvent separation test:**

No data available

**Potassium hydroxide 0.01 mol/l in Propan**

Revision: 27.05.2025

Product code: AC15.00477

Page 8 of 12

|                      |                   |
|----------------------|-------------------|
| Solvent content:     | No data available |
| Solid content:       | No data available |
| Sublimation point:   | No data available |
| Softening point:     | No data available |
| Pour point:          | No data available |
| Viscosity / dynamic: | No data available |
| Flow time:           | No data available |

**Further Information**

No data available

**SECTION 10: Stability and reactivity****10.1. Reactivity**

Vapours may form explosive mixtures with air.

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

Oxidising agent, Alkali metals, Alkaline earth metal  
chromium trioxide, Nitric acid, aldehydes  
Amines, Aluminium, Chlorine (Cl<sub>2</sub>)  
Phosphorus trichloride, Strong acid, Phosgene  
Hydrogen peroxide, Nitrogen oxides (NO<sub>x</sub>), Iron.

**10.4. Conditions to avoid**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**10.5. Incompatible materials**

Glass  
Metal  
Plastic articles

**10.6. Hazardous decomposition products**

in case of fire, see:  
SECTION 5: Firefighting measures

**Further information**

No data available

**SECTION 11: Toxicological information****11.1. Information on hazard classes****Toxicokinetics, metabolism and distribution**

No data available

**Acute toxicity**

Based on available data, the classification criteria are not met.  
Mucous membrane irritation in the mouth, throat, esophagus and gastrointestinal tract.

**ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

**Irritation and corrosivity**

Serious eye damage/eye irritation: Causes serious eye irritation.  
Skin corrosion/irritation: Based on available data, the classification criteria are not met.  
Repeated exposure may cause skin dryness or cracking.



**Potassium hydroxide 0.01 mol/l in Propan**

Revision: 27.05.2025

Product code: AC15.00477

Page 9 of 12

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause drowsiness or dizziness. ("propan-2-ol; isopropyl alcohol; isopropanol")

Organs affected: central nervous system

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

Observe risk of aspiration if vomiting occurs.

**Specific effects in experiment on an animal**

No data available

**Additional information on tests**

No data available

**Practical experience**

No data available

**11.2. Information on other hazards****Endocrine disrupting properties**

No data available

**Other information**

Pulmonary oedema Pneumonia

**Further information**

Irritant

Respiratory complaints

Headache

Gastrointestinal complaints

Dizziness

Dizziness

Inebriation

Anaesthetic state

Unconsciousness

Repeated exposure may cause skin dryness or cracking.

**SECTION 12: Ecological information****12.1. Toxicity**

Based on available data, the classification criteria are not met.

| CAS No  | Chemical name                                 |                 |           |                     |                    |                    |
|---------|---|-----------------|-----------|---------------------|--------------------|--------------------|
|         | Aquatic toxicity                              | Dose            | [h]   [d] | Species             | Source             | Method             |
| 67-63-0 | "propan-2-ol; isopropyl alcohol; isopropanol" |                 |           |                     |                    |                    |
|         | Acute fish toxicity                           | LC50 10000 mg/l | 96 h      | Pimephales promelas | Publication (1983) | OECD Guideline 203 |

**12.2. Persistence and degradability**

There are no data available on the mixture itself.

**12.3. Bioaccumulative potential**

**Potassium hydroxide 0.01 mol/l in Propan**

Revision: 27.05.2025

Product code: AC15.00477

Page 10 of 12

There are no data available on the mixture itself.

**Partition coefficient n-octanol/water**

| CAS No  | Chemical name                                 | Log Pow |
|---------|---|---------|
| 67-63-0 | "propan-2-ol; isopropyl alcohol; isopropanol" | 0,05    |

**12.4. Mobility in soil**

There are no data available on the mixture itself.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

Avoid release to the environment.

**Further information**

Do not allow to enter into surface water or drains.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.  
Send to a physico-chemical treatment facility under observation of official regulations.  
Do not mix with other wastes.

**Contaminated packaging**

Handle contaminated packages in the same way as the substance itself.  
Waste codes/waste designations according to EWC/AVV

**SECTION 14: Transport information****Land transport (ADR/RID)**

|  |                                 |
|--|---------------------------------|
| <b>14.1. UN number or ID number:</b>     | UN 1219                         |
| <b>14.2. UN proper shipping name:</b>    | ISOPROPANOL (ISOPROPYL ALCOHOL) |
| <b>14.3. Transport hazard class(es):</b> | 3                               |
| <b>14.4. Packing group:</b>              | II                              |
| Hazard label:                            | 3                               |
| Classification code:                     | F1                              |
| Special Provisions:                      | 601                             |
| Limited quantity:                        | 1 L                             |
| Excepted quantity:                       | E2                              |
| Transport category:                      | 2                               |
| Hazard No:                               | 33                              |
| Tunnel restriction code:                 | D/E                             |

**Inland waterways transport (ADN)**

|  |                                 |
|--|---------------------------------|
| <b>14.1. UN number or ID number:</b>     | UN 1219                         |
| <b>14.2. UN proper shipping name:</b>    | ISOPROPANOL (ISOPROPYL ALCOHOL) |
| <b>14.3. Transport hazard class(es):</b> | 3                               |
| <b>14.4. Packing group:</b>              | II                              |
| Hazard label:                            | 3                               |
| Classification code:                     | F1                              |
| Special Provisions:                      | 601                             |

**Potassium hydroxide 0.01 mol/l in Propan**

Revision: 27.05.2025

Product code: AC15.00477

Page 11 of 12

Limited quantity: 1 L

Excepted quantity: E2

**Marine transport (IMDG)****14.1. UN number or ID number:** UN 1219**14.2. UN proper shipping name:** ISOPROPANOL (ISOPROPYL ALCOHOL)**14.3. Transport hazard class(es):** 3**14.4. Packing group:** II

Hazard label: 3

Special Provisions: -

Limited quantity: 1 L

Excepted quantity: E2

EmS: F-E, S-D

**Air transport (ICAO-TI/IATA-DGR)****14.1. UN number or ID number:** UN 1219**14.2. UN proper shipping name:** ISOPROPANOL**14.3. Transport hazard class(es):** 3**14.4. Packing group:** II

Hazard label: 3

Special Provisions: A180

Limited quantity Passenger: 1 L

Passenger LQ: Y341

Excepted quantity: E2

IATA-packing instructions - Passenger: 353

IATA-max. quantity - Passenger: 5 L

IATA-packing instructions - Cargo: 364

IATA-max. quantity - Cargo: 60 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Information according to Directive 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

**National regulatory information****SECTION 16: Other information****Abbreviations and acronyms**

Met. Corr. 1: Corrosive to metals, hazard category 1

Flam. Liq. 2: Flammable liquids, hazard category 2

Eye Irrit. 2: Eye irritation, hazard category 2

STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3

**Potassium hydroxide 0.01 mol/l in Propan**

Revision: 27.05.2025

Product code: AC15.00477

Page 12 of 12

**Classification for mixtures and used evaluation method**

| Classification     | Classification procedure |
|--------------------|--------------------------|
| Flam. Liq. 2; H225 | On basis of test data    |
| Met. Corr. 1; H290 | On basis of test data    |
| Eye Irrit. 2; H319 | Calculation method       |
| STOT SE 3; H336    | Calculation method       |

**Relevant H and EUH statements (number and full text)**

|      |                                     |
|------|-------------------------------------|
| H225 | Highly flammable liquid and vapour. |
| H290 | May be corrosive to metals.         |
| H319 | Causes serious eye irritation.      |
| H336 | May cause drowsiness or dizziness.  |

**Further Information**

Provide appropriate information, instructions and training to users

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*