

according to Regulation (EC) No 1907/2006

Eriochrome black T - Buffer solution

Revision: 07.10.2025 Product code: AC15.01457 Page 1 of 16

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Eriochrome black T - Buffer solution

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Reagents and laboratory chemicals Only for laboratory and analysis purposes.

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Details of the supplier of the safety data sheet

Company name: AnalytiChem Services, Unipessoal, Lda

Rua de Júlio Dinis 676 7º Street: N-4050-320 Porto Place: +351 226002917 Telephone: info@analytichem.com E-mail: SDS service department Contact person: SDS@analytichem.com F-mail: www.analvtichem.com Internet: SDS service department Responsible Department:

Supplier or manufacturer details

AnalytiChem Belgium NV Company name: Industriezone "De Arend" 2 Street:

Place: B-8210 Zedelgem +32 50 28 83 20 Telephone:

info.be@analytichem.com E-mail: SDS service department Contact person: SDS@analytichem.com E-mail:

Responsible Department: AnalytiChem:

EU-Belgium: AnalytiChem Belgium, Industriezone "De Arend" 2, 8210 Zedelgem,

Belgium, +32 50 28 83 20

EU-Germany: AnalytiChem Germany, Stempelstrasse 6, 47167 Duisburg,

Germany, +49 203 51 94 - 200

EU-Netherlands: AnalytiChem Netherlands, Communicatieweg 7, 3641 SG

Mijdrecht, The Netherlands, +31 297 286848

UK: AnalytiChem UK, Unit 7 Launton Business Center, Murdock Road, Bicester,

OX26 4XB, England, +44 1869 355 500

USA: AnalytiChem USA, 227 China Road, Winslow, Maine, 04901, United States,

+1 800-244-8378

Canada: AnalytiChem Canada, 21800 Clark Graham Avenue, Baie d'Urfe, H9X

Print date: 08.11.2025

4B6, Canada, +1 514-457-0701

+353 1 901 4670 (CHEMTREC)

Australia: ORE Research & Exploration Pty Ltd, 37A Hosie Street, Bayswater

North, 3153, Australia, +61 3 9729 0333

1.4. Emergency telephone

number:

Revision No. 1 00

Further Information

No data available

IRI - en



according to Regulation (EC) No 1907/2006

Eriochrome black T - Buffer solution

Revision: 07.10.2025 Product code: AC15.01457 Page 2 of 16

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 2; H225 Met. Corr. 1; H290 Skin Corr. 1B; H314 Eye Dam. 1; H318 STOT SE 3; H335 H336 Aquatic Acute 1; H400 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

"propan-2-ol; isopropyl alcohol; isopropanol"

Ammonia

Signal word: Danger

Pictograms:









Hazard statements

H225 Highly flammable liquid and	vapour.
----------------------------------	---------

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H335 May cause respiratory irritation.H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P260 Do not breathe mist/vapours/spray.

P264 Wash hands and face thoroughly after handling.

P280 Wear protective gloves/protective clothing and eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

Special labelling of certain mixtures

EUH208 Contains 2-aminoethanol. May produce an allergic reaction.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures



according to Regulation (EC) No 1907/2006

Eriochrome black T - Buffer solution

Revision: 07.10.2025 Product code: AC15.01457 Page 3 of 16

Relevant ingredients

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification (Regulat	ion (EC) No 1272/2008)	·		
67-63-0	"propan-2-ol; isopropyl	alcohol; isopropanol"		65 - < 70 %	
	200-661-7	603-117-00-0	01-2119457558-25		
	Flam. Liq. 2, Eye Irrit.	2, STOT SE 3; H225 H319 H336			
1336-21-6	Ammonia			5 - < 10 %	
	215-647-6	007-001-01-2	01-2119488876-14		
	Skin Corr. 1B, Aquatic	Acute 1, Aquatic Chronic 2; H314 H40	0 H411		
12125-02-9	ammonium chloride			1 - < 5 %	
	235-186-4	017-014-00-8	01-2119487950-27		
	Acute Tox. 4, Eye Irrit.	2; H302 H319			
141-43-5	2-aminoethanol			< 1 %	
	205-483-3	603-030-00-8	01-2119486455-28		
	Acute Tox. 4, Acute To H332 H312 H302 H31	x. 4, Acute Tox. 4, Skin Corr. 1B, Eye l 4 H318 H317 H335	Dam. 1, Skin Sens. 1, STOT SE 3;		

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

opecinic donic. Elinits, in-lactors and ATE					
CAS No	EC No	Chemical name	Quantity		
	Specific Conc	Limits, M-factors and ATE			
1336-21-6	215-647-6	Ammonia	5 - < 10 %		
		C50 = 4230 mg/l (vapours); oral: LD50 = 350 mg/kg STOT SE 3; H335: >= 5 - 100 1; H400: M=10			
12125-02-9	235-186-4	ammonium chloride	1 - < 5 %		
	dermal: LD50) = > 2000 mg/kg; oral: LD50 = 1410 mg/kg			
141-43-5	205-483-3	2-aminoethanol	< 1 %		
		E = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = oral: LD50 = ca. 1515 mg/kg			

Further Information

No data available

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection!

After inhalation

Provide fresh air.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Remove contact lenses, if present and easy to do. Continue rinsing.



according to Regulation (EC) No 1907/2006

Eriochrome black T - Buffer solution

Revision: 07.10.2025 Product code: AC15.01457 Page 4 of 16

Protect uninjured eye.

After ingestion

If swallowed, immediately drink: Water

Do NOT induce vomiting.

Do not allow a neutralisation agent to be drunk.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns.

Irritant

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Combustible liquids

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated:

Carbon dioxide

Carbon monoxide

Nitrogen oxides (NOx)

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

Heating causes rise in pressure with risk of bursting.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Vapours can form explosive mixtures with air.

May be corrosive to metals.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

To follow: Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8



according to Regulation (EC) No 1907/2006

Eriochrome black T - Buffer solution

Revision: 07.10.2025 Product code: AC15.01457 Page 5 of 16

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Explosion risk.

6.3. Methods and material for containment and cleaning up

For containment

Cover drains

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Collect in closed and suitable containers for disposal.

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use.

Handle and open container with care.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Do not breathe dust/fume/gas/mist/vapours/spray.

Provide adequate ventilation.

Use extractor hood (laboratory).

Advice on protection against fire and explosion

Take precautionary measures against static discharges.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Advice on general occupational hygiene

Keep away from: Food and feedingstuffs

When using do not eat, drink, smoke, sniff.

Provide eye shower and label its location conspicuously

In the immediate working surroundings there must be: Emergency shower installed

Further information on handling

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary $\!.$

Take off immediately all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities



according to Regulation (EC) No 1907/2006

Eriochrome black T - Buffer solution

Revision: 07.10.2025 Product code: AC15.01457 Page 6 of 16

Requirements for storage rooms and vessels

Keep container tightly closed.

Corrosive to metals.

Unsuitable container/equipment material: Metal

Protect against: Radiant heat.

Hints on joint storage

national regulations /National regulations

Further information on storage conditions

Store in a dry place.

Store in a well-ventilated place.

7.3. Specific end use(s)

The product is intended for research, analysis and scientific education.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
7664-41-7	Ammonia, anhydrous	20	14		TWA (8 h)	
		50	36		STEL (15 min)	•
12125-02-9	Ammonium chloride, fume	-	10		TWA (8 h)	•
		-	20		STEL (15 min)	•
141-43-5	Ethanolamine (2-Aminoethanol)	1	2.5		TWA (8 h)	•
		3	7.6		STEL (15 min)	•
67-63-0	Propan-2-ol	200	-		TWA (8 h)	1
		400	-		STEL (15 min)	•
102-71-6	Triethanolamine	-	5		TWA (8 h)	

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
67-63-0	2-Propanol	Acetone	40 mg/L		End of shift at end of workweek



according to Regulation (EC) No 1907/2006

Eriochrome black T - Buffer solution

Revision: 07.10.2025 Product code: AC15.01457 Page 7 of 16

DNEL/DMEL values

CAS No	Substance			
DNEL type	•	Exposure route	Effect	Value
67-63-0	"propan-2-ol; isopropyl alcohol; isopropanol"			
Worker DNEL	, long-term	inhalation	systemic	500 mg/m³
Worker DNEL	, long-term	dermal	systemic	888 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	systemic	89 mg/m³
Consumer DN	EL, long-term	dermal	systemic	319 mg/kg bw/day
Consumer DN	EL, long-term	oral	systemic	26 mg/kg bw/day
1336-21-6	Ammonia	·		
Worker DNEL	long-term	inhalation	systemic	47,6 mg/m³
Worker DNEL	, acute	inhalation	systemic	47,6 mg/m³
Worker DNEL	, long-term	inhalation	local	14 mg/m³
Worker DNEL	, acute	inhalation	local	36 mg/m³
Worker DNEL	, long-term	dermal	systemic	6,8 mg/kg bw/day
Worker DNEL	, acute	dermal	systemic	6,8 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	systemic	23,8 mg/m³
Consumer DN	EL, acute	inhalation	systemic	23,8 mg/m³
Consumer DN	EL, long-term	inhalation	local	2,8 mg/m³
Consumer DN	EL, acute	inhalation	local	7,2 mg/m³
Consumer DN	EL, long-term	dermal	systemic	68 mg/kg bw/day
Consumer DN	EL, acute	dermal	systemic	68 mg/kg bw/day
Consumer DN	EL, long-term	oral	systemic	6,8 mg/kg bw/day
Consumer DN	EL, acute	oral	systemic	6,8 mg/kg bw/day
12125-02-9	ammonium chloride			
Worker DNEL	, long-term	inhalation	systemic	33,5 mg/m³
Worker DNEL	, long-term	dermal	systemic	190 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	systemic	9,9 mg/m³
Consumer DN	EL, long-term	dermal	systemic	114 mg/kg bw/day
Consumer DN	EL, long-term	oral	systemic	11,4 mg/kg bw/day
102-71-6	Triethanolamine			
Consumer DN	EL, long-term	inhalation	local	1,25 mg/m³
Worker DNEL	, long-term	inhalation	systemic	5 mg/m³
Worker DNEL	, long-term	inhalation	local	5 mg/m³
Worker DNEL	, long-term	dermal	systemic	6,3 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	systemic	1,25 mg/m³
Consumer DN	EL, long-term	dermal	systemic	3,1 mg/kg bw/day
Consumer DN	EL, long-term	oral	systemic	13 mg/kg bw/day
141-43-5	2-aminoethanol			
Worker DNEL	, long-term	inhalation	local	3,3 mg/m³
Worker DNEL	, long-term	dermal	systemic	1 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	local	2 mg/m³



according to Regulation (EC) No 1907/2006

Revision: 07.10.2025 Product code: AC15.01457 Page 8 of 16

Consumer DNEL, long-term	dermal	systemic	0,24 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	3,75 mg/kg bw/day

PNEC values

PNEC values	
CAS No Substance	
Environmental compartment	Value
67-63-0 "propan-2-ol; isopropyl alcohol; isopropanol"	
Freshwater	140,9 mg/l
Freshwater (intermittent releases)	140,9 mg/l
Marine water	140,9 mg/l
Freshwater sediment	552 mg/kg
Marine sediment	552 mg/kg
Secondary poisoning	160 mg/kg
Micro-organisms in sewage treatment plants (STP)	2251 mg/l
Soil	28 mg/kg
1336-21-6 Ammonia	
Freshwater	0,001 mg/l
Freshwater (intermittent releases)	0,007 mg/l
Marine water	0,001 mg/l
12125-02-9 ammonium chloride	
Freshwater	1,2 mg/l
Freshwater (intermittent releases)	1,2 mg/l
Marine water	11,2 mg/l
Micro-organisms in sewage treatment plants (STP)	16,2 mg/l
Soil	0,163 mg/kg
102-71-6 Triethanolamine	
Freshwater	0,32 mg/l
Freshwater (intermittent releases)	5,12 mg/l
Marine water	0,032 mg/l
Freshwater sediment	1,7 mg/kg
Marine sediment	0,17 mg/kg
Micro-organisms in sewage treatment plants (STP)	10 mg/l
Soil	0,151 mg/kg
141-43-5 2-aminoethanol	
Freshwater	0,085 mg/l
Freshwater (intermittent releases)	0,028 mg/l
Marine water	0,009 mg/l
Freshwater sediment	0,434 mg/kg
Marine sediment	0,043 mg/kg
Micro-organisms in sewage treatment plants (STP)	100 mg/l
Soil	0,037 mg/kg

Additional advice on limit values

Observe in addition any national regulations!



according to Regulation (EC) No 1907/2006

Eriochrome black T - Buffer solution

Revision: 07.10.2025 Product code: AC15.01457 Page 9 of 16

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Face protection umbrella

Hand protection

Tested protective gloves must be worn

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing. Flame-retardant protective clothing . Wear anti-static footwear and clothing When handling with chemical substances, protective clothing with CE-labels including the four control digits must be worn.

Take off immediately all contaminated clothing and wash it before reuse.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Thermal hazards

No data available

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:

Colour:

Odour:

Odour threshold:

Liquid

black

characteristic

No data available

Melting point/freezing point:

-89 °C

Boiling point or initial boiling point and

82 °C

boiling range:

No data available Flammability: No data available Lower explosion limits: No data available Upper explosion limits: Flash point: 12 °C No data available Auto-ignition temperature: No data available Decomposition temperature: 11-12 pH-Value: No data available Viscosity / kinematic: Water solubility: No data available

Solubility in other solvents

No data available

Dissolution rate:

Partition coefficient n-octanol/water:

Dispersion stability:

No data available

No data available

No data available



according to Regulation (EC) No 1907/2006

Eriochrome black T - Buffer solution

Revision: 07.10.2025 Product code: AC15.01457 Page 10 of 16

Vapour pressure:No data availableVapour pressure:No data availableDensity:0,82 g/cm³Relative density:No data availableBulk density:No data availableRelative vapour density:No data availableParticle characteristics:No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

Vapours can form explosive mixtures with air.

Sustained combustibility:

No data available

Self-ignition temperature

Solid: No data available
Gas: No data available

Oxidizing properties

Oxidizing

Other safety characteristics

Evaporation rate:

Solvent separation test:

No data available
Solvent content:

No data available
Solid content:

No data available
Sublimation point:

No data available
Softening point:

No data available
Pour point:

No data available

No data available:

Viscosity / dynamic: No data available Flow time: No data available

Further Information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapours can form explosive mixtures with air.

Corrosive to metals.

10.2. Chemical stability

Protect against: Radiant heat.

10.3. Possibility of hazardous reactions

Oxidising agent

Acid

10.4. Conditions to avoid

Radiant heat.

10.5. Incompatible materials

Metal

10.6. Hazardous decomposition products

In case of fire may be liberated: SECTION 5: Firefighting measures



according to Regulation (EC) No 1907/2006

Eriochrome black T - Buffer solution

Revision: 07.10.2025 Product code: AC15.01457 Page 11 of 16

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 5000 mg/kg; ATE (dermal) > 2000 mg/kg

CAS No	Chemical name								
	Exposure route	Dose		Species	Source	Method			
1336-21-6	Ammonia								
	oral	LD50 mg/kg	350	Rat	Journal of Industrial Hygiene and Toxico	OECD Guideline 401			
	inhalation (1 h) vapour	LC50 mg/l	4230	Mouse	Bull. Environm. Contam. Toxicol, 1982, 2	Assessment of acute inhalation toxicity			
12125-02-9	ammonium chloride								
	oral	LD50 mg/kg	1410	Rat	Other company data (1983)	other: not mentioned			
	dermal	LD50 mg/kg	> 2000	Rat	Study report (2010)	EU Method B.3			
141-43-5	2-aminoethanol				·	·			
	oral	LD50 mg/kg	ca. 1515	Rat	Study report (1966)	OECD Guideline 401			
	dermal	LD50 mg/kg	2504	Rabbit	Study report (1988)	OECD Guideline 402			
	inhalation vapour	ATE	11 mg/l						
	inhalation dust/mist	ATE	1,5 mg/l						

Irritation and corrosivity

Skin corrosion/irritation: Causes severe skin burns and eye damage.

Serious eye damage/eye irritation: Causes serious eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

Contains 2-aminoethanol. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (Ammonia)

May cause drowsiness or dizziness. ("propan-2-ol; isopropyl alcohol; isopropanol")

STOT-repeated exposure

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

Eriochrome black T - Buffer solution

Revision: 07.10.2025 Product code: AC15.01457 Page 12 of 16

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

No data available

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

No data available

11.2. Information on other hazards

Endocrine disrupting properties

No data available

Other information

No data available

Further information

No data available

SECTION 12: Ecological information

12.1. Toxicity

Very toxic to aquatic life.

Harmful to aquatic life with long lasting effects.



according to Regulation (EC) No 1907/2006

Eriochrome black T - Buffer solution

Revision: 07.10.2025 Product code: AC15.01457 Page 13 of 16

CAS No	Chemical name								
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method		
67-63-0	"propan-2-ol; isopropyl ald	cohol; isopro	panol"						
	Acute fish toxicity	LC50 mg/l	10000	96 h	Pimephales promelas	Publication (1983)	OECD Guideline 203		
1336-21-6	Ammonia								
	Acute fish toxicity	LC50 3,4 mg/l	0,75 -	96 h	Pimephales promelas	Trans Amer Fish Soc; 112 (5). 1983. 705-	Assessment of acute toxicity in the fath		
	Acute crustacea toxicity	EC50	101 mg/l	48 h	Daphnia magna	Environ. Toxicol. Chem. 5: 443-447 (1986	other: ASTM E729-80		
	Fish toxicity	NOEC	1,2 mg/l	61 d	Oncorhynchus gorbuscha	Fish. Bull. 78(3): 641-648 (1980)	OECD Guideline 210		
12125-02-9	ammonium chloride								
	Acute fish toxicity	LC50	209 mg/l	96 h	Cyprinus carpio	Indian J. Environ. Health, 17, 140-146,	other: E03-05:APHA, AWWA & WPCF		
	Acute crustacea toxicity	EC50	101 mg/l	48 h	Daphnia magna	Env. Tox. Chem. 5, 443-447 (1986) (1986)	other: ASTM E729-80		
	Fish toxicity	NOEC	11,8 mg/l	28 d	Pimephales promelas	Env.Tox. Chem. 5, 437-442 (1986) (1986)	other: - Americar Society for Testing an		
	Algae toxicity	NOEC mg/l	26,8	10 d	Navicula sp.	Mar. Biol. 43(4), 307-315, (1977) (1977)	no data		
	Crustacea toxicity	NOEC mg/l	14,6	21 d	Daphnia magna	Env. Tox. Chem. 5, 443-447 (1986) (1986)	other: not mentioned		
	Acute bacteria toxicity	EC50 mg/l ()	1618	0,5 h	activated sludge, domestic	Study report (1988)	OECD Guideline 209		
141-43-5	2-aminoethanol								
	Acute fish toxicity	LC50	349 mg/l	96 h	Cyprinus carpio	Study report (1997)	other: Directive 92/69/EEC, C.1.		
	Acute algae toxicity	ErC50	2,8 mg/l	72 h	Pseudokirchneriella subcapitata	unpublished (1997)	OECD Guideline 201		
	Acute crustacea toxicity	EC50	65 mg/l	48 h	Daphnia magna	Study report (1997)	EU Method C.2		
	Fish toxicity	NOEC mg/l	1,24	41 d	Oryzias latipes	unpublished (2008)	OECD Guideline 210		
	Crustacea toxicity	NOEC mg/l	0,85	21 d	Daphnia magna	unpublished (1997)	other: OECD 202 "Daphnia sp., Acute Immo		

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available



according to Regulation (EC) No 1907/2006

Revision: 07.10.2025 Product code: AC15.01457 Page 14 of 16

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-63-0	"propan-2-ol; isopropyl alcohol; isopropanol"	0,05
1336-21-6	Ammonia	-1,38
141-43-5	2-aminoethanol	-2,3

BCF

CAS No	Chemical name	BCF	Species	Source
141-43-5	2-aminoethanol	2,3		SAR and QSAR in Envi

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Discharge into the environment must be avoided.

Further information

Do not allow to enter into surface water or drains.

Explosion risk.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Send to a physico-chemical treatment facility under observation of official regulations.

Do not allow to enter into surface water or drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 2924

14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (propan-2-ol, Ammonia)

14.3. Transport hazard class(es): 14.4. Packing group: Ш 3+8 Hazard label: Classification code: FC 274 Special Provisions: 5 L Limited quantity: E1 Excepted quantity: 3 Transport category: 38 Hazard No: Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 2924

14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (propan-2-ol, Ammonia)

14.3. Transport hazard class(es): 3
14.4. Packing group: |||



according to Regulation (EC) No 1907/2006

Eriochrome black T - Buffer solution				
Revision: 07.10.2025	Product code: A	AC15.01457	Page 15 of 16	
Hazard label:	3+8			
Classification code:	FC			
Special Provisions:	274			
Limited quantity:	5 L			
Excepted quantity:	E1			
Marine transport (IMDG)				
14.1. UN number or ID number:	UN 2924			
14.2. UN proper shipping name:	FLAMMABLE LIQUID,	, CORROSIVE, N.O.S. (propan-2-ol, Ammonia)		
14.3. Transport hazard class(es):	3			
14.4. Packing group:	III			
Hazard label:	3+8			
Special Provisions:	223 274			
Limited quantity:	5 L			
Excepted quantity:	E1			
EmS:	F-E, S-C			
Air transport (ICAO-TI/IATA-DGR)				
14.1. UN number or ID number:	UN 2924			
14.2. UN proper shipping name:	FLAMMABLE LIQUID,	, CORROSIVE, N.O.S. (propan-2-ol, Ammonia)		
14.3. Transport hazard class(es):	3			
14.4. Packing group:	III			
Hazard label:	3+8			
Special Provisions:	A3 A803			
Limited quantity Passenger:	1 L			
Passenger LQ:	Y342			
Excepted quantity:	E1			
IATA-packing instructions - Passenger:	-	354		
IATA-max. quantity - Passenger:		5 L		
IATA-packing instructions - Cargo:		365		
IATA-max. quantity - Cargo:	6	60 L		
14.5. Environmental hazards				
ENVIRONMENTALLY HAZARDOUS:	Yes			

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ammonia

EU regulatory information

Danger releasing substance:

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Information according to Directive

E1 Hazardous to the Aquatic Environment

2012/18/EU (SEVESO III):

Additional information: P5c

Additional information

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing ...

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

SECTION 16: Other information



according to Regulation (EC) No 1907/2006

Eriochrome black T - Buffer solution

Revision: 07.10.2025 Product code: AC15.01457 Page 16 of 16

Abbreviations and acronyms

Met. Corr. 1: Corrosive to metals, hazard category 1 Flam. Liq. 2: Flammable liquids, hazard category 2 Acute Tox. 4: Acute toxicity, hazard category 4 Skin Corr. 1B: Skin corrosion, sub-category 1B Eye Dam. 1: Serious eye damage, hazard category 1 Eye Irrit. 2: Eye irritation, hazard category 2

Eye Irrit. 2: Eye irritation, hazard category 2 Skin Sens. 1: Skin sensitisation, hazard category 1

STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3 Aquatic Acute 1: Hazardous to the aquatic environment, hazard category: Acute 1

Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard category: Chronic 2

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Met. Corr. 1; H290	On basis of test data
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method
STOT SE 3; H335	Calculation method
STOT SE 3; H336	Calculation method
Aquatic Acute 1; H400	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains 2-aminoethanol. May produce an allergic rea

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)