

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Methanolysis Mixture E

Revision: 10.10.2025

Product code: AC15.02377

Page 1 of 15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Methanolysis Mixture E

UFI: X2SU-C2X4-C00H-U0T8

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Reagents and laboratory chemicals
Only for laboratory and analysis purposes.

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Details of the supplier of the safety data sheet

Company name: AnalytiChem Services, Unipessoal, Lda
Street: Rua de Júlio Dinis 676 7º
Place: P-4050-320 Porto
Telephone: +351 226002917
E-mail: info@analytichem.com
Contact person: SDS service department
E-mail: SDS@analytichem.com
Internet: www.analytichem.com
Responsible Department: SDS service department

Supplier or manufacturer details

Company name: AnalytiChem GmbH
Street: Stempelstraße 6
Place: D-47167 Duisburg
Telephone: 0203/5194-0
E-mail: info@analytichem.de
Contact person: SDS service department
E-mail: SDS@analytichem.com
Internet: www.analytichem.de
Responsible Department: AnalytiChem:
EU-Belgium: AnalytiChem Belgium, Industriezone "De Arend" 2, 8210 Zedelgem, Belgium, +32 50 28 83 20
EU-Germany: AnalytiChem Germany, Stempelstrasse 6, 47167 Duisburg, Germany, +49 203 51 94 – 200
EU-Netherlands: AnalytiChem Netherlands, Communicatieweg 7, 3641 SG Mijdrecht, The Netherlands, +31 297 286848
UK: AnalytiChem UK, Unit 7 Launton Business Center, Murdock Road, Bicester, OX26 4XB, England, +44 1869 355 500
USA: AnalytiChem USA, 227 China Road, Winslow, Maine, 04901, United States, +1 800-244-8378
Canada: AnalytiChem Canada, 21800 Clark Graham Avenue, Baie d'Urfe, H9X 4B6, Canada, +1 514-457-0701
Australia: ORE Research & Exploration Pty Ltd, 37A Hosie Street, Bayswater North, 3153, Australia, +61 3 9729 0333
+353 1 901 4670 (CHEMTREC)

1.4. Emergency telephone number:

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Methanolysis Mixture E

Revision: 10.10.2025

Product code: AC15.02377

Page 2 of 15

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 2; H225
Met. Corr. 1; H290
Acute Tox. 3; H331
Acute Tox. 3; H311
Acute Tox. 3; H301
Skin Corr. 1B; H314
Eye Dam. 1; H318
STOT SE 1; H370

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

methanol
potassium hydroxide

Signal word:

Danger

Pictograms:



Hazard statements

H225 Highly flammable liquid and vapour.
H290 May be corrosive to metals.
H301+H311+H331 Toxic if swallowed, in contact with skin or if inhaled.
H314 Causes severe skin burns and eye damage.
H370 Causes damage to organs.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Methanolysis Mixture E

Revision: 10.10.2025

Product code: AC15.02377

Page 3 of 15

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
67-56-1	methanol			95 - < 100 %
	200-659-6	603-001-00-X	01-2119433307-44	
	Flam. Liq. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, STOT SE 1; H225 H331 H311 H301 H370			
1310-58-3	potassium hydroxide			2 - < 5 %
	215-181-3	019-002-00-8	01-2119487136-33	
	Met. Corr. 1, Acute Tox. 4, Skin Corr. 1A, Eye Dam. 1; H290 H302 H314 H318			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
67-56-1	200-659-6	methanol	95 - < 100 %
	inhalation: LC50 = 128,2 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: LD50 = 6000 mg/kg STOT SE 1; H370: >= 10 - 100 STOT SE 2; H371: >= 3 - < 10		
1310-58-3	215-181-3	potassium hydroxide	2 - < 5 %
	oral: LD50 = 333 mg/kg Skin Corr. 1A; H314: >= 5 - 100 Skin Corr. 1B; H314: >= 2 - < 5 Skin Irrit. 2; H315: >= 0,5 - < 2 Eye Irrit. 2; H319: >= 0,5 - < 2		

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection!

After inhalation

Provide fresh air.

If breathing is irregular or stopped, administer artificial respiration.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

After eye contact: Rinse immediately carefully and thoroughly with eye-bath or water.

Remove contact lenses, if present and easy to do. Continue rinsing.

Consult an ophthalmologist.

After ingestion

Provide fresh air.

Call a physician immediately.

Notes for the doctor : Methanol

4.2. Most important symptoms and effects, both acute and delayed

Irritant, Dizziness

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Methanolysis Mixture E

Revision: 10.10.2025

Product code: AC15.02377

Page 4 of 15

Dizziness, Anaesthetic state
Agitation, Spasms
Inebriation, Vomiting
Headache, Impairment of vision
Repeated exposure may cause skin dryness or cracking.
corrosive

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**Water spray jet, Carbon dioxide (CO₂), Foam, Extinguishing powder.**Unsuitable extinguishing media**

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquids
Highly flammable.
Hazardous combustion products
In case of fire may be liberated: Carbon dioxide, Carbon monoxide
Vapours are heavier than air, spread along floors and form explosive mixtures with air.
Beware of reignition.
Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.
Wear full chemical protective clothing.
In case of fire and/or explosion do not breathe fumes.

Additional information

Use water spray jet to protect personnel and to cool endangered containers.
Move undamaged containers from immediate hazard area if it can be done safely.
Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Keep away from sources of ignition - No smoking.
This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).
Take action to prevent static discharges.
Corrosive to metals.

For non-emergency personnel

Provide adequate ventilation.
Use personal protection equipment.
Avoid contact with skin, eyes and clothes.
Remove persons to safety.
Emergency procedures
Consult an expert
Do not breathe dust/fume/gas/mist/vapours/spray.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Methanolysis Mixture E

Revision: 10.10.2025

Product code: AC15.02377

Page 5 of 15

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

6.3. Methods and material for containment and cleaning up**For containment**

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Avoid exposure - obtain special instructions before use.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep in a cool, well-ventilated place.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Methanolysis Mixture E

Revision: 10.10.2025

Product code: AC15.02377

Page 6 of 15

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.
national regulations

Further information on storage conditions

Keep cool. Protect from sunlight.
Unsuitable container/equipment material: Metal

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
67-56-1	Methyl alcohol	200	260		TWA (8 h)	
1310-58-3	Potassium hydroxide	-	2		STEL (15 min)	

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
67-56-1	Methanol	Methanol	15 mg/L	Urine	End of shift

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
67-56-1	methanol			
Consumer DNEL, acute	inhalation	systemic	50 mg/m ³	
Worker DNEL, long-term	inhalation	systemic	260 mg/m ³	
Worker DNEL, acute	inhalation	systemic	260 mg/m ³	
Worker DNEL, long-term	inhalation	local	260 mg/m ³	
Worker DNEL, acute	inhalation	local	260 mg/m ³	
Worker DNEL, long-term	dermal	systemic	40 mg/kg bw/day	
Worker DNEL, acute	dermal	systemic	40 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	systemic	50 mg/m ³	
Consumer DNEL, long-term	inhalation	local	50 mg/m ³	
Consumer DNEL, acute	inhalation	local	50 mg/m ³	
Consumer DNEL, long-term	dermal	systemic	8 mg/kg bw/day	
Consumer DNEL, acute	dermal	systemic	8 mg/kg bw/day	
Consumer DNEL, long-term	oral	systemic	8 mg/kg bw/day	
Consumer DNEL, acute	oral	systemic	8 mg/kg bw/day	
1310-58-3	potassium hydroxide			
Worker DNEL, long-term	inhalation	local	1 mg/m ³	
Consumer DNEL, long-term	inhalation	local	1 mg/m ³	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Methanolysis Mixture E

Revision: 10.10.2025

Product code: AC15.02377

Page 7 of 15

PNEC values

CAS No	Substance	
Environmental compartment		Value
67-56-1	methanol	
Freshwater		20,8 mg/l
Freshwater (intermittent releases)		1540 mg/l
Marine water		2,08 mg/l
Freshwater sediment		77 mg/kg
Marine sediment		7,7 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		100 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Do not breathe vapour/aerosol.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 898 Butoject®

Recommended material: Butyl caoutchouc (butyl rubber) 0,7 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 890 Vitoject®

Recommended material: FKM (fluoro rubber) 0,7 mm

Wearing time with occasional contact (splashes): > 120 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Take off immediately all contaminated clothing and wash it before reuse.

Wear fire resistant or flame retardant clothing.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Methanolysis Mixture E

Revision: 10.10.2025

Product code: AC15.02377

Page 8 of 15

Wash hands and face before breaks and after work and take a shower if necessary.

Draw up and observe skin protection programme.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Environmental exposure controls

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Danger of explosion

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	colourless
Odour:	like: Methanol
Melting point/freezing point:	No data available
Boiling point or initial boiling point and boiling range:	No data available
Flammability:	not applicable
Lower explosion limits:	No data available
Upper explosion limits:	No data available
Flash point:	~10 °C
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH-Value:	alkaline
Viscosity / kinematic:	No data available
Water solubility:	easily soluble
Solubility in other solvents	
not determined	
Partition coefficient n-octanol/water:	No data available
Vapour pressure:	No data available
Vapour pressure:	No data available
Density:	0,8239 g/cm³
Bulk density:	not determined
Relative vapour density:	No data available

9.2. Other information**Information with regard to physical hazard classes****Explosive properties**

Vapours can form explosive mixtures with air.

Sustained combustibility:

Sustained combustibility

Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

Oxidizing properties

not determined

Other safety characteristics**Evaporation rate:**

No data available

Solvent separation test:

No data available

Solvent content:

No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Methanolysis Mixture E

Revision: 10.10.2025

Product code: AC15.02377

Page 9 of 15

Solid content:	No data available
Sublimation point:	No data available
Softening point:	No data available
Pour point:	No data available
No data available:	
Viscosity / dynamic: (at 20 °C)	No data available
Flow time:	No data available

Further Information

No data available

SECTION 10: Stability and reactivity**10.1. Reactivity**

Highly flammable.
Vapours can form explosive mixtures with air.
Corrosive to metals.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent, Nitrogen oxides (NO_x), Potassium chlorate, peroxides, for example hydrogen peroxide, Nitric acid, sulphuric acid, sodium hypochlorite, Acid halogen, Acetic anhydride, Maleic anhydride, Reducing agent, Acid, Bromine, Chlorine, Chloroform, Fluorine, Alkali metals, Alkaline earth metal;
Risk of explosion with: Oxidizing agents, perchloric acid, perchlorates, salts of oxyhalogenic acids, chromium(VI) oxide, halogen oxides, nitrogen oxides, nonmetallic oxides, chromosulfuric acid, chlorates, hydrides, zinc diethyl, halogens, powdered magnesium, hydrogen peroxide, Nitric acid, sulphuric acid, permanganic acid, sodium hypochlorite Exothermic reaction with: acid halides, Acid anhydrides, Reducing agents, acids, Bromine, Chlorine, Chloroform, magnesium, tetrachloromethane, CYANURIC CHLORIDE Risk of ignition or formation of inflammable gases or vapours with: Fluorine, Oxides of phosphorus, Raney-nickel Generates dangerous gases or fumes in contact with: Alkaline earth metals, Alkali metals

10.4. Conditions to avoid

Vapours can form explosive mixtures with air.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Metal
Plastic articles
Zinc

10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Toxicokinetics, metabolism and distribution**

Avoid exposure - obtain special instructions before use.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Methanolysis Mixture E

Revision: 10.10.2025

Product code: AC15.02377

Page 10 of 15

Acute toxicity

Toxic if inhaled.
Toxic in contact with skin.
Toxic if swallowed.
Irritation to respiratory tract

ATEmix calculated

ATE (oral) 102,5 mg/kg; ATE (dermal) 310,6 mg/kg; ATE (inhalation vapour) 3,110 mg/l; ATE (inhalation dust/mist) 0,5180 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
67-56-1	methanol				
	oral	LD50 6000 mg/kg	Monkey	Amer J Ophthalmol 40: 76-83 (cited in DG	Determination of the acute toxicity of t
	dermal	ATE 300 mg/kg			
	inhalation (4 h) vapour	LC50 128,2 mg/l	Rat	Study report (1980)	Study performed according to internal co
	inhalation dust/mist	ATE 0,5 mg/l			
1310-58-3	potassium hydroxide				
	oral	LD50 333 mg/kg	Rat	Fund. Appl. Toxicol., 8, 97-100 (1987)	OECD Guideline 425

Irritation and corrosivity

Skin corrosion/irritation: Causes severe skin burns and eye damage.
Serious eye damage/eye irritation: Causes serious eye damage.
Has degreasing effect on the skin.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.
Carcinogenicity: Based on available data, the classification criteria are not met.
Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Causes damage to organs. (methanol)
(eyes)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.

11.2. Information on other hazards

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Methanolysis Mixture E

Revision: 10.10.2025

Product code: AC15.02377

Page 11 of 15

Other information

Irritation to respiratory tract
 Repeated exposure may cause skin dryness or cracking.
 Causes damage to organs.
 Organs affected:
 Liver and kidney damage
 eyes
 heart
 Irreversible damage to the optic nerve.

Further information

Irritant, Dizziness, Dizziness, Anaesthetic state, Agitation, Spasms, Inebriation, Vomiting, Headache,
 Impairment of vision
 Repeated exposure may cause skin dryness or cracking.
 The substance has delayed effects.
 Other dangerous properties cannot be excluded.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
67-56-1	methanol					
	Acute fish toxicity	LC50 15400 mg/l	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-009, 1975
	Acute algae toxicity	ErC50 ca. 22000 mg/l	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 10000 mg/l	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11
	Fish toxicity	NOEC 446,7 mg/l	28 d	Pimephales promelas	SAR and QSAR in Environmental Research,	Calculation performed with ECOSAR
	Crustacea toxicity	NOEC 208 mg/l	21 d	Daphnia magna	OECD QSAR Toolbox Report (2013)	Toxicity of the target chemical is predi

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-56-1	methanol	-0,77

BCF

CAS No	Chemical name	BCF	Species	Source
67-56-1	methanol	1	Cyprinus carpio	Comparative Biochemi

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Methanolysis Mixture E

Revision: 10.10.2025

Product code: AC15.02377

Page 12 of 15

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Discharge into the environment must be avoided.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not allow to enter into surface water or drains.

Contaminated packaging

This material and its container must be disposed of as hazardous waste.

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information**Land transport (ADR/RID)**

<u>14.1. UN number or ID number:</u>	UN 3286
<u>14.2. UN proper shipping name:</u>	FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (methanol, potassium hydroxide)
<u>14.3. Transport hazard class(es):</u>	3
<u>14.4. Packing group:</u>	II
Hazard label:	3+6.1+8
Classification code:	FTC
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	368
Tunnel restriction code:	D/E

Inland waterways transport (ADN)

<u>14.1. UN number or ID number:</u>	UN 3286
<u>14.2. UN proper shipping name:</u>	FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (methanol, potassium hydroxide)
<u>14.3. Transport hazard class(es):</u>	3
<u>14.4. Packing group:</u>	II
Hazard label:	3+6.1+8
Classification code:	FTC
Special Provisions:	274 802
Limited quantity:	1 L

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Methanolysis Mixture E

Revision: 10.10.2025

Product code: AC15.02377

Page 13 of 15

Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 3286
14.2. UN proper shipping name: FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (methanol, potassium hydroxide)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3+6.1/8
 Special Provisions: 274
 Limited quantity: 1 L
 Excepted quantity: E2
 EmS: F-E, S-C

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 3286
14.2. UN proper shipping name: FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (methanol, potassium hydroxide)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3+6.1 8
 Limited quantity Passenger: 0.5 L
 Passenger LQ: Y340
 Excepted quantity: E2
 IATA-packing instructions - Passenger: 352
 IATA-max. quantity - Passenger: 1 L
 IATA-packing instructions - Cargo: 363
 IATA-max. quantity - Cargo: 5 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Combustible liquid. Toxic.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 69, Entry 75

Information according to Directive H2 ACUTE TOXIC

2012/18/EU (SEVESO III):

Additional information: P5c

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

Skin resorption/Sensitization: Permeates easily through outer skin and causes poisoning.

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Methanolysis Mixture E

Revision: 10.10.2025

Product code: AC15.02377

Page 14 of 15

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,3,9,12.

Abbreviations and acronyms

Met. Corr. 1: Corrosive to metals, hazard category 1

Flam. Liq. 2: Flammable liquids, hazard category 2

Acute Tox. 3: Acute toxicity, hazard category 3

Skin Corr. 1A: Skin corrosion, sub-category 1A

Eye Dam. 1: Serious eye damage, hazard category 1

STOT SE 1: Specific target organ toxicity - single exposure, hazard category 1

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Met. Corr. 1; H290	On basis of test data
Acute Tox. 3; H331	Calculation method
Acute Tox. 3; H311	Calculation method
Acute Tox. 3; H301	Calculation method
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method
STOT SE 1; H370	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H290	May be corrosive to metals.
H301	Toxic if swallowed.
H301+H311+H331	Toxic if swallowed, in contact with skin or if inhaled.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H370	Causes damage to organs (eyes, central nervous system).
H370	Causes damage to organs.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Methanolysis Mixture E

Revision: 10.10.2025

Product code: AC15.02377

Page 15 of 15

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

Provide appropriate information, instructions and training to users

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)