

**Phenolphthalein 50 mg/l in ethanol-diethy**

Revision: 12.06.2025

Product code: AC16.00769

Page 1 of 14

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Phenolphthalein 50 mg/l in ethanol-diethy

UFI: FEMJ-W2X9-WWCR-K2SR

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Reagents and laboratory chemicals

Only for laboratory and analysis purposes.

**Uses advised against**

Do not use for private purposes (household).

**1.3. Details of the supplier of the safety data sheet****Details of the supplier of the safety data sheet**

Company name: AnalytiChem Services, Unipessoal, Lda  
Street: Rua de Júlio Dinis 676 7º  
Place: N-4050-320 Porto  
Telephone: +351 226002917  
E-mail: info@analytichem.com  
Contact person: SDS service department  
E-mail: SDS@analytichem.com  
Internet: www.analytichem.com  
Responsible Department: SDS service department

**Supplier or manufacturer details**

Company name: AnalytiChem Belgium NV  
Street: Industriezone "De Arend" 2  
Place: B-8210 Zedelgem  
Telephone: +32 50 28 83 20  
E-mail: info.be@analytichem.com  
Contact person: SDS service department  
E-mail: SDS@analytichem.com  
Responsible Department: AnalytiChem:  
EU-Belgium: AnalytiChem Belgium, Industriezone "De Arend" 2, 8210 Zedelgem, Belgium, +32 50 28 83 20  
EU-Germany: AnalytiChem Germany, Stempelstrasse 6, 47167 Duisburg, Germany, +49 203 51 94 – 200  
EU-Netherlands: AnalytiChem Netherlands, Communicatieweg 7, 3641 SG Mijdrecht, The Netherlands, +31 297 286848  
UK: AnalytiChem UK, Unit 7 Launton Business Center, Murdock Road, Bicester, OX26 4XB, England, +44 1869 355 500  
USA: AnalytiChem USA, 227 China Road, Winslow, Maine, 04901, United States, +1 800-244-8378  
Canada: AnalytiChem Canada, 21800 Clark Graham Avenue, Baie d'Urfe, H9X 4B6, Canada, +1 514-457-0701  
Australia: ORE Research & Exploration Pty Ltd, 37A Hosie Street, Bayswater North, 3153, Australia, +61 3 9729 0333  
+44 20 3807 3798 (CHEMTREC)

**1.4. Emergency telephone number:****Further Information**

inapplicable, this product is a mixture REACH registration number see section 3

**Phenolphthalein 50 mg/l in ethanol-diethy**

Revision: 12.06.2025

Product code: AC16.00769

Page 2 of 14

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Flam. Liq. 1; H224

STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

**2.2. Label elements****Regulation (EC) No 1272/2008****Hazard components for labelling**

diethyl ether

**Signal word:**

Danger

**Pictograms:****Hazard statements**

H224

Extremely flammable liquid and vapour.

H336

May cause drowsiness or dizziness.

EUH019

May form explosive peroxides.

EUH066

Repeated exposure may cause skin dryness or cracking.

**Precautionary statements**

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233

Keep container tightly closed.

P261

Avoid breathing dust/fume/gas/mist/vapours/spray.

P280

Wear protective gloves/protective clothing and eye protection/face protection.

P312

Call a POISON CENTER/doctor if you feel unwell.

P403+P235

Store in a well-ventilated place. Keep cool.

P501

Dispose of contents/container to an appropriate recycling or disposal facility.

**2.3. Other hazards**

No data available

**SECTION 3: Composition/information on ingredients****3.2. Mixtures**

**Phenolphthalein 50 mg/l in ethanol-diethy**

Revision: 12.06.2025

Product code: AC16.00769

Page 3 of 14

**Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
60-29-7	diethyl ether			55 - < 60 %
	200-467-2	603-022-00-4	01-2119535785-29	
	Flam. Liq. 1, Acute Tox. 4, STOT SE 3; H224 H302 H336 EUH019 EUH066			
64-17-5	ethanol			35 - < 40 %
	200-578-6	603-002-00-5	01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225 H319			

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
60-29-7	200-467-2	diethyl ether	55 - < 60 %
	inhalation: LC50 = 32000 mg/l (vapours); dermal: LD50 = > 20000 mg/kg; oral: LD50 = 1600 mg/kg		
64-17-5	200-578-6	ethanol	35 - < 40 %
	inhalation: LC50 = 124,7 mg/l (vapours); oral: LD50 = 10470 mg/kg Eye Irrit. 2; H319: >= 50 - 100		

**Further Information**

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

First aider: Pay attention to self-protection!

**After inhalation**

Provide fresh air.

Call a physician immediately.

**After contact with skin**

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

**After contact with eyes**

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Remove contact lenses, if present and easy to do. Continue rinsing.

Protect uninjured eye.

**After ingestion**

Rinse mouth.

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

**4.2. Most important symptoms and effects, both acute and delayed**

Irritant

Respiratory complaints

**Phenolphthalein 50 mg/l in ethanol-diethy**

Revision: 12.06.2025

Product code: AC16.00769

Page 4 of 14

Headache  
Dizziness  
Dizziness  
Inebriation  
Anaesthetic state  
Unconsciousness  
Repeated exposure may cause skin dryness or cracking.

**4.3. Indication of any immediate medical attention and special treatment needed**

No data available

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Co-ordinate fire-fighting measures to the fire surroundings.

**Unsuitable extinguishing media**

Full water jet

**5.2. Special hazards arising from the substance or mixture**

Combustible liquids

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO<sub>2</sub>) Carbon monoxide

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Heating causes rise in pressure with risk of bursting.

Beware of reignition.

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

**Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

**For non-emergency personnel**

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

**For emergency responders**

Precautionary statements For emergency responders : Personal protection equipment: see section 8

**Phenolphthalein 50 mg/l in ethanol-diethy**

Revision: 12.06.2025

Product code: AC16.00769

Page 5 of 14

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

**6.3. Methods and material for containment and cleaning up****For containment**

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

**For cleaning up**

Clean contaminated articles and floor according to the environmental legislation.

**Other information**

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

**6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe vapour/aerosol. Provide adequate ventilation.

**Advice on protection against fire and explosion**

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

**Advice on general occupational hygiene**

Keep away from food, drink and animal feedingstuffs.

Wash hands and face before breaks and after work and take a shower if necessary.

When using do not eat or drink.

Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

**Further information on handling**

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place.

Store in a cool dry place.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

## Phenolphthalein 50 mg/l in ethanol-diethy

Revision: 12.06.2025

Product code: AC16.00769

Page 6 of 14

**Hints on joint storage**

National regulatory information

**Further information on storage conditions**

Protect from sunlight.

**7.3. Specific end use(s)**

Laboratory chemicals

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
60-29-7	Diethyl ether	100	310		TWA (8 h)	WEL
		200	620		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
60-29-7	diethyl ether			
Worker DNEL, long-term		inhalation	systemic	308 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	systemic	616 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	44 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	54,5 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	15,6 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	15,6 mg/kg bw/day
64-17-5	ethanol			
Worker DNEL, long-term		inhalation	systemic	950 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	343 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	114 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	206 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	87 mg/kg bw/day

**Phenolphthalein 50 mg/l in ethanol-diethy**

Revision: 12.06.2025

Product code: AC16.00769

Page 7 of 14

**PNEC values**

CAS No	Substance	
Environmental compartment		Value
60-29-7	diethyl ether	
Freshwater		2 mg/l
Freshwater (intermittent releases)		1,65 mg/l
Marine water		0,2 mg/l
Freshwater sediment		9,14 mg/kg
Marine sediment		0,914 mg/kg
Micro-organisms in sewage treatment plants (STP)		4,2 mg/l
Soil		0,66 mg/kg
64-17-5	ethanol	
Freshwater		0,96 mg/l
Freshwater (intermittent releases)		2,75 mg/l
Marine water		0,79 mg/l
Freshwater sediment		3,6 mg/kg
Marine sediment		2,9 mg/kg
Secondary poisoning		380 mg/kg
Micro-organisms in sewage treatment plants (STP)		580 mg/l
Soil		0,63 mg/kg

**Additional advice on limit values**

Observe in addition any national regulations!

**8.2. Exposure controls****Appropriate engineering controls**

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

goggles

Face protection umbrella

**Hand protection**

Tested protective gloves must be worn. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

**Skin protection**

Wear fire resistant or flame retardant clothing.

Take off immediately all contaminated clothing and wash it before reuse.

Wear suitable protective clothing. Take off immediately all contaminated clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

**Respiratory protection**

Respiratory protection necessary at: aerosol or mist formation

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are

**Phenolphthalein 50 mg/l in ethanol-diethy**

Revision: 12.06.2025

Product code: AC16.00769

Page 8 of 14

carried out according to the instructions of the producer. These measures have to be properly documented.

**Thermal hazards**

No data available

**Environmental exposure controls**

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Danger of explosion

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	Liquid	
Colour:	colourless	
Odour:	characteristic	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		No data available
Flammability:		No data available
Lower explosion limits:		No data available
Upper explosion limits:		No data available
Flash point:		<21 °C
Auto-ignition temperature:		No data available
Decomposition temperature:		No data available
pH-Value:		7
Viscosity / kinematic:		No data available
Water solubility:		No data available
Solubility in other solvents		
No data available		
Dissolution rate:		No data available
Partition coefficient n-octanol/water:		No data available
Dispersion stability:		No data available
Vapour pressure:		No data available
Vapour pressure:		No data available
Density (at 20 °C):		0,746 g/cm <sup>3</sup>
Relative density:		No data available
Bulk density:		No data available
Relative vapour density:		No data available
Particle characteristics:		No data available

**9.2. Other information****Information with regard to physical hazard classes****Explosive properties**

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

**Sustained combustibility:**

Sustained combustibility

**Self-ignition temperature**

Solid:

No data available

Gas:

No data available

**Oxidizing properties**

No data available

**Other safety characteristics****Evaporation rate:**

No data available

**Phenolphthalein 50 mg/l in ethanol-diethy**

Revision: 12.06.2025

Product code: AC16.00769

Page 9 of 14

Solvent separation test:	No data available
Solvent content:	No data available
Solid content:	No data available
Sublimation point:	No data available
Softening point:	No data available
Pour point:	No data available
Flow time:	No data available

**Further Information**

No data available

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

Vapours may form explosive mixtures with air.

**10.2. Chemical stability**

Protect against: Radiant heat.

**10.3. Possibility of hazardous reactions**

Oxidising agent

**10.4. Conditions to avoid**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**10.5. Incompatible materials**

Plastic articles

Rubber articles

**10.6. Hazardous decomposition products**

In case of fire may be liberated:

SECTION 5: Firefighting measures

**Further information**

No data available

**SECTION 11: Toxicological information**

**11.1. Information on hazard classes**

**Toxicokinetics, metabolism and distribution**

No data available

**Acute toxicity**

Based on available data, the classification criteria are not met.

**ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

## Phenolphthalein 50 mg/l in ethanol-diethy

Revision: 12.06.2025

Product code: AC16.00769

Page 10 of 14

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
60-29-7	diethyl ether				
	oral	LD50 1600 mg/kg	Rat	Toxicology and applied pharmacology, 197	OECD Guideline 401
	dermal	LD50 > 20000 mg/kg	Rabbit	Am. Ind. Hyg. Assoc. J., 1962, 23, 95-10	OECD Guideline 402
	inhalation (4 h) vapour	LC50 32000 mg/l	Rat	Am. Ind. Hyg. Assoc. J., 1962, 23, 95-10	Test animals are exposed to metered vapo
64-17-5	ethanol				
	oral	LD50 10470 mg/kg	Rat	Study report (1976)	OECD Guideline 401
	inhalation (4 h) vapour	LC50 124,7 mg/l	Rat	Study report (1980)	OECD Guideline 403

**Irritation and corrosivity**

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause drowsiness or dizziness. (diethyl ether)

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Information on likely routes of exposure**

No data available

**Specific effects in experiment on an animal**

No data available

**Additional information on tests**

No data available

**Practical experience**

No data available

**11.2. Information on other hazards****Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**Other information**

Observe risk of aspiration if vomiting occurs. Pulmonary oedema Pneumonia

Repeated exposure may cause skin dryness or cracking.

## Phenolphthalein 50 mg/l in ethanol-diethy

Revision: 12.06.2025

Product code: AC16.00769

Page 11 of 14

## Further information

No data available

## SECTION 12: Ecological information

## 12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
60-29-7	diethyl ether					
	Acute fish toxicity	LC50 2560 mg/l	96 h	Pimephales promelas	Acute toxicities of organic chemicals to	other: American Society for Testing and
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Desmodesmus subspicatus	Study report (2010)	OECD Guideline 201
	Crustacea toxicity	NOEC 100 mg/l	21 d	Daphnia magna	Study report (2010)	OECD Guideline 211
	Acute bacteria toxicity	EC50 26000 mg/l ( )	3 h	activated sludge of a predominantly domestic sewage	Study report (2010)	OECD Guideline 209
64-17-5	ethanol					
	Acute fish toxicity	LC50 15400 mg/l	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-009, 1975
	Acute algae toxicity	ErC50 ca. 22000 mg/l	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 10000 mg/l	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11
	Algae toxicity	NOEC 5400 mg/l	5 d	Skeletonema costatum	Environ Toxicol Chem 8(5):451-455. (1989)	Study to determine the sensitivity of a
	Crustacea toxicity	NOEC 2 mg/l	10 d	Ceriodaphnia dubia	Arch Environ Contam Toxicol 20(2):211-21	Follows the basic methodology for the th

## 12.2. Persistence and degradability

There are no data available on the mixture itself.

## 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

## Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
60-29-7	diethyl ether	1,05
64-17-5	ethanol	-0,77

## BCF

CAS No	Chemical name	BCF	Species	Source
60-29-7	diethyl ether	2	not applicable	Other company data (
64-17-5	ethanol	1	Cyprinus carpio	Comparative Biochemi

**Phenolphthalein 50 mg/l in ethanol-diethy**

Revision: 12.06.2025

Product code: AC16.00769

Page 12 of 14

**12.4. Mobility in soil**

There are no data available on the mixture itself.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

Avoid release to the environment.

**Further information**

Do not allow to enter into surface water or drains.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

**Contaminated packaging**

Handle contaminated packages in the same way as the substance itself.

**SECTION 14: Transport information****Land transport (ADR/RID)**

<b><u>14.1. UN number or ID number:</u></b>	UN 1993
<b><u>14.2. UN proper shipping name:</u></b>	FLAMMABLE LIQUID, N.O.S. (diethyl ether, ethanol)
<b><u>14.3. Transport hazard class(es):</u></b>	3
<b><u>14.4. Packing group:</u></b>	I
Hazard label:	3
Classification code:	F1
Special Provisions:	274
Limited quantity:	0
Excepted quantity:	E3
Transport category:	1
Hazard No:	33
Tunnel restriction code:	D/E

**Inland waterways transport (ADN)**

<b><u>14.1. UN number or ID number:</u></b>	UN 1993
<b><u>14.2. UN proper shipping name:</u></b>	FLAMMABLE LIQUID, N.O.S. (diethyl ether, ethanol)
<b><u>14.3. Transport hazard class(es):</u></b>	3
<b><u>14.4. Packing group:</u></b>	I
Hazard label:	3
Classification code:	F1
Special Provisions:	274
Limited quantity:	0
Excepted quantity:	E3

**Marine transport (IMDG)**

<b><u>14.1. UN number or ID number:</u></b>	UN 1993
<b><u>14.2. UN proper shipping name:</u></b>	FLAMMABLE LIQUID, N.O.S. (diethyl ether, ethanol)
<b><u>14.3. Transport hazard class(es):</u></b>	3

## Phenolphthalein 50 mg/l in ethanol-diethy

Revision: 12.06.2025

Product code: AC16.00769

Page 13 of 14

**14.4. Packing group:** I  
Hazard label: 3  
Special Provisions: 274  
Limited quantity: 0  
Excepted quantity: E3  
EmS: F-E, S-E

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number or ID number:** UN 1993  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, N.O.S. (diethyl ether, ethanol)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** I  
Hazard label: 3  
Special Provisions: A3  
Limited quantity Passenger: Forbidden  
Passenger LQ: Forbidden  
Excepted quantity: E3  
IATA-packing instructions - Passenger: 351  
IATA-max. quantity - Passenger: 1 L  
IATA-packing instructions - Cargo: 361  
IATA-max. quantity - Cargo: 30 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Information according to Directive 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

**Additional information**

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

**National regulatory information****SECTION 16: Other information****Abbreviations and acronyms**

Flam. Liq. 1: Flammable liquids, hazard category 1

Flam. Liq. 2: Flammable liquids, hazard category 2

Acute Tox. 4: Acute toxicity, hazard category 4

Eye Irrit. 2: Eye irritation, hazard category 2

STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3

**Classification for mixtures and used evaluation method**

Classification	Classification procedure
Flam. Liq. 1; H224	On basis of test data
STOT SE 3; H336	Calculation method

**Relevant H and EUH statements (number and full text)**

**Phenolphthalein 50 mg/l in ethanol-diethy**

Revision: 12.06.2025

Product code: AC16.00769

Page 14 of 14

H224	Extremely flammable liquid and vapour.
H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH019	May form explosive peroxides.
EUH066	Repeated exposure may cause skin dryness or cracking.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. Provide appropriate information, instructions and training to users

---

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*