

CONOSTAN® Custom Blend Standard

Revision date: 09/12/2024

Product code: AC18.03246

Page 2 of 14

2. Hazard(s) identification

Classification of the chemical

Regulation (EC) No 1272/2008

- Flam. Liq. 2; H225
- Repr. 2; H361d
- Skin Irrit. 2; H315
- STOT SE 3; H336
- STOT RE 2; H373
- Asp. Tox. 1; H304
- Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

toluene

Signal word: Danger

Pictograms:



Hazard statements

- H225 Highly flammable liquid and vapor
- H304 May be fatal if swallowed and enters airways
- H315 Causes skin irritation
- H336 May cause drowsiness or dizziness
- H361d Suspected of damaging the unborn child
- H373 May cause damage to organs (central nervous system) through prolonged or repeated exposure if inhaled
- H412 Harmful to aquatic life with long lasting effects

Precautionary statements

- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P260 Do not breathe mist/vapors/spray.
- P280 Wear protective gloves/protective clothing and eye protection/face protection.
- P301+P310 If swallowed: Immediately call a poison center/doctor.
- P331 Do NOT induce vomiting.
- P403+P235 Store in a well-ventilated place. Keep cool.

Hazards not otherwise classified

No data available

3. Composition/information on ingredients

Mixtures

Chemical characterization

Hydrocarbons, aromatic

CONOSTAN® Custom Blend Standard

Revision date: 09/12/2024

Product code: AC18.03246

Page 3 of 14

Relevant ingredients

CAS No	Components			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
108-88-3	toluene			95 - < 100 %
	203-625-9	601-021-00-3	01-2119471310-51	
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H225 H361d H315 H336 H373 H304 H412			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Components	Quantity
	Specific Conc. Limits, M-factors and ATE		
108-88-3	203-625-9	toluene	95 - < 100 %
	inhalation: LC50 = 28,1 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = 5580 mg/kg		

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

4. First-aid measures
Description of first aid measures
General information

No data available

After inhalation

Provide fresh air.

If breathing is irregular or stopped, administer artificial respiration.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

Most important symptoms and effects, both acute and delayed

Irritant, Headache

Dizziness, Dizziness

Vomiting, Inebriation

Spasms, Circulatory collapse

Respiratory complaints, Dyspnoea

Unconsciousness

Indication of any immediate medical attention and special treatment needed

No data available

CONOSTAN® Custom Blend Standard

Revision date: 09/12/2024

Product code: AC18.03246

Page 4 of 14

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

- Foam.
- Extinguishing powder
- Carbon dioxide (CO₂)

Unsuitable extinguishing media

no restriction

Specific hazards arising from the chemical

- Combustible liquids
- Beware of reignition.
- Hazardous combustion products
- In case of fire may be liberated:
- Carbon dioxide (CO₂), Carbon monoxide
- Vapors are heavier than air, spread along floors and form explosive mixtures with air.
- Heating causes rise in pressure with risk of bursting.

Special protective equipment and precautions for fire-fighters

- In case of fire: Wear self-contained breathing apparatus.
- In case of fire and/or explosion do not breathe fumes.
- Avoid contact with skin, eyes and clothes.

Additional information

- Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.
- Move undamaged containers from immediate hazard area if it can be done safely.
- Use water spray jet to protect personnel and to cool endangered containers.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

General advice

- Keep away from sources of ignition - No smoking.
- This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).
- Take precautionary measures against static discharge.

For non-emergency personnel

- Provide adequate ventilation.
- Use personal protection equipment.
- Avoid contact with skin, eyes and clothes.
- Remove persons to safety.
- Emergency procedures
- Consult an expert
- Do not breathe dust/fume/gas/mist/vapors/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment (PPE): see section 8

Environmental precautions

- Do not allow to enter into surface water or drains.
- The vapors are heavier than air and can accumulate in high concentrations on the ground, in cavities, channels and cellars.
- Danger of explosion

CONOSTAN® Custom Blend Standard

Revision date: 09/12/2024

Product code: AC18.03246

Page 5 of 14

Methods and material for containment and cleaning up
For containment

- Cover drains.
- Prevent spread over a wide area (e.g. by containment or oil barriers).
- Collect in closed and suitable containers for disposal.
- Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

- Clean contaminated articles and floor according to the environmental legislation.

Other information

- Provide adequate ventilation.
- Do not breathe dust/fume/gas/mist/vapors/spray.
- Wear breathing apparatus if exposed to vapors/dusts/aerosols.

Reference to other sections

- Safe handling: see section 7
- Personal protection equipment (PPE): see section 8
- Disposal: see section 13

7. Handling and storage
Precautions for safe handling
Advice on safe handling

- Avoid exposure - obtain special instructions before use.
- Read label before use. Handle and open container with care.
- When using do not eat, drink, smoke, sniff. Keep container tightly closed.
- Use personal protection equipment. Use extractor hood (laboratory).
- Do not breathe gas/fume/vapor/spray. Provide adequate ventilation.

Advice on protection against fire and explosion

- Take precautionary measures against static discharge. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on general occupational hygiene

- Keep away from food, drink and animal feedingstuffs.
- Draw up and observe skin protection programme.
- The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of the protective agents should be clarified with their suppliers.

Further information on handling

- Take off immediately all contaminated clothing and wash it before reuse.
- Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.
- Store in a place accessible by authorized persons only.

Conditions for safe storage, including any incompatibilities
Requirements for storage rooms and vessels

- Keep in a cool, well-ventilated place.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Keep container tightly closed.

Hints on joint storage

- Take national regulations into account.

Further information on storage conditions

- Keep cool. Protect from sunlight.

Specific end use(s)

CONOSTAN® Custom Blend Standard

Revision date: 09/12/2024

Product code: AC18.03246

Page 6 of 14

Laboratory chemicals
Only for laboratory and analysis purposes.

8. Exposure controls/personal protection
Control parameters
Exposure limits

CAS No	Substance	ppm	mg/m ³	Category	Origin
108-88-3	Toluene	200	-	TWA (8 h)	PEL
		C 300	-	Ceiling	PEL
		500	-	Peak (10 min)	PEL
108-88-3	Toluene	100	375	TWA (8 h)	REL
		150	560	STEL (15 min)	REL
108-88-3	Toluene	20	-	TWA (8 h)	ACGIH-2025

Biological Exposure Indices (BEI-ACGIH)

CAS No	Substance	Determinant	Value	Test material	Sampling time
108-88-3	TOLUENE	Toluene	0.02 mg/L	blood	Prior to last shift of workweek

DNEL/DMEL values

CAS No	Substance	DNEL type	Exposure route	Effect	Value
108-88-3	toluene	Worker DNEL, long-term	inhalation	systemic	192 mg/m ³
		Worker DNEL, acute	inhalation	systemic	384 mg/m ³
		Worker DNEL, long-term	inhalation	local	192 mg/m ³
		Worker DNEL, acute	inhalation	local	384 mg/m ³
		Worker DNEL, long-term	dermal	systemic	384 mg/kg bw/day
		Consumer DNEL, long-term	inhalation	systemic	56,5 mg/m ³
		Consumer DNEL, acute	inhalation	systemic	226 mg/m ³
		Consumer DNEL, long-term	inhalation	local	56,5 mg/m ³
		Consumer DNEL, acute	inhalation	local	226 mg/m ³
		Consumer DNEL, long-term	dermal	systemic	226 mg/kg bw/day
		Consumer DNEL, long-term	oral	systemic	8,13 mg/kg bw/day

CONOSTAN® Custom Blend Standard

Revision date: 09/12/2024

Product code: AC18.03246

Page 7 of 14

PNEC values

CAS No	Substance	
Environmental compartment		Value
108-88-3	toluene	
Freshwater		0,68 mg/l
Freshwater (intermittent releases)		0,68 mg/l
Marine water		0,68 mg/l
Freshwater sediment		16,39 mg/kg
Marine sediment		16,39 mg/kg
Microorganisms in sewage treatment plants (STP)		13,61 mg/l
Soil		2,89 mg/kg

Exposure controls
Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment
Eye/face protection

goggles

Face protection umbrella

Hand protection

Tested protective gloves must be worn. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Take off immediately all contaminated clothing and wash it before reuse.

Wear fire resistant or flame retardant clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented. A respiratory protection program that meets OSHA's 29 CFR 1910.134 requirements must be followed whenever workplace conditions warrant a respirator's use.

Thermal hazards

No data available

Environmental exposure controls

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapors into cellars, flues and ditches.

Danger of explosion

9. Physical and chemical properties
Information on basic physical and chemical properties

Physical state:	Liquid
Color:	clear
Odor:	like: Hydrocarbons, aromatic

CONOSTAN® Custom Blend Standard

Revision date: 09/12/2024

Product code: AC18.03246

Page 8 of 14

Odour threshold:	No data available
Melting point/freezing point:	-95 °C
Boiling point or initial boiling point and boiling range:	110,6 °C
Flammability:	No data available
Lower explosion limits:	1,1 vol. %
Upper explosion limits:	7,1 vol. %
Flash point:	4,4 °C
Auto-ignition temperature:	480 °C
Decomposition temperature:	No data available
pH-Value:	No data available
Viscosity / kinematic: (at 20 °C)	0,7 mm ² /s
Water solubility: (at 20 °C)	0,52 g/l
Solubility in other solvents No data available	
Dissolution rate:	No data available
Partition coefficient n-octanol/water:	log Pow: 2,65
Dispersion stability:	No data available
Vapor pressure: (at 20 °C)	29,3 hPa
Vapor pressure: (at 50 °C)	123 hPa
Density:	0,87 g/cm ³
Relative density:	No data available
Bulk density:	No data available
Relative vapour density:	No data available
Particle characteristics:	No data available

Other information
Information with regard to physical hazard classes
Explosive properties

Vapors are heavier than air, spread along floors and form explosive mixtures with air.

Sustained combustibility: Sustained combustibility

Self-ignition temperature

Solid: No data available

Gas: No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate: No data available

Solvent separation test: No data available

Solvent content: 100,00 %

Solid content: 0

Sublimation point: No data available

Softening point: No data available

Pour point: No data available

No data available

Viscosity / dynamic: 0,6 mPa·s

(at 20 °C)

Flow time: No data available

CONOSTAN® Custom Blend Standard

Revision date: 09/12/2024

Product code: AC18.03246

Page 9 of 14

Further Information

No data available

10. Stability and reactivity

Reactivity

Vapours may form explosive mixtures with air.

Chemical stability

The product is stable under storage at normal ambient temperatures.

Possibility of hazardous reactions

- Oxidising agent
- Nitric acid
- Acetic acid
- Strong acid
- silver

Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Incompatible materials

- Plastic articles
- Rubber articles

Hazardous decomposition products

in case of fire, see:
SECTION 5: Fire fighting measures

Further information

No data available

11. Toxicological information

Information on toxicological effects

Toxicokinetics, metabolism and distribution

Avoid exposure - obtain special instructions before use.

Acute toxicity

Based on available data, the classification criteria are not met.

- Irritation to respiratory tract
- Resorption (by inhalation)
- Resorption (dermal)

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Components					
	Exposure route	Dose	Species	Source	Method	
108-88-3	toluene					
	oral	LD50 mg/kg	5580	Rat	Toxicology 4, 5-15 (1975)	EU Method B.1
	dermal	LD50 mg/kg	> 5000	Rabbit	American Industrial Hygiene Association	Study investigated mortality in groups o
	inhalation (4 h) vapour	LC50	28,1 mg/l	Rat	Study report (1980)	OECD Guideline 403

CONOSTAN® Custom Blend Standard

Revision date: 09/12/2024

Product code: AC18.03246

Page 10 of 14

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation
 Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.
 Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

Sensitizing effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of damaging the unborn child (toluene)
 Germ cell mutagenicity: Based on available data, the classification criteria are not met.
 Carcinogenicity: Based on available data, the classification criteria are not met.

Specific target organ toxicity (STOT) - single exposure

May cause drowsiness or dizziness (toluene)

Specific target organ toxicity (STOT) - repeated exposure

May cause damage to organs through prolonged or repeated exposure (toluene)

Aspiration hazard

May be fatal if swallowed and enters airways

Route(s) of Entry

No data available

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

No data available

Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Other information

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

Further information

Irritant, Headache
 Dizziness, Dizziness
 Vomiting, Inebriation
 Spasms, Circulatory collapse
 Respiratory complaints, Dyspnoea
 Unconsciousness

12. Ecological information

Ecotoxicity

Harmful to aquatic life with long lasting effects

CONOSTAN® Custom Blend Standard

Revision date: 09/12/2024

Product code: AC18.03246

Page 11 of 14

CAS No	Components					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
108-88-3	toluene					
	Acute fish toxicity	LC50 5,5 mg/l	96 h	Oncorhynchus kisutch	Transactions A. Fish. Soc. 110, 430-436.	Fry were exposed to toluene in a flow th
	Acute algae toxicity	ErC50 > 433 mg/l	96 h	Pseudokirchneriella subcapitata	REACH Registration Dossier	Method: other
	Acute crustacea toxicity	EC50 11,5 mg/l	48 h	Daphnia magna	REACH Registration Dossier	Method: other
	Fish toxicity	NOEC 1,39 mg/l	40 d	Oncorhynchus kisutch	Transactions A. Fish. Soc. 110, 430-436.	Fry were exposed to toluene in a flow th
	Algae toxicity	NOEC > 400 mg/l	7 d	Scenedesmus quadricauda	REACH Registration Dossier	Method: other
	Crustacea toxicity	NOEC 0,74 mg/l	7 d	Ceriodaphnia dubia	Ecotoxicol. Environ. Saf. 39, 136-146. (other: US EPA 600/4-91-003

Persistence and degradability

There are no data available on the mixture itself.

Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Components	Log Pow
108-88-3	toluene	2,73

BCF

CAS No	Components	BCF	Species	Source
108-88-3	toluene	90	Leuciscus idus melanotus	Chemosphere 14 (10).

Mobility in soil

There are no data available on the mixture itself.

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Other adverse effects

Do not allow to enter into surface water or drains.

Further information

Avoid release to the environment.

13. Disposal considerations
Waste treatment methods
Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

CONOSTAN® Custom Blend Standard

Revision date: 09/12/2024

Product code: AC18.03246

Page 12 of 14

Send to a physico-chemical treatment facility under observation of official regulations .

Do not mix with other wastes.

Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

Waste codes/waste designations according to EWC/AVV

14. Transport information

Land transport (ADR/RID)

<u>UN number or ID number:</u>	UN 1294
<u>UN proper shipping name:</u>	TOLUENE
<u>Transport hazard class(es):</u>	3
<u>Packing group:</u>	II
Hazard label:	3
Classification Code:	F1
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

Inland waterways transport (ADN)

<u>UN number or ID number:</u>	UN 1294
<u>UN proper shipping name:</u>	TOLUENE
<u>Transport hazard class(es):</u>	3
<u>Packing group:</u>	II
Hazard label:	3
Classification Code:	F1
Limited quantity:	1 L
Excepted quantity:	E2

Marine transport (IMDG)

<u>UN number or ID number:</u>	UN 1294
<u>UN proper shipping name:</u>	TOLUENE
<u>Transport hazard class(es):</u>	3
<u>Packing group:</u>	II
Hazard label:	3
Special Provisions:	-
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

<u>UN number or ID number:</u>	UN 1294	
<u>UN proper shipping name:</u>	TOLUENE	
<u>Transport hazard class(es):</u>	3	
<u>Packing group:</u>	II	
Hazard label:	3	
Limited quantity Passenger:	1 L	
Passenger LQ:	Y341	
Excepted quantity:	E2	
IATA-packing instructions - Passenger:		353
IATA-max. quantity - Passenger:		5 L
IATA-packing instructions - Cargo:		364

CONOSTAN® Custom Blend Standard

Revision date: 09/12/2024

Product code: AC18.03246

Page 13 of 14

IATA-max. quantity - Cargo: 60 L

Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

15. Regulatory information
Safety, health and environmental regulations/legislation specific for the substance or mixture
EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 48, Entry 75

Information according to Directive 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

National regulatory information

Employment restrictions: Observe employment restrictions for young people. Observe employment restrictions for child bearing mothers and nursing. Observe employment restrictions for women of child-bearing age.

Water hazard class (D): 3 - highly hazardous to water

16. Other information
Abbreviations and acronyms

Flam. Liq. 2: Flammable liquids, category 2

Asp. Tox. 1: Aspiration hazard, category 1

Skin Irrit. 2: Skin irritation, category 2

Repr. 2: Reproductive toxicity, category 2

STOT SE 3: Specific target organ toxicity single exposure, category 3

STOT RE 2: Specific target organ toxicity repeated exposure, category 2

Aquatic Chronic 3: Chronic aquatic hazard, category 3

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Repr. 2; H361d	Calculation method
Skin Irrit. 2; H315	Calculation method
STOT SE 3; H336	Calculation method
STOT RE 2; H373	Calculation method
Asp. Tox. 1; H304	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H statements (full text)

H225	Highly flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness
H361d	Suspected of damaging the unborn child
H373	May cause damage to organs (central nervous system) through prolonged or repeated exposure if inhaled
H373	May cause damage to organs through prolonged or repeated exposure
H412	Harmful to aquatic life with long lasting effects

Other data

Provide appropriate information, instructions and training to users.

The above information describes exclusively the safety requirements of the product and is based on our

CONOSTAN® Custom Blend Standard

Revision date: 09/12/2024

Product code: AC18.03246

Page 14 of 14

present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)