

Conostan Single-Element Standard, Arsenic 100 ppm (As)

Revision date: 12/20/2024

Product code: AC18.05990

Page 2 of 12

2. Hazard(s) identification

Classification of the chemical

Regulation (EC) No 1272/2008

Asp. Tox. 1; H304

Full text of hazard statements: see SECTION 16.

Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

White mineral oil, petroleum

Signal word: Danger

Pictograms:



Hazard statements

H304 May be fatal if swallowed and enters airways

Precautionary statements

- P301+P310 If swallowed: Immediately call a poison center/doctor.
- P331 Do NOT induce vomiting.
- P405 Store locked up.
- P501 Dispose of contents/container to an appropriate recycling or disposal facility.

Hazards not otherwise classified

No data available

3. Composition/information on ingredients

Mixtures

Relevant ingredients

CAS No	Components			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
8042-47-5	White mineral oil, petroleum			95 - < 100 %
	232-455-8			
	Asp. Tox. 1; H304			
7440-38-2	arsenic			< 0.1 %
	231-148-6	033-001-00-X		
	Acute Tox. 3, Acute Tox. 3, Aquatic Acute 1, Aquatic Chronic 1; H331 H301 H400 H410			

Full text of H and EUH statements: see section 16.

Conostan Single-Element Standard, Arsenic 100 ppm (As)

Revision date: 12/20/2024

Product code: AC18.05990

Page 3 of 12

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Components	Quantity
		Specific Conc. Limits, M-factors and ATE	
8042-47-5	232-455-8	White mineral oil, petroleum	95 - < 100 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg	
7440-38-2	231-148-6	arsenic	< 0.1 %
		inhalation: ATE = 3 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); oral: ATE = 100 mg/kg	

Further Information

No data available

4. First-aid measures
Description of first aid measures
General information

No data available

After inhalation

Provide fresh air.

Call a physician immediately.

After contact with skin

Wash immediately with: Water, Soap

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

Most important symptoms and effects, both acute and delayed

Gastrointestinal complaints

Pneumonia

Vapors may cause drowsiness and dizziness.

Dizziness

Depression of central nervous system

Headache

Indication of any immediate medical attention and special treatment needed

Aspiration hazard

5. Fire-fighting measures
Extinguishing media
Suitable extinguishing media

Foam

 Carbon dioxide (CO₂)

Extinguishing powder

Water

Unsuitable extinguishing media

no restriction

Conostan Single-Element Standard, Arsenic 100 ppm (As)

Revision date: 12/20/2024

Product code: AC18.05990

Page 4 of 12

Specific hazards arising from the chemical

- Combustible liquids
- Hazardous combustion products
- In case of fire may be liberated:
- Carbon dioxide (CO₂)
- Carbon monoxide
- Metal oxide smoke, toxic
- In case of warming:
- Vapors are heavier than air, spread along floors and form explosive mixtures with air.

Special protective equipment and precautions for fire-fighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

- Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.
- Use water spray jet to protect personnel and to cool endangered containers.
- Move undamaged containers from immediate hazard area if it can be done safely.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

General advice

- In case of warming:
- Vapors are heavier than air, spread along floors and form explosive mixtures with air.
- Take precautionary measures against static discharges.

For non-emergency personnel

- Provide adequate ventilation.
- Use personal protection equipment.
- Avoid contact with skin, eyes and clothes.
- Remove persons to safety.
- Emergency procedures
- Consult an expert
- Do not breathe dust/fume/gas/mist/vapors/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment (PPE): see section 8

Environmental precautions

Do not allow to enter into surface water or drains.

Methods and material for containment and cleaning up

For containment

- Cover drains.
- Prevent spread over a wide area (e.g. by containment or oil barriers).
- Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).
- Collect in closed and suitable containers for disposal.

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

- Provide adequate ventilation.
- Do not breathe dust/fume/gas/mist/vapors/spray.
- Wear breathing apparatus if exposed to vapors/dusts/aerosols.

Reference to other sections

- Safe handling: see section 7
- Personal protection equipment (PPE): see section 8
- Disposal: see section 13

Conostan Single-Element Standard, Arsenic 100 ppm (As)

Revision date: 12/20/2024

Product code: AC18.05990

Page 5 of 12

7. Handling and storage

Precautions for safe handling

Advice on safe handling

- Read label before use. Handle and open container with care.
- When using do not eat, drink, smoke, sniff. Keep container tightly closed.
- Use personal protection equipment.
- Do not breathe vapor or spray.
- Use extractor hood (laboratory).
- Provide adequate ventilation.

Advice on protection against fire and explosion

- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Take precautionary measures against static discharges.
- In case of warming:
- Vapors are heavier than air, spread along floors and form explosive mixtures with air.

Advice on general occupational hygiene

- Keep away from food, drink and animal feedingstuffs.
- The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of the protective agents should be clarified with their suppliers.

Further information on handling

- Take off immediately all contaminated clothing and wash it before reuse.
- Draw up and observe skin protection programme.
- Wash hands and face before breaks and after work and take a shower if necessary.

Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

- Keep container tightly closed.

Hints on joint storage

- National regulations

Further information on storage conditions

- Keep cool. Protect from sunlight.

Specific end use(s)

- Laboratory chemicals
- Only for laboratory and analysis purposes.

8. Exposure controls/personal protection

Control parameters

Conostan Single-Element Standard, Arsenic 100 ppm (As)

Revision date: 12/20/2024

Product code: AC18.05990

Page 6 of 12

Exposure limits

CAS No	Substance	ppm	mg/m ³	Category	Origin
7440-38-2	Arsenic (inorganic compounds, as As)	-	C 0.002	15 min	REL
7440-38-2	Arsenic, organic compounds (as As)	-	0.5	TWA (8 h)	PEL
7440-38-2	Arsenic	-	0.01	TWA (8 h)	ACGIH-2025
-	Mineral oil, excluding metal working fluids (inhalable fraction); Pure, highly and severely refined	-	5	TWA (8 h)	ACGIH-2025
8012-95-1	Oil mist (mineral)	-	5	TWA (8 h)	REL
		-	10	STEL (15 min)	REL
8012-95-1	Oil mist, mineral	-	5	TWA (8 h)	PEL

Biological Exposure Indices (BEI-ACGIH)

CAS No	Substance	Determinant	Value	Test material	Sampling time
7440-38-2	ARSENIC, ELEMENTAL	Inorganic arsenic plus methylated metabolites (creatinine)	15 g/g	urine	End of workweek

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
8042-47-5	White mineral oil, petroleum			
	Worker DNEL, long-term	inhalation	systemic	160 mg/m ³
	Worker DNEL, long-term	dermal	systemic	220 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	35 mg/m ³
	Consumer DNEL, long-term	dermal	systemic	93 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	40 mg/kg bw/day

Additional advice on limit values

Observe in addition any national regulations!

Exposure controls
Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment
Eye/face protection

goggles

Face protection umbrella

Hand protection

Tested protective gloves must be worn

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Take off immediately all contaminated clothing and wash it before reuse.

Conostan Single-Element Standard, Arsenic 100 ppm (As)

Revision date: 12/20/2024

Product code: AC18.05990

Page 7 of 12

Wash hands and face before breaks and after work and take a shower if necessary .

Draw up and observe skin protection programme.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented. A respiratory protection program that meets OSHA's 29 CFR 1910.134 requirements must be followed whenever workplace conditions warrant a respirator's use.

Thermal hazards

No data available

Environmental exposure controls

Do not allow to enter into surface water or drains.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state:	Liquid
Color:	colorless
Odor:	like: Hydrocarbons
Odour threshold:	No data available
Melting point/freezing point:	No data available
Boiling point or initial boiling point and boiling range:	218-800 (424.4-1472°F) °C
Flammability:	No data available
Lower explosion limits:	No data available
Upper explosion limits:	No data available
Flash point:	No data available
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH-Value:	No data available
Viscosity / kinematic:	~20 mm ² /s
Water solubility:	No data available
Solubility in other solvents	
No data available	
Dissolution rate:	No data available
Partition coefficient n-octanol/water:	No data available
Dispersion stability:	No data available
Vapor pressure:	No data available
Vapor pressure:	No data available
Density:	No data available
Relative density:	No data available
Bulk density:	No data available
Relative vapour density:	No data available
Particle characteristics:	No data available

Other information

Information with regard to physical hazard classes

Explosive properties

In case of warming:

Vapors are heavier than air, spread along floors and form explosive mixtures with air.

Sustained combustibility:

No data available

Self-ignition temperature

Conostan Single-Element Standard, Arsenic 100 ppm (As)

Revision date: 12/20/2024

Product code: AC18.05990

Page 8 of 12

Solid: No data available
 Gas: No data available
 Oxidizing properties
 No data available

Other safety characteristics

Evaporation rate: No data available
 Solvent separation test: No data available
 Solvent content: 100%
 Solid content: No data available
 Sublimation point: No data available
 Softening point: No data available
 Pour point: No data available
 Viscosity / dynamic: No data available
 Flow time: No data available

Further Information

No data available

10. Stability and reactivity

Reactivity

In case of warming:
 Vapours may form explosive mixtures with air.

Chemical stability

The product is stable under storage at normal ambient temperatures.

Possibility of hazardous reactions

Oxidising agent

Conditions to avoid

Heat
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Incompatible materials

No data available

Hazardous decomposition products

in case of fire, see:
 SECTION 5: Fire fighting measures

Further information

No data available

11. Toxicological information

Information on toxicological effects

Toxicokinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Conostan Single-Element Standard, Arsenic 100 ppm (As)

Revision date: 12/20/2024

Product code: AC18.05990

Page 9 of 12

CAS No	Components				
	Exposure route	Dose	Species	Source	Method
8042-47-5	White mineral oil, petroleum				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1987)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rabbit	Study report (1987)	OECD Guideline 402
7440-38-2	arsenic				
	oral	ATE 100 mg/kg			
	inhalation vapour	ATE 3 mg/l			
	inhalation dust/mist	ATE 0,5 mg/l			

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitizing effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

Specific target organ toxicity (STOT) - single exposure

Based on available data, the classification criteria are not met.

Specific target organ toxicity (STOT) - repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways

Route(s) of Entry

No data available

Specific effects in experiment on an animal

No data available

Additional information on tests

There is no reliable information on carcinogenicity, mutagenicity, target organ toxicity or developmental toxicity.

Practical experience

No data available

Information on other hazards

Endocrine disrupting properties

This substance does not have endocrine disrupting properties with respect to non-target organisms.

Other information

No data available

Further information

Gastrointestinal complaints

Pneumonia

Vapors may cause drowsiness and dizziness.

Dizziness

Depression of central nervous system

Headache

Conostan Single-Element Standard, Arsenic 100 ppm (As)

Revision date: 12/20/2024

Product code: AC18.05990

Page 10 of 12

12. Ecological information

Ecotoxicity

Based on available data, the classification criteria are not met.

CAS No	Components					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
8042-47-5	White mineral oil, petroleum					
	Acute fish toxicity	LC50 > 10000 mg/l	96 h	Lepomis macrochirus	REACH Registration Dossier	Method: other: procedure as detailed in
	Acute crustacea toxicity	EC50 > 100 mg/l	48 h	Daphnia magna	Study report (2008)	OECD Guideline 202

Persistence and degradability

No data available

Bioaccumulative potential

Partition coefficient n-octanol/water

CAS No	Components	Log Pow
8042-47-5	White mineral oil, petroleum	> 6

Mobility in soil

No data available

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Other adverse effects

Do not allow to enter into surface water or drains.

Further information

Avoid release to the environment.

13. Disposal considerations

Waste treatment methods

Disposal recommendations

- Send to a physico-chemical treatment facility under observation of official regulations.
- Do not allow to enter into surface water or drains.
- Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

14. Transport information

Land transport (ADR/RID)

- UN number or ID number:** No dangerous good in sense of this transport regulation.
- UN proper shipping name:** No dangerous good in sense of this transport regulation.
- Transport hazard class(es):** No dangerous good in sense of this transport regulation.
- Packing group:** No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

Conostan Single-Element Standard, Arsenic 100 ppm (As)

Revision date: 12/20/2024

Product code: AC18.05990

Page 11 of 12

UN number or ID number: No dangerous good in sense of this transport regulation.
UN proper shipping name: No dangerous good in sense of this transport regulation.
Transport hazard class(es): No dangerous good in sense of this transport regulation.
Packing group: No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

UN number or ID number: No dangerous good in sense of this transport regulation.
UN proper shipping name: No dangerous good in sense of this transport regulation.
Transport hazard class(es): No dangerous good in sense of this transport regulation.
Packing group: No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

UN number or ID number: No dangerous good in sense of this transport regulation.
UN proper shipping name: No dangerous good in sense of this transport regulation.
Transport hazard class(es): No dangerous good in sense of this transport regulation.
Packing group: No dangerous good in sense of this transport regulation.

Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

Special precautions for user

No dangerous good in sense of this transport regulation.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No dangerous good in sense of this transport regulation.

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):
 Entry 3, Entry 75

Information according to Directive 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

National regulatory information

16. Other information

Abbreviations and acronyms

- Acute Tox. 3: Acute toxicity
- Asp. Tox. 1: Aspiration hazard
- Aquatic Acute 1: Acute aquatic hazard
- Aquatic Chronic 1: Chronic aquatic hazard

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008

Classification	Classification procedure
Asp. Tox. 1; H304	Calculation method

Relevant H statements (full text)

- H301 Toxic if swallowed
- H304 May be fatal if swallowed and enters airways
- H331 Toxic if inhaled
- H400 Very toxic to aquatic life
- H410 Very toxic to aquatic life with long lasting effects

Other data

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product

Conostan Single-Element Standard, Arsenic 100 ppm (As)

Revision date: 12/20/2024

Product code: AC18.05990

Page 12 of 12

named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

Provide appropriate information, instructions and training to users.

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	PC21	-	-	21	15	-	-	-	
2	PROC15	-	-	-	15	-	-	-	

LCS: Life cycle stages

PC: Product categories

ERC: Environmental release categories

TF: Technical functions

SU: Sectors of use

PROC: Process categories

AC: Article categories

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)