

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CONOSTAN Single Element Standard, 0.05% (500ppm) Sulfur in B20 [Biodiesel 20%]

Revision: 28.11.2024

Product code: AC18.06070

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

CONOSTAN Single Element Standard, 0.05% (500ppm) Sulfur in B20 [Biodiesel 20%]

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Reagents and laboratory chemicals
Only for laboratory and analysis purposes.

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Details of the supplier of the safety data sheet

Company name: AnalytiChem Services, Unipessoal, Lda
Street: Rua de Júlio Dinis 676 7º
Place: P-4050-320 Porto
Telephone: +351 226002917
E-mail: info@analytichem.com
Contact person: SDS service department
E-mail: SDS@analytichem.com
Internet: www.analytichem.com
Responsible Department: SDS service department

Supplier or manufacturer details

Company name: AnalytiChem Canada Inc.
Street: Québec, CANADA
21800 Clark Graham Ave
Place: CDN-H9X 4B6 Baie-D'Urfé
Telephone: +1 (800) 361-6820 Telefax: +1 (800) 253-5549
E-mail: info@analytichem.com
Contact person: SDS service department
E-mail: SDS@analytichem.com
Internet: www.analytichem.com
Responsible Department: AnalytiChem:
EU-Belgium: AnalytiChem Belgium, Industriezone "De Arend" 2, 8210 Zedelgem, Belgium, +32 50 28 83 20
EU-Germany: AnalytiChem Germany, Stempelstrasse 6, 47167 Duisburg, Germany, +49 203 51 94 – 200
EU-Netherlands: AnalytiChem Netherlands, Communicatieweg 7, 3641 SG Mijdrecht, The Netherlands, +31 297 286848
UK: AnalytiChem UK, Unit 7 Launton Business Center, Murdock Road, Bicester, OX26 4XB, England, +44 1869 355 500
USA: AnalytiChem USA, 227 China Road, Winslow, Maine, 04901, United States, +1 800-244-8378
Canada: AnalytiChem Canada, 21800 Clark Graham Avenue, Baie d'Urfe, H9X 4B6, Canada, +1 514-457-0701
Australia: ORE Research & Exploration Pty Ltd, 37A Hosie Street, Bayswater North, 3153, Australia, +61 3 9729 0333
+353 1 901 4670 (CHEMTREC)

1.4. Emergency telephone number:

Further Information

No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CONOSTAN Single Element Standard, 0.05% (500ppm) Sulfur in B20 [Biodiesel 20%]

Revision: 28.11.2024

Product code: AC18.06070

Page 2 of 11

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Asp. Tox. 1; H304

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

"Distillates (petroleum), hydro-treated light; Kerosine - unspecified"

Signal word: Danger

Pictograms:



Hazard statements

H304 May be fatal if swallowed and enters airways.

Precautionary statements

- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
- P331 Do NOT induce vomiting.
- P405 Store locked up.
- P501 Dispose of contents/container to hazardous or special waste collection point.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Biodiesel

Relevant ingredients

CAS No	Chemical name	Quantity
	EC No Index No REACH No	
	Classification (Regulation (EC) No 1272/2008)	
64742-47-8	"Distillates (petroleum), hydro-treated light; Kerosine - unspecified"	75 - < 80 %
	265-149-8 649-422-00-2	
	Asp. Tox. 1; H304	
61788-61-2	Fatty acids, tallow, methyl esters	10 - < 15 %
	262-989-7	
68990-52-3	Vegetable fatty acid methyl ester	10 - < 15 %
	273-606-8 01-2119485821-32	

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CONOSTAN Single Element Standard, 0.05% (500ppm) Sulfur in B20 [Biodiesel 20%]

Revision: 28.11.2024

Product code: AC18.06070

Page 3 of 11

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64742-47-8	265-149-8	"Distillates (petroleum), hydro-treated light; Kerosine - unspecified"	75 - < 80 %
		inhalation: LC50 = > 5,28 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg	
68990-52-3	273-606-8	Vegetable fatty acid methyl ester	10 - < 15 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg	

Further Information

No data available

SECTION 4: First aid measures
4.1. Description of first aid measures
General information

No data available

After inhalation

Provide fresh air.

Call a doctor if you feel unwell.

After contact with skin

Wash immediately with: Water, Soap

Take off immediately all contaminated clothing and wash it before reuse.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

Remove contact lenses, if present and easy to do. Continue rinsing.

In case of eye irritation consult an ophthalmologist.

After ingestion

Rinse mouth.

Do NOT induce vomiting.

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No data available

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures
5.1. Extinguishing media
Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Combustible liquids

Hazardous combustion products

In case of fire may be liberated:

 Carbon dioxide (CO₂)

Carbon monoxide

Sulphur oxides

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CONOSTAN Single Element Standard, 0.05% (500ppm) Sulfur in B20 [Biodiesel 20%]

Revision: 28.11.2024

Product code: AC18.06070

Page 4 of 11

In case of warming:

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Use water spray jet to protect personnel and to cool endangered containers.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

In case of warming:

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Take precautionary measures against static discharges.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe vapour/aerosol.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Collect in closed and suitable containers for disposal.

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe vapour/aerosol.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Handle and open container with care.

When using do not eat, drink, smoke, sniff.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CONOSTAN Single Element Standard, 0.05% (500ppm) Sulfur in B20 [Biodiesel 20%]

Revision: 28.11.2024

Product code: AC18.06070

Page 5 of 11

Keep container tightly closed.
 Use personal protection equipment.
 Use extractor hood (laboratory).
 Do not breathe vapour/aerosol.
 Provide adequate ventilation.

Advice on protection against fire and explosion

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 Take precautionary measures against static discharges.
 In case of warming:
 Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.
 The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.
 Draw up and observe skin protection programme.
 Wash hands and face before breaks and after work and take a shower if necessary.

7.2. Conditions for safe storage, including any incompatibilities
Requirements for storage rooms and vessels

Keep container tightly closed.

Hints on joint storage

National regulations

Further information on storage conditions

Keep cool. Protect from sunlight.

7.3. Specific end use(s)

Laboratory chemicals
 Only for laboratory and analysis purposes.

SECTION 8: Exposure controls/personal protection
8.1. Control parameters
Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
-	Mineral Oil pure, highly & severely refined (Inhalable)	-	5		TWA (8 h)	

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
68990-52-3	Vegetable fatty acid methyl ester			
Worker DNEL, long-term		inhalation	systemic	49,3 mg/m ³
Worker DNEL, long-term		dermal	systemic	14 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	8,7 mg/m ³
Consumer DNEL, long-term		dermal	systemic	5 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	5 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CONOSTAN Single Element Standard, 0.05% (500ppm) Sulfur in B20 [Biodiesel 20%]

Revision: 28.11.2024

Product code: AC18.06070

Page 6 of 11

PNEC values

CAS No	Substance	
Environmental compartment		Value
68990-52-3	Vegetable fatty acid methyl ester	
Freshwater		2,504 mg/l
Freshwater (intermittent releases)		25,04 mg/l
Marine water		0,25 mg/l
Freshwater sediment		10,4 mg/kg
Marine sediment		1,04 mg/kg
Micro-organisms in sewage treatment plants (STP)		520 mg/l

Additional advice on limit values

Observe in addition any national regulations!

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Face protection umbrella

Hand protection

Tested protective gloves must be worn

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Take off immediately all contaminated clothing and wash it before reuse.

Wash hands and face before breaks and after work and take a shower if necessary.

Draw up and observe skin protection programme.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Thermal hazards

No data available

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	amber	
Odour:	like: SULPHUR	
Odour threshold:	No data available	
Melting point/freezing point:		No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CONOSTAN Single Element Standard, 0.05% (500ppm) Sulfur in B20 [Biodiesel 20%]

Revision: 28.11.2024

Product code: AC18.06070

Page 7 of 11

Boiling point or initial boiling point and boiling range:	~200 °C
Flammability:	No data available
Lower explosion limits:	No data available
Upper explosion limits:	No data available
Flash point:	No data available
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH-Value:	No data available
Viscosity / kinematic:	No data available
Water solubility:	No data available
Solubility in other solvents	
No data available	
Dissolution rate:	No data available
Partition coefficient n-octanol/water:	No data available
Dispersion stability:	No data available
Vapour pressure:	No data available
Vapour pressure:	No data available
Density (at 25 °C):	0.8051 g/cm ³
Relative density:	No data available
Bulk density:	No data available
Relative vapour density:	No data available
Particle characteristics:	No data available

9.2. Other information
Information with regard to physical hazard classes

Explosive properties

In case of warming:

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustained combustibility:

No data available

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate:

No data available

Solvent separation test:

No data available

Solvent content:

100%

Solid content:

0%

Sublimation point:

No data available

Softening point:

No data available

Pour point:

No data available

No data available

Viscosity / dynamic:

No data available

Flow time:

No data available

Further Information

No data available

SECTION 10: Stability and reactivity

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CONOSTAN Single Element Standard, 0.05% (500ppm) Sulfur in B20 [Biodiesel 20%]

Revision: 28.11.2024

Product code: AC18.06070

Page 8 of 11

10.1. Reactivity

In case of warming:
Vapours may form explosive mixtures with air.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent

10.4. Conditions to avoid

Heat
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

in case of fire, see:
SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information
11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008
Toxicokinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-47-8	"Distillates (petroleum), hydro-treated light; Kerosine - unspecified"				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1992)	EPA OTS 798.1175
	dermal	LD50 > 2000 mg/kg	Rabbit	Study report (1992)	EPA OTS 798.1100
	inhalation (4 h) vapour	LC50 > 5,28 mg/l	Rat	Study report (1987)	OECD Guideline 403
68990-52-3	Vegetable fatty acid methyl ester				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1984)	other: AFNOR NF T 03-021
	dermal	LD50 > 2000 mg/kg	Rabbit	Study report (1994)	EPA OPPTS 870.1200

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.
Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CONOSTAN Single Element Standard, 0.05% (500ppm) Sulfur in B20 [Biodiesel 20%]

Revision: 28.11.2024

Product code: AC18.06070

Page 9 of 11

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

Information on likely routes of exposure

There are no data available on the mixture itself.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.

11.2. Information on other hazards
Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Other information

No data available

Further information

No data available

SECTION 12: Ecological information
12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64742-47-8	"Distillates (petroleum), hydro-treated light; Kerosine - unspecified"					
	Acute fish toxicity	LL50 2 - 5 mg/l	96 h	Oncorhynchus mykiss	Study report (1994)	OECD Guideline 203
	Acute algae toxicity	ErC50 8,3 mg/l	72 h	Raphidocelis subcapitata	Study report (1995)	OECD Guideline 201
	Acute crustacea toxicity	EL50 1,4 mg/l	48 h	Daphnia magna	Study report (1995)	OECD Guideline 202
68990-52-3	Vegetable fatty acid methyl ester					
	Acute algae toxicity	ErC50 ca. 73729 mg/l	72 h	Raphidocelis subcapitata	REACH Registration Dossier	EU Method C.3
	Acute crustacea toxicity	EC50 ca. 2504 mg/l	48 h	Daphnia magna	REACH Registration Dossier	EU Method C.2

12.2. Persistence and degradability

There are no data available on the mixture itself.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CONOSTAN Single Element Standard, 0.05% (500ppm) Sulfur in B20 [Biodiesel 20%]

Revision: 28.11.2024

Product code: AC18.06070

Page 10 of 11

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
68990-52-3	Vegetable fatty acid methyl ester	> 6,2

BCF

CAS No	Chemical name	BCF	Species	Source
68990-52-3	Vegetable fatty acid methyl ester	ca. 3	Mitylus edulis	Study report (1997)

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Do not allow to enter into surface water or drains.

Further information

There are no data available on the mixture itself.

SECTION 13: Disposal considerations
13.1. Waste treatment methods
Disposal recommendations

Send to a physico-chemical treatment facility under observation of official regulations .

Do not allow to enter into surface water or drains.

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information
Land transport (ADR/RID)

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
--------------------------------------	--

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CONOSTAN Single Element Standard, 0.05% (500ppm) Sulfur in B20 [Biodiesel 20%]

Revision: 28.11.2024

Product code: AC18.06070

Page 11 of 11

14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.

14.4. Packing group: No dangerous good in sense of this transport regulation.

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

Information according to Directive

Not subject to 2012/18/EU (SEVESO III)

2012/18/EU (SEVESO III):

National regulatory information

SECTION 16: Other information

Abbreviations and acronyms

Asp. Tox. 1: Aspiration hazard, hazard category 1

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Asp. Tox. 1; H304	Calculation method

Relevant H and EUH statements (number and full text)

H304 May be fatal if swallowed and enters airways.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

Provide appropriate information, instructions and training to users

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)