



**CONOSTAN® Total Acid Number Standard 10 mg/g KOH**

Revision date: 08/09/2024

Product code: AC18.06653

Page 2 of 13

**2. Hazard(s) identification**

**Classification of the chemical**

Regulation (EC) No 1272/2008

Asp. Tox. 1; H304

Full text of hazard statements: see SECTION 16.

**Label elements**

Regulation (EC) No 1272/2008

**Hazard components for labelling**

"Distillates (petroleum), hydro-treated light; Kerosine - unspecified"

Signal word: Danger

**Pictograms:**



**Hazard statements**

H304 May be fatal if swallowed and enters airways

**Precautionary statements**

- P301+P310 If swallowed: Immediately call a poison center/doctor.
- P331 Do NOT induce vomiting.
- P405 Store locked up.

**Hazards not otherwise classified**

No data available

**3. Composition/information on ingredients**

**Mixtures**

**Relevant ingredients**

CAS No	Components			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
8042-47-5	White mineral oil, petroleum			45 - < 50 %
	232-455-8			
64742-47-8	"Distillates (petroleum), hydro-treated light; Kerosine - unspecified"			45 - < 50 %
	265-149-8	649-422-00-2		
	Asp. Tox. 1; H304			
67-63-0	propan-2-ol			1 - < 5 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			

Full text of H and EUH statements: see section 16.

**CONOSTAN® Total Acid Number Standard 10 mg/g KOH**

Revision date: 08/09/2024

Product code: AC18.06653

Page 3 of 13

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Components	Quantity
		Specific Conc. Limits, M-factors and ATE	
8042-47-5	232-455-8	White mineral oil, petroleum	45 - < 50 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg	
64742-47-8	265-149-8	"Distillates (petroleum), hydro-treated light; Kerosine - unspecified"	45 - < 50 %
		inhalation: LC50 = > 5,28 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg	

**Further Information**

No data available

**4. First-aid measures**
**Description of first aid measures**
**General information**

No data available

**After inhalation**

Provide fresh air.

Call a doctor if you feel unwell.

**After contact with skin**

Wash immediately with: Water, Soap

Take off immediately all contaminated clothing and wash it before reuse.

In case of skin irritation, consult a physician.

**After contact with eyes**

Rinse immediately carefully and thoroughly with eye-bath or water.

Remove contact lenses, if present and easy to do. Continue rinsing.

In case of eye irritation consult an ophthalmologist.

**After ingestion**

Rinse mouth.

Do NOT induce vomiting.

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

**Most important symptoms and effects, both acute and delayed**

Gastrointestinal complaints

Pneumonia

Vapors may cause drowsiness and dizziness.

Dizziness

Depression of central nervous system

Headache

**Indication of any immediate medical attention and special treatment needed**

No data available

**5. Fire-fighting measures**
**Extinguishing media**
**Suitable extinguishing media**

Foam

 Carbon dioxide (CO<sub>2</sub>)

Extinguishing powder

Water

**CONOSTAN® Total Acid Number Standard 10 mg/g KOH**

Revision date: 08/09/2024

Product code: AC18.06653

Page 4 of 13

**Unsuitable extinguishing media**

no restriction

**Specific hazards arising from the chemical**

Combustible liquids

Hazardous combustion products

In case of fire may be liberated:

 Carbon dioxide (CO<sub>2</sub>)

Carbon monoxide

In case of warming:

Vapors are heavier than air, spread along floors and form explosive mixtures with air.

**Special protective equipment and precautions for fire-fighters**

In case of fire: Wear self-contained breathing apparatus.

**Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Use water spray jet to protect personnel and to cool endangered containers.

Move undamaged containers from immediate hazard area if it can be done safely.

**6. Accidental release measures**
**Personal precautions, protective equipment and emergency procedures**
**General advice**

In case of warming:

Vapors are heavier than air, spread along floors and form explosive mixtures with air.

Take precautionary measures against static discharges.

**For non-emergency personnel**

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapors/spray.

**For emergency responders**

Precautionary statements For emergency responders : Personal protection equipment (PPE): see section 8

**Environmental precautions**

Do not allow to enter into surface water or drains.

**Methods and material for containment and cleaning up**
**For containment**

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Collect in closed and suitable containers for disposal.

**For cleaning up**

Clean contaminated articles and floor according to the environmental legislation.

**Other information**

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear breathing apparatus if exposed to vapors/dusts/aerosols.

**Reference to other sections**

Safe handling: see section 7

**CONOSTAN® Total Acid Number Standard 10 mg/g KOH**

Revision date: 08/09/2024

Product code: AC18.06653

Page 5 of 13

Personal protection equipment (PPE): see section 8

Disposal: see section 13

**7. Handling and storage**
**Precautions for safe handling**
**Advice on safe handling**

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe vapor or spray.

Provide adequate ventilation.

**Advice on protection against fire and explosion**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Take precautionary measures against static discharges.

In case of warming:

Vapors are heavier than air, spread along floors and form explosive mixtures with air.

**Advice on general occupational hygiene**

Keep away from food, drink and animal feedingstuffs.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of the protective agents should be clarified with their suppliers.

**Further information on handling**

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

**Conditions for safe storage, including any incompatibilities**
**Requirements for storage rooms and vessels**

Keep container tightly closed.

**Hints on joint storage**

National regulations

**Further information on storage conditions**

Keep cool. Protect from sunlight.

**Specific end use(s)**

Laboratory chemicals

Only for laboratory and analysis purposes.

**8. Exposure controls/personal protection**
**Control parameters**

**CONOSTAN® Total Acid Number Standard 10 mg/g KOH**

Revision date: 08/09/2024

Product code: AC18.06653

Page 6 of 13

**Exposure limits**

CAS No	Substance	ppm	mg/m <sup>3</sup>	Category	Origin
67-63-0	2-Propanol	200	491	TWA (8 h)	ACGIH-2025
		400	984	STEL (15 min)	ACGIH-2025
67-63-0	Isopropyl alcohol	400	980	TWA (8 h)	REL
		400	980	TWA (8 h)	REL
		500	1225	STEL (15 min)	REL
-	Mineral oil, excluding metal working fluids (inhalable fraction); Pure, highly and severely refined		5	TWA (8 h)	ACGIH-2025
8012-95-1	Oil mist (mineral)	-	5	TWA (8 h)	REL
		-	10	STEL (15 min)	REL
8012-95-1	Oil mist, mineral	-	5	TWA (8 h)	REL

**Biological Exposure Indices (BEI-ACGIH)**

CAS No	Substance	Determinant	Value	Test material	Sampling time
67-63-0	2-PROPANOL	Acetone	40 mg/L	urine	End of shift at end of workweek

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
8042-47-5	White mineral oil, petroleum			
	Worker DNEL, long-term	inhalation	systemic	160 mg/m <sup>3</sup>
	Worker DNEL, long-term	dermal	systemic	220 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	35 mg/m <sup>3</sup>
	Consumer DNEL, long-term	dermal	systemic	93 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	40 mg/kg bw/day
67-63-0	propan-2-ol			
	Worker DNEL, long-term	inhalation	systemic	500 mg/m <sup>3</sup>
	Worker DNEL, long-term	dermal	systemic	888 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	89 mg/m <sup>3</sup>
	Consumer DNEL, long-term	dermal	systemic	319 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	26 mg/kg bw/day

**CONOSTAN® Total Acid Number Standard 10 mg/g KOH**

Revision date: 08/09/2024

Product code: AC18.06653

Page 7 of 13

**PNEC values**

CAS No	Substance	
Environmental compartment		Value
67-63-0	propan-2-ol	
Freshwater		140,9 mg/l
Freshwater (intermittent releases)		140,9 mg/l
Marine water		140,9 mg/l
Freshwater sediment		552 mg/kg
Marine sediment		552 mg/kg
Secondary poisoning		160 mg/kg
Micro-organisms in sewage treatment plants (STP)		2251 mg/l
Soil		28 mg/kg

**Additional advice on limit values**

Observe in addition any national regulations!

**Exposure controls**
**Appropriate engineering controls**

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

**Individual protection measures, such as personal protective equipment**
**Eye/face protection**

goggles

Face protection umbrella

**Hand protection**

Tested protective gloves must be worn

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

**Skin protection**

Take off immediately all contaminated clothing and wash it before reuse.

Wash hands and face before breaks and after work and take a shower if necessary.

Draw up and observe skin protection programme.

**Respiratory protection**

Respiratory protection necessary at: aerosol or mist formation

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented. A respiratory protection program that meets OSHA's 29 CFR 1910.134 requirements must be followed whenever workplace conditions warrant a respirator's use.

**Thermal hazards**

No data available

**Environmental exposure controls**

Do not allow to enter into surface water or drains.

**9. Physical and chemical properties**
**Information on basic physical and chemical properties**

Physical state:

Liquid

**CONOSTAN® Total Acid Number Standard 10 mg/g KOH**

Revision date: 08/09/2024

Product code: AC18.06653

Page 8 of 13

Color:	colorless	
Odor:	like: Hydrocarbons	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		227-288 °C
Flammability:		No data available
Lower explosion limits:		No data available
Upper explosion limits:		No data available
Flash point:		No data available
Auto-ignition temperature:		No data available
Decomposition temperature:		No data available
pH-Value:		No data available
Viscosity / kinematic:		No data available
Water solubility:		No data available
Solubility in other solvents		
No data available		
Dissolution rate:		No data available
Partition coefficient n-octanol/water:		No data available
Dispersion stability:		No data available
Vapor pressure:		No data available
Vapor pressure:		No data available
Density:		0,79-0,84 g/cm <sup>3</sup>
Relative density:		No data available
Bulk density:		No data available
Relative vapour density:		No data available
Particle characteristics:		No data available

**Other information**

**Information with regard to physical hazard classes**

Explosive properties

    In case of warming:

        Vapors are heavier than air, spread along floors and form explosive mixtures with air.

Sustained combustibility:

No data available

Self-ignition temperature

    Solid:

No data available

    Gas:

No data available

Oxidizing properties

    No data available

**Other safety characteristics**

Evaporation rate:

No data available

Solvent separation test:

No data available

Solvent content:

No data available

Solid content:

No data available

Sublimation point:

No data available

Softening point:

No data available

Pour point:

No data available

No data available

Viscosity / dynamic:

No data available

Flow time:

No data available

**Further Information**

**CONOSTAN® Total Acid Number Standard 10 mg/g KOH**

Revision date: 08/09/2024

Product code: AC18.06653

Page 9 of 13

No data available

**10. Stability and reactivity**
**Reactivity**

In case of warming:  
Vapours may form explosive mixtures with air.

**Chemical stability**

The product is stable under storage at normal ambient temperatures.

**Possibility of hazardous reactions**

Oxidising agent

**Conditions to avoid**

Heat  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Incompatible materials**

No data available

**Hazardous decomposition products**

in case of fire, see:  
SECTION 5: Fire fighting measures

**Further information**

No data available

**11. Toxicological information**
**Information on toxicological effects**
**Toxicokinetics, metabolism and distribution**

No data available

**Acute toxicity**

Based on available data, the classification criteria are not met.

**ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Components				
	Exposure route	Dose	Species	Source	Method
8042-47-5	White mineral oil, petroleum				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1987)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rabbit	Study report (1987)	OECD Guideline 402
64742-47-8	"Distillates (petroleum), hydro-treated light; Kerosine - unspecified"				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1992)	EPA OTS 798.1175
	dermal	LD50 > 2000 mg/kg	Rabbit	Study report (1992)	EPA OTS 798.1100
	inhalation (4 h) vapour	LC50 > 5,28 mg/l	Rat	Study report (1987)	OECD Guideline 403

**CONOSTAN® Total Acid Number Standard 10 mg/g KOH**

Revision date: 08/09/2024

Product code: AC18.06653

Page 10 of 13

**Irritation and corrosivity**

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

**Sensitizing effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

**Specific target organ toxicity (STOT) - single exposure**

Based on available data, the classification criteria are not met.

**Specific target organ toxicity (STOT) - repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

May be fatal if swallowed and enters airways

**Route(s) of Entry**

No data available

**Specific effects in experiment on an animal**

No data available

**Additional information on tests**

No data available

**Practical experience**

No data available

**Information on other hazards**

**Endocrine disrupting properties**

No data available

**Other information**

No data available

**Further information**

Gastrointestinal complaints

Pneumonia

Vapors may cause drowsiness and dizziness.

Dizziness

Depression of central nervous system

Headache

**12. Ecological information**

**Ecotoxicity**

Based on available data, the classification criteria are not met.

**CONOSTAN® Total Acid Number Standard 10 mg/g KOH**

Revision date: 08/09/2024

Product code: AC18.06653

Page 11 of 13

CAS No	Components					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
8042-47-5	White mineral oil, petroleum					
	Acute fish toxicity	LC50 > 10000 mg/l	96 h	Lepomis macrochirus	REACH Registration Dossier	Method: other: procedure as detailed in
	Acute crustacea toxicity	EC50 > 100 mg/l	48 h	Daphnia magna	Study report (2008)	OECD Guideline 202
64742-47-8	"Distillates (petroleum), hydro-treated light; Kerosine - unspecified"					
	Acute fish toxicity	LL50 2 - 5 mg/l	96 h	Oncorhynchus mykiss	Study report (1994)	OECD Guideline 203
	Acute algae toxicity	ErC50 8,3 mg/l	72 h	Raphidocelis subcapitata	Study report (1995)	OECD Guideline 201
	Acute crustacea toxicity	EL50 1,4 mg/l	48 h	Daphnia magna	Study report (1995)	OECD Guideline 202
67-63-0	propan-2-ol					
	Acute fish toxicity	LC50 10000 mg/l	96 h	Pimephales promelas	Publication (1983)	OECD Guideline 203

**Persistence and degradability**

No data available

**Bioaccumulative potential**
**Partition coefficient n-octanol/water**

CAS No	Components	Log Pow
8042-47-5	White mineral oil, petroleum	> 6
67-63-0	propan-2-ol	0,05

**Mobility in soil**

No data available

**Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**Other adverse effects**

Do not allow to enter into surface water or drains.

**Further information**

Avoid release to the environment.

**13. Disposal considerations**
**Waste treatment methods**
**Disposal recommendations**

Send to a physico-chemical treatment facility under observation of official regulations.

Do not allow to enter into surface water or drains.

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

**Contaminated packaging**

Handle contaminated packages in the same way as the substance itself.

**CONOSTAN® Total Acid Number Standard 10 mg/g KOH**

Revision date: 08/09/2024

Product code: AC18.06653

Page 12 of 13

**14. Transport information**
**Land transport (ADR/RID)**

<b>UN number or ID number:</b>	UN 1993
<b>UN proper shipping name:</b>	FLAMMABLE LIQUID, N.O.S. (propan-2-ol)
<b>Transport hazard class(es):</b>	3
<b>Packing group:</b>	III
Hazard label:	3
Classification Code:	F1
Special Provisions:	274 601
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	30
Tunnel restriction code:	D/E

**Inland waterways transport (ADN)**

<b>UN number or ID number:</b>	UN 1993
<b>UN proper shipping name:</b>	FLAMMABLE LIQUID, N.O.S. (propan-2-ol)
<b>Transport hazard class(es):</b>	3
<b>Packing group:</b>	III
Hazard label:	3
Classification Code:	F1
Special Provisions:	274 601
Limited quantity:	5 L
Excepted quantity:	E1

**Marine transport (IMDG)**

<b>UN number or ID number:</b>	UN 1993
<b>UN proper shipping name:</b>	FLAMMABLE LIQUID, N.O.S. (propan-2-ol)
<b>Transport hazard class(es):</b>	3
<b>Packing group:</b>	III
Hazard label:	3
Special Provisions:	223 274 955
Limited quantity:	5 L
Excepted quantity:	E1
EmS:	F-E, S-E

**Air transport (ICAO-TI/IATA-DGR)**

<b>UN number or ID number:</b>	UN 1993
<b>UN proper shipping name:</b>	FLAMMABLE LIQUID, N.O.S. (propan-2-ol)
<b>Transport hazard class(es):</b>	3
<b>Packing group:</b>	III
Hazard label:	3
Special Provisions:	A3
Limited quantity Passenger:	10 L
Passenger LQ:	Y344
Excepted quantity:	E1
IATA-packing instructions - Passenger:	355
IATA-max. quantity - Passenger:	60 L
IATA-packing instructions - Cargo:	366
IATA-max. quantity - Cargo:	220 L

**Environmental hazards**

ENVIRONMENTALLY HAZARDOUS:	No
----------------------------	----

**CONOSTAN® Total Acid Number Standard 10 mg/g KOH**

Revision date: 08/09/2024

Product code: AC18.06653

Page 13 of 13

**Special precautions for user**

No dangerous good in sense of this transport regulation.

**15. Regulatory information**

**Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Information according to Directive 2012/18/EU (SEVESO III):

Not subject to 2012/18/EU (SEVESO III)

**National regulatory information**

Water hazard class (D):

2 - obviously hazardous to water

**16. Other information**

**Abbreviations and acronyms**

Flam. Liq. 2: Flammable liquids

Asp. Tox. 1: Aspiration hazard

Eye Irrit. 2: Eye irritation

STOT SE 3: Specific target organ toxicity single exposure

**Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008**

Classification	Classification procedure
Asp. Tox. 1; H304	Calculation method

**Relevant H statements (full text)**

- H225 Highly flammable liquid and vapor
- H304 May be fatal if swallowed and enters airways
- H319 Causes serious eye irritation
- H336 May cause drowsiness or dizziness

**Other data**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

Provide appropriate information, instructions and training to users.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*